


# Keysight HMMC-1002

## DC–50 GHz Variable Attenuator

1GG7-8001

Data Sheet




### Features

- Specified frequency range:  
DC to 26.5 GHz
- Return loss: 10 dB
- Minimum attenuation: 2.0 dB
- Maximum attenuation: 30.0 dB

## Description

The HMMC-1002 is a monolithic, voltage variable, GaAs IC attenuator that operates from DC to 50 GHz. It is fabricated using WPTC's MMICB process which features an MBE epitaxial layer, backside ground vias, and FET gate lengths of approximately 0.4  $\mu\text{m}$ . The variable resistive elements of the HMMC-1002 are two 750  $\mu\text{m}$  wide series FETs and four 200  $\mu\text{m}$  wide shunt FETs. The distributed topology of the HMMC-1002 minimizes the parasitic effects of its series and shunt FETs, allowing the HMMC-1002 to exhibit a wide dynamic range across its full bandwidth. An on-chip DC reference circuit may be used to maintain optimum VSWR for any attenuation setting or to improve the attenuation versus voltage linearity of the attenuator circuit.



Chip size:

1470 x 610  $\mu\text{m}$  (57.9 x 24.0 mils)

Chip size tolerance:

$\pm 10 \mu\text{m}$  ( $\pm 0.4$  mils)

Chip thickness:

$127 \pm 15 \mu\text{m}$  ( $5.0 \pm 0.6$  mils)

RF pad dimensions:

60 x 70  $\mu\text{m}$  (2.4 x 2.8 mils) or larger

DC pad dimensions:

75 x 75  $\mu\text{m}$  (3.0 x 3.0 mils) or larger

## Absolute Maximum Ratings<sup>1</sup>

Symbol	Parameters/conditions	Minimum	Maximum	Units
$V_{\text{DC-RF}}$	DC voltage to RF ports	-0.6	+1.6	Volts
$V_1$	$V_1$ control voltage	-5.0	+0.5	Volts
$V_2$	$V_2$ control voltage	-5.0	+0.5	Volts
$V_{\text{DC}}$	DC in/DC out	-0.6	+1.0	Volts
$P_{\text{in}}$	RF input power		17	dBm
$T_{\text{mina}}$	Minimum ambient operating temperature	-55		$^{\circ}\text{C}$
$T_{\text{maxa}}$	Maximum ambient operating temperature		+125	$^{\circ}\text{C}$
$T_{\text{stg}}$	Storage temperature	-65	+165	$^{\circ}\text{C}$
$T_{\text{max}}$	Maximum assembly temperature (for 60 seconds maximum)		+300	$^{\circ}\text{C}$

1. Operation in excess of any one of these conditions may result in damage to this device

## DC Specifications/Physical Properties

( $T_A = 25\text{ }^\circ\text{C}$ )

Symbol	Parameters/conditions	Minimum	Typical	Maximum	Units
$I_{V1}$	$V_1$ control current, ( $V_1 = -4\text{ V}$ )	5.3	9.3	12	mA
$I_{V2}$	$V_2$ control current, ( $V_2 = -4\text{ V}$ )	5.3	9.3	12	mA
$V_p$	Pinch-off voltage, ( $V_2, W/V_1 = 0\text{ V}$ ) (Four 200 $\mu\text{m}$ wide shunt FETs, $V_{DD} = 1\text{ V}$ @ $R_{F_{in}}, I_{DD} = 5\text{ mA}$ )	-0.6	-1.3	-2.5	Volts

## Electrical Specifications<sup>1</sup>

( $T_A = 25\text{ }^\circ\text{C}$ ,  $Z_0 = 50\text{ }\Omega$ )

Parameters/conditions	Frequency (GHz)	Minimum	Typical	Maximum	Units
Minimum attenuation, $ S_{21} $ ( $V_1 = 0\text{ V}, V_2 = -4\text{ V}$ )	1.5		1.0	2.4	dB
	8.0		1.4	2.4	dB
	20.00		1.7	2.4	dB
	26.5		2.0	2.4	dB
	50.0		3.9		dB
Input/output return loss @ minimum attenuation setting, ( $V_1 = 0\text{ V}, V_2 = -4\text{ V}$ )	< 26.5	10	16		dB
	< 50.0		8		dB
Maximum attenuation $ S_{21} $ ( $V_1 = -4\text{ V}, V_2 = 0\text{ V}$ )	1.5	27	30		dB
	8.0	27	38		dB
	20.0	27	38		dB
	26.5	27	40		dB
	50.0		35		dB
Input/output return loss @ maximum attention setting, ( $V_1 = -4\text{ V}, V_2 = 0\text{ V}$ )	< 26.5	8	10		dB
	< 50.0		10		dB
DC power dissipation, ( $V_1 = -5\text{ V}, V_2 = -5\text{ V}$ ) (does not include input signals)				152	mW

1. Attenuation is a positive number; whereas,  $S_{21}$  as measured on a network analyzer would be a negative number.

## Applications

The HMMC-1002 is designed to be used as a gain control block in an ALC assembly. Because of its wide dynamic range and return loss performance, the HMMC-1002 may also be used as a broadband pulse modulator or single-pole single-throw, non-reflective switch.

## Operation

The attenuation value of the HMMC-1002 is adjusted by applying negative voltage to V<sub>2</sub>. At any attenuation setting, optimum VSWR is obtained by applying negative voltage to V<sub>1</sub>. Applying negative voltage (V<sub>2</sub>) to the gates of the shunt FETs sets the source-to-drain resistance and establishes the attenuation level. Applying negative voltage (V<sub>1</sub>) to the gates of the series FETs optimizes the input and output match for different attenuation settings. In some applications, a single setting of V<sub>1</sub> may provide sufficient input and output match over the desired attenuation range (V<sub>2</sub>). For any HMMC-1002 the values of V<sub>1</sub> may be adjusted so that the device attenuation versus voltage is monotonic for both V<sub>1</sub> and V<sub>2</sub>; however, this will slightly degrade the input and output return loss.

The attenuation and input/output match of the HMMC-1002 may also be controlled using only a single input voltage by utilizing the on-chip DC reference circuit and the driver circuit shown in Figure 4. This circuit optimizes VSWR for any attenuation setting. Because of process variations, the values of V<sub>REF</sub>, R<sub>REF</sub>, and R<sub>L</sub> are different for each wafer if optimum performance is required. Typical values for these elements are given. The ratio of the resistors R<sub>1</sub> and R<sub>2</sub> determines the sensitivity of the attenuation versus voltage performance of the attenuator.

## Assembly Techniques

GaAs MMICs are ESD sensitive. ESD preventive measures must be employed in all aspects of storage, handling, and assembly.

MMIC ESD precautions, handling considerations, die attach and bonding methods are critical factors in successful GaAs MMIC performance and reliability.

The Keysight Technologies, Inc. application note *GaAs MMIC ESD, Die Attach and Bonding Guidelines*, literature number 5991-3484EN, provides basic information on these subjects.

## Additional References

*2-26.5 Variable Gain Amplifier Using HMMC-5021/22/26 and HMMC-1002 GaAs MMIC Components*, Application Note, literature number 5991-3543EN

*HMMC-1002 Attenuator: Attenuation Control*, Application Note, literature number 5991-3555EN

*DC-50 GHz Variable Attenuator: S-Parameters*, Application Note, literature number 5991-3556EN

*HMMC-1002 DC-50 GHz Variable Attenuator: Switching Speed Limitations*, Application Note, literature number 5991-3557EN

*HMMC-1002 50 GHz Attenuator 0-50 GHz Performance*, Technical Overview, literature number 5991-3554EN




Figure 1. Schematic




Figure 2. Bonding pad locations

Notes:

- 1) All dimensions in microns and shown to center of bond pad.
- 2)  $DC_{in}$ ,  $V_1$ ,  $DC_{out}$ , and  $V_2$  bonding pads are  $75 \times 75$  microns.
- 3) RF input and output bonding pads are  $60 \times 70$  microns.
- 4) Chip thickness:  $127 \pm 15 \mu\text{m}$ .





Figure 3. Assembly diagram

Figure 4. Attenuator driver



## Typical Performance




Figure 5. Attenuation vs. frequency<sup>1</sup>




Figure 6. Output return loss vs. frequency<sup>1</sup>

1. Data obtained from on-wafer measurements.  $T_{\text{chuck}} = 25^{\circ}\text{C}$ .

## Typical Power Performance

(NOTE: All attenuation settings were done at 1 GHz)




Figure 7. Attenuation vs. input power @ 50.0 MHz<sup>1</sup>




Figure 8. Attenuation vs. input power @ 2.0 GHz<sup>1</sup>




Figure 9. Attenuation vs. input power @ 10.0 GHz<sup>1</sup>




Figure 10. Attenuation vs. input power @ 14.0 GHz<sup>1</sup>




Figure 11. Attenuation vs. input power @ 18.0 GHz<sup>1</sup>




Figure 12. Attenuation vs. input power @ 22.0 GHz<sup>1</sup>

1. Data taken with the device mounted in connectorized package

## Typical Harmonic Performance




Figure 13. Second harmonic suppression vs. attenuation, input power = 0.0 dBm<sup>1</sup>




Figure 14. Third harmonic suppression vs. attenuation, input power = 0.0 dBm<sup>1</sup>

1. Data taken with the device mounted in connectorized package

## Typical Temperature Performance




Figure 15. Attenuation vs. temperature @ minimum attenuation<sup>1</sup>




Figure 16. Attenuation vs. temperature @ 5 dB attenuation<sup>1</sup>




Figure 17. Attenuation vs. temperature @ 10 dB attenuation<sup>1</sup>




Figure 18. Attenuation vs. temperature @ 20 dB attenuation<sup>1</sup>




Figure 19. Attenuation vs. temperature @ 30 dB attenuation<sup>1</sup>




Figure 20. Attenuation vs. temperature @ maximum attenuation<sup>1</sup>

1. Data taken with the device mounted in connectorized package

This data sheet contains a variety of typical and guaranteed performance data. The information supplied should not be interpreted as a complete list of circuit specifications. Customers considering the use of this, or other Keysight GaAs ICs, for their design should obtain the current production

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: [www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)

**myKeysight**

myKeysight

[www.keysight.com/find/mykeysight](http://www.keysight.com/find/mykeysight)

A personalized view into the information most relevant to you.



[www.axiestandard.org](http://www.axiestandard.org)

AdvancedTCA® Extensions for Instrumentation and Test (AXIe) is an open standard that extends the AdvancedTCA for general purpose and semiconductor test. Keysight is a founding member of the AXIe consortium.



[www.lxistandard.org](http://www.lxistandard.org)

LAN eXtensions for Instruments puts the power of Ethernet and the Web inside your test systems. Keysight is a founding member of the LXI consortium.



[www.pxisa.org](http://www.pxisa.org)

PCI eXtensions for Instrumentation (PXI) modular instrumentation delivers a rugged, PC-based high-performance measurement and automation system.

**Three-Year Warranty**

[www.keysight.com/find/ThreeYearWarranty](http://www.keysight.com/find/ThreeYearWarranty)

Keysight's commitment to superior product quality and lower total cost of ownership. The only test and measurement company with three-year warranty standard on all instruments, worldwide.



**Keysight Assurance Plans**

[www.keysight.com/find/AssurancePlans](http://www.keysight.com/find/AssurancePlans)

Up to five years of protection and no budgetary surprises to ensure your instruments are operating to specification so you can rely on accurate measurements.



[www.keysight.com/quality](http://www.keysight.com/quality)

Keysight Technologies, Inc.  
DEKRA Certified ISO 9001:2008  
Quality Management System



**Keysight Channel Partners**

[www.keysight.com/find/channelpartners](http://www.keysight.com/find/channelpartners)

Get the best of both worlds: Keysight's measurement expertise and product breadth, combined with channel partner convenience.

**Americas**

Canada	(877) 894 4414
Brazil	55 11 3351 7010
Mexico	001 800 254 2440
United States	(800) 829 4444

**Asia Pacific**

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 6375 8100

**Europe & Middle East**

Austria	0800 001122
Belgium	0800 58580
Finland	0800 523252
France	0805 980333
Germany	0800 6270999
Ireland	1800 832700
Israel	1 809 343051
Italy	800 599100
Luxembourg	+32 800 58580
Netherlands	0800 0233200
Russia	8800 5009286
Spain	0800 000154
Sweden	0200 882255
Switzerland	0800 805353
	Opt. 1 (DE)
	Opt. 2 (FR)
	Opt. 3 (IT)
United Kingdom	0800 0260637

For other unlisted countries:  
[www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)  
(BP-06-23-14)

