


**Low Vcesat PNP Epitaxial Planar Transistor**

# BTB857T3


## Features

- Low  $V_{CE(sat)}$ ,  $V_{CE(sat)} = -0.15V$  (typical), at  $I_C / I_B = -2A / -0.2A$
- Excellent DC current gain characteristics
- Wide SOA
- RoHS compliant package

## Symbol




## Outline



## Ordering Information

Device	Package	Shipping
BTB857T3-0-BL-G	TO-126 (Pb-free lead plating and halogen-free package)	200 pcs / bag, 3,000 pcs/box 30,000 pcs/carton
BTB857T3-0-UH-G		60 pcs/ tube, 40 tubes/box





**Absolute Maximum Ratings** (Ta=25°C)

Parameter	Symbol	Limits	Unit
Collector-Base Voltage	V <sub>CBO</sub>	-100	V
Collector-Emitter Voltage	V <sub>CEO</sub>	-100	V
Emitter-Base Voltage	V <sub>EBO</sub>	-6	V
Collector Current	I <sub>C</sub>	Continuous	-5
		Pulse	-8 *1
Power Dissipation	P <sub>D</sub>	T <sub>A</sub> =25°C	1.5
		T <sub>C</sub> =25°C	20
Operating Junction Temperature Range	T <sub>j</sub>	-55~+150	°C
Storage Temperature Range	T <sub>stg</sub>	-55~+150	°C

Note : \*1. Single Pulse Pw=10ms

**Characteristics** (Ta=25°C)


Symbol	Min.	Typ.	Max.	Unit	Test Conditions
BV <sub>CBO</sub>	-100	-	-	V	I <sub>C</sub> =-50μA, I <sub>E</sub> =0
BV <sub>CEO</sub>	-100	-	-	V	I <sub>C</sub> =-10mA, I <sub>B</sub> =0
BV <sub>EBO</sub>	-6	-	-	V	I <sub>E</sub> =-50μA, I <sub>C</sub> =0
I <sub>CBO</sub>	-	-	-50	nA	V <sub>CB</sub> =-100V, I <sub>E</sub> =0
I <sub>CEO</sub>	-	-	-10	μA	V <sub>CE</sub> =-100V, I <sub>B</sub> =0
I <sub>EBO</sub>	-	-	-50	nA	V <sub>EB</sub> =-6V, I <sub>C</sub> =0
*V <sub>CE(sat)</sub>	-	-	-0.2	V	I <sub>C</sub> =-1A, I <sub>B</sub> =-100mA
*V <sub>CE(sat)</sub>	-	-	-0.3	V	I <sub>C</sub> =-2A, I <sub>B</sub> =-200mA
*V <sub>CE(sat)</sub>	-	-	-0.4	V	I <sub>C</sub> =-3A, I <sub>B</sub> =-300mA
*V <sub>BE(sat)</sub>	-	-	-1.2	V	I <sub>C</sub> =-2A, I <sub>B</sub> =-200mA
*h <sub>FE 1</sub>	180	-	390	-	V <sub>CE</sub> =-3V, I <sub>C</sub> =-500mA
*h <sub>FE 2</sub>	120	-	-	-	V <sub>CE</sub> =-2V, I <sub>C</sub> =-1A
f <sub>T</sub>	-	15	-	MHz	V <sub>CE</sub> =-5V, I <sub>C</sub> =-500mA, f=100MHz

\*Pulse Test : Pulse Width ≤300μs, Duty Cycle ≤2%




### Typical Characteristics


Current Gain vs Collector Current




Saturation Voltage vs Collector Current




Saturation Voltage vs Collector Current




On Voltage vs Collector Current



Power Derating Curve




Power Derating Curve



**Recommended wave soldering condition**

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


**Recommended temperature profile for IR reflow**



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T <sub>smax</sub> to T <sub>p</sub> )	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T <sub>s min</sub> )	100°C	150°C
-Temperature Max(T <sub>s max</sub> )	150°C	200°C
-Time(t <sub>s min</sub> to t <sub>s max</sub> )	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T <sub>L</sub> )	183°C	217°C
- Time (t <sub>L</sub> )	60-150 seconds	60-150 seconds
Peak Temperature(T <sub>p</sub> )	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

**TO-126 Dimension**



3-Lead TO-126 Plastic Package  
 CYStek Package Code: T3

Marking:  
 B857  
 □□□□  
 Date Code

Style: Pin 1. Emitter 2. Collector 3. Base

\*: Typical

DIM	Millimeters		Inches		DIM	Millimeters		Inches	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	2.500	2.900	0.098	0.114	e	*2.290		*0.090	
A1	1.100	1.500	0.043	0.059	e1	4.480	4.680	0.176	0.184
b	0.660	0.860	0.026	0.034	h	0.000	0.300	0.000	0.012
b1	1.170	1.370	0.046	0.054	L	15.300	15.700	0.602	0.618
c	0.450	0.600	0.018	0.024	L1	2.100	2.300	0.083	0.091
D	7.400	7.800	0.291	0.307	P	3.900	4.100	0.154	0.161
E	10.600	11.000	0.417	0.433	Φ	3.000	3.200	0.118	0.126

- Notes:**
- Controlling dimension: millimeters.
  - Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
  - If there is any question with packing specification or packing method, please contact your local CYStek sales office.

**Material:**

- Lead: Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.