



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

2N2219A

Silicon NPN Transistor

General Purpose Audio Amplifier, Switch

TO-39 Type Package

Absolute Maximum Ratings:

Collector-Emitter Voltage, V_{CEO}	40V
Collector-Base Voltage, V_{CBO}	75V
Emitter-Base Voltage, V_{EBO}	6V
Continuous Collector Current, I_C	800mA
Total Device Dissipation ($T_A = +25^\circ\text{C}$), P_D	800mW
Derate Above 25°C	5.33mW/ $^\circ\text{C}$
Total Device Dissipation ($T_C = +25^\circ\text{C}$), P_D	3.0W
Derate Above 25°C	20mW/ $^\circ\text{C}$
Operating Junction Temperature Range, T_J	-65° to $+200^\circ\text{C}$
Storage Temperature Range, T_{stg}	-65° to $+200^\circ\text{C}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
OFF Characteristics						
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 10\text{mA}$, $I_B = 0$	40	—	—	V
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 10\mu\text{A}$, $I_E = 0$	75	—	—	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 10\mu\text{A}$, $I_C = 0$	6	—	—	V
Collector Cutoff Current	I_{CBO}	$V_{CE} = 60\text{V}$, $I_E = 0$	—	—	0.01	μA
		$V_{CE} = 60\text{V}$, $I_E = 0$, $T_A = +150^\circ\text{C}$	—	—	10	μA
	I_{CEX}	$V_{CE} = 60\text{V}$, $V_{EB(off)} = 3\text{V}$	—	—	10	nA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 3\text{V}$, $I_C = 0$	—	—	10	nA
Base Cutoff Current	I_{BL}	$V_{CE} = 60\text{V}$, $V_{EB(off)} = 3\text{V}$	—	—	20	nA

Electrical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
ON Characteristics (Note 1)						
DC Current Gain	h_{FE}	$I_C = 0.1\text{mA}$, $V_{CE} = 10\text{V}$	35	–	–	
		$I_C = 1\text{mA}$, $V_{CE} = 10\text{V}$	50	–	–	
		$I_C = 10\text{mA}$, $V_{CE} = 10\text{V}$	75	–	–	
		$I_C = 10\text{mA}$, $V_{CE} = 10\text{V}$, $T_A = -55^{\circ}\text{C}$	35	–	–	
		$I_C = 150\text{mA}$, $V_{CE} = 10\text{V}$	100	–	300	
		$I_C = 150\text{mA}$, $V_{CE} = 1.0\text{V}$	50	–	–	
		$I_C = 500\text{mA}$, $V_{CE} = 10\text{V}$	40	–	–	
Collector–Emitter Saturation Voltage	$V_{CE(\text{sat})}$	$I_C = 150\text{mA}$, $I_B = 15\text{mA}$	–	–	0.3	V
		$I_C = 500\text{mA}$, $I_B = 50\text{mA}$	–	–	1.0	V
Base–Emitter Saturation Voltage	$V_{BE(\text{sat})}$	$I_C = 150\text{mA}$, $I_B = 15\text{mA}$	0.6	–	1.2	V
		$I_C = 500\text{mA}$, $I_B = 50\text{mA}$	–	–	2.0	V
Small–Signal Characteristics						
Current Gain–Bandwidth Product	f_T	$I_C = 20\text{mA}$, $V_{CE} = 20\text{V}$, $f = 100\text{MHz}$, Note 2	300	–	–	MHz
Output Capacitance	C_{obo}	$V_{CB} = 10\text{V}$, $I_E = 0$, $f = 100\text{kHz}$	–	–	8	pF
Input Capacitance	C_{ibo}	$V_{EB} = 0.5\text{V}$, $I_C = 0$, $f = 100\text{kHz}$	–	–	25	pF
Input Impedance	h_{ie}	$I_C = 1\text{mA}$, $V_{CE} = 10\text{V}$, $f = 1\text{kHz}$	2.0	–	8.0	k Ω
		$I_C = 10\text{mA}$, $V_{CE} = 10\text{V}$, $f = 1\text{kHz}$	0.25	–	1.25	k Ω
Voltage Feedback Ratio	h_{re}	$I_C = 1\text{mA}$, $V_{CE} = 10\text{V}$, $f = 1\text{kHz}$	–	–	8	$\times 10^{-4}$
		$I_C = 10\text{mA}$, $V_{CE} = 10\text{V}$, $f = 1\text{kHz}$	–	–	4	$\times 10^{-4}$
Small–Signal Current Gain	h_{fe}	$I_C = 1\text{mA}$, $V_{CE} = 10\text{V}$, $f = 1\text{kHz}$	50	–	300	
		$I_C = 10\text{mA}$, $V_{CE} = 10\text{V}$, $f = 1\text{kHz}$	75	–	375	
Output Admittance	h_{oe}	$I_C = 1\text{mA}$, $V_{CE} = 10\text{V}$, $f = 1\text{kHz}$	5.0	–	35	μmhos
		$I_C = 10\text{mA}$, $V_{CE} = 10\text{V}$, $f = 1\text{kHz}$	25	–	200	μmhos
Collector–Base Time Constant	$r_b'C_C$	$I_E = 20\text{mA}$, $V_{CB} = 20\text{V}$, $f = 31.8\text{MHz}$	–	–	150	ps
Noise Figure	NF	$I_C = 100\mu\text{A}$, $V_{CE} = 10\text{V}$, $R_S = 1\text{k}\Omega$, $f = 1\text{kHz}$	–	–	4	dB
Real Part of Common–Emitter High Frequency Input Impedance	$\text{Re}(h_{ie})$	$I_C = 20\text{mA}$, $V_{CE} = 20\text{V}$, $f = 300\text{MHz}$	–	–	60	Ω
Switching Characteristics						
Delay Time	t_q	$V_{CC} = 30\text{V}$, $V_{BE(\text{off})} = 0.5\text{V}$, $I_C = 150\text{mA}$, $I_{B1} = 15\text{mA}$	–	–	10	ns
Rise Time	t_r		–	–	25	ns
Storage Time	t_s	$V_{CC} = 30\text{V}$, $I_C = 150\text{mA}$, $I_{B1} = I_{B2} = 15\text{mA}$	–	–	225	ns
Fall Time	t_f		–	–	60	ns
Active Region Time Constant	T_A	$I_C = 150\text{mA}$, $V_{CE} = 30\text{V}$	–	–	2.5	ns

Note 1. Pulse Test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.

Note 2. f_T is defined as the frequency at which $|h_{fe}|$ extrapolates to unity.

