

isc Silicon NPN Transistor


MMBT3904

DESCRIPTION

- Low Voltage Use
- Ultra Super Mini Mold Package
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Telephony and professional communication equipment.

ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	60	V
V_{CEO}	Collector-Emitter Voltage	40	V
V_{EBO}	Emitter-Base Voltage	6	V
I_C	Collector Current-Continuous	200	mA
P_C	Collector Power Dissipation @ $T_C=25^{\circ}\text{C}$	350	mW
T_J	Junction Temperature	-55~150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^{\circ}\text{C}$


ELECTRICAL CHARACTERISTICS

$T_c=25^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
I_{CBO}	Collector Cutoff Current	$V_{CE}=60\text{V}$		50	nA
I_{CEX}	Collector Cutoff Current	$V_{CE}=30\text{V}$		50	nA
h_{FE}	DC Current Gain	$I_C=0.1\text{mA}; V_{CE}=1\text{V}$	40		
		$I_C=1\text{mA}; V_{CE}=1\text{V}$	70		
		$I_C=10\text{mA}; V_{CE}=1\text{V}$	100	300	
		$I_C=50\text{mA}; V_{CE}=1\text{V}$	60		
		$I_C=100\text{mA}; V_{CE}=1\text{V}$	30		
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C=10\text{mA}; I_B=1\text{mA}$		0.2	V
		$I_C=50\text{mA}; I_B=5\text{mA}$		0.3	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C=10\text{mA}; I_B=1\text{mA}$	0.65	0.85	V
		$I_C=50\text{mA}; I_B=5\text{mA}$		0.95	V
f_T	Current Gain-Bandwidth Product	$I_C=10\text{mA}; V_{CE}=20\text{V}; f=100\text{MHz}$	300		MHz
NF	Noise Figure	$V_{CE}=5.0\text{V}; f=10\text{Hz to }15.7\text{kHz}; I_C=100\mu\text{A}; R_S=1.0\text{k}\Omega$		5	dB

isc Silicon NPN Transistor
MMBT3904
SWITCHING CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
t_d	Delay Time	$V_{CC}=3.0V; V_{BE}=0.5V; I_C=10mA; I_{B1}=1.0mA$	35	ns
t_r	Rise Time		35	ns
t_s	Storage Time	$V_{CC}=3.0V; I_C=10mA; I_{B1}=1.0mA$	200	ns
t_f	Fall Time		50	ns

SOT-23 Package Outline Dimensions


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.900	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
phi	0°	8°	0°	8°

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.