

Ultrafast Recovery Rectifier

STTH812D

FEATURES



- Ultrafast Recovery Time
- Low Forward Voltage
- Low Leakage Current
- 150°C Operating Junction Temperature
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Switching power supplies
- Power switching circuits
- General purpose

ABSOLUTE MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{RRM} V _{RWM} V _R	Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	1200	V
I _{F(AV)}	Average Rectified Forward Current (Rated V _R)	8	A
I _{FRM}	Peak Repetitive Forward Current	100	A
I _{FSM}	Nonrepetitive Peak Surge Current	80	A
T _J	Junction Temperature	-65~150	°C
T _{stg}	Storage Temperature Range	-65~150	°C



Ultrafast Recovery Rectifier

STTH812D

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.9	°C/W

ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$) (Pulse Test: Pulse Width=300 μ s, Duty Cycle $\leq$ 2%)

SYMBOL	PARAMETER	CONDITIONS	MAX	UNIT
V_F^*	Maximum Instantaneous Forward Voltage	$I_F=8\text{A}$	2.2	V
		$I_F=8\text{A}, T_c=125^{\circ}\text{C}$	2.0	
I_R	Maximum Instantaneous Reverse Current	$V_{RRM}=1200\text{V}$	8	μA
		$V_{RRM}=1200\text{V}, T_c=125^{\circ}\text{C}$	50	
t_{rr}	Maximum Reverse Recovery Time	$I_F=1\text{A}, I_R=1.0\text{A}, I_{REC}=0.25\text{A}$	100	ns

*:Pulse test ,Pulse width=300us,duty cycle $\leq$ 2%

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.