

A suffix of "-C" specifies halogen & RoHS compliant


## FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Glass passivated junction
- 1500W peak pulse power capability on 10/1000us waveform, repetition rate (duty cycle): 0.05%
- Excellent clamping capability
- Low incremental surge resistance
- Very fast response time
- High temperature soldering guaranteed: 265°C/10s  
0.375" (9.5mm) lead length, 5lbs. (2.3kg) tension

## MECHANICAL DATA

- Case: DO-27
- Terminals: Plated axial leads, solderable per MIL-STD-750, method 2026
- Polarity: For uni-directional types the color band denotes the cathode, which is positive with respect to the anode under normal TVS operation
- Mounting position: Any

### DO-27



REF.	Millimeter	
	Min.	Max.
A	25.4 (TYP)	
B	7.20	9.50
C	4.80	5.60
D	0.96	1.32

## ORDER INFORMATION

Part Number	Type
1.5KE Series	Lead (Pb)-free
1.5KE Series-C	Lead (Pb)-free and Halogen-free

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T<sub>A</sub>=25°C unless otherwise specified)

Parameter	Symbol	Rating	Unit
Peak Power Dissipation <sup>1</sup> @10/1000us waveform (Fig.1)	P <sub>PP</sub>	Minimum 1500	W
Peak Pulse Current <sup>1</sup> @10/1000us waveform	I <sub>PP</sub>	(See Next Table.)	A
Steady State Power Dissipation <sup>2</sup>	T <sub>L</sub> =75°C P <sub>D</sub>	6.5	W
Peak Forward Surge Current <sup>3</sup> @8.3ms single half sine-wave uni-directional only	I <sub>FSM</sub>	200	A
Maximum Instantaneous Forward Voltage <sup>4</sup> @100A for uni-directional only	V <sub>F</sub>	3.5/5	V
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 ~ 150	°C
<b>Thermal Resistance Ratings</b>			
Thermal Resistance Junction-Ambient	R <sub>θJA</sub>	75	°C/W

### Notes:

1. Non-repetitive current pulse, per Fig. 3 and derated above T<sub>A</sub>=25°C per Fig. 2.
2. Mounted on copper pad area of 1.6" X 1.6" (40mm X 40mm) per Fig. 5.
3. Measured on 8.3ms single half sine-wave or equivalent square wave, duty cycle=4 pulses per minute maximum.
4. V<sub>F</sub>=3.5V for devices of V<sub>BR</sub><220V, and V<sub>F</sub>=5V max. for devices of V<sub>BR</sub>>220V.

**ELECTRICAL CHARACTERISTIC** ( $T_A=25^{\circ}\text{C}$  unless otherwise specified)

Part Number		Reverse Stand-Off Voltage	Breakdown Voltage $V_{BR}$ @ $I_T$		Test Current	Maximum Clamping Voltage $V_C$ @ $I_{PP}$	Peak Pulse Current	Reverse Leakage $I_R$ @ $V_{RWM}$	Maximum Temperature Coefficient Of $V_{BR}$
			Min.	Max.					
Directional		$V_{RWM}$	$V_{BR}$		$I_T$	$V_C$	$I_{PP}$	$I_R$	-
Uni	Bi	V	V		mA	V	A	uA	%/ $^{\circ}\text{C}$
1.5KE6.8A	1.5KE6.8CA	5.8	6.45	7.14	10	10.5	143	1000	0.057
1.5KE7.5A	1.5KE7.5CA	6.4	7.13	7.88	10	11.3	133	500	0.061
1.5KE8.2A	1.5KE8.2CA	7.02	7.79	8.61	10	12.1	124	200	0.065
1.5KE9.1A	1.5KE9.1CA	7.78	8.65	9.55	1	13.4	112	50	0.068
1.5KE10A	1.5KE10CA	8.55	9.5	10.5	1	14.5	103	10	0.073
1.5KE11A	1.5KE11CA	9.4	10.5	11.6	1	15.6	96.2	5	0.075
1.5KE12A	1.5KE12CA	10.2	11.4	12.6	1	16.7	89.8	5	0.078
1.5KE13A	1.5KE13CA	11.1	12.4	13.7	1	18.2	82.4	5	0.081
1.5KE15A	1.5KE15CA	12.8	14.3	15.8	1	21.2	70.8	1	0.084
1.5KE16A	1.5KE16CA	13.6	15.2	16.8	1	22.5	66.7	1	0.086
1.5KE18A	1.5KE18CA	15.3	17.1	18.9	1	25.2	59.5	1	0.088
1.5KE20A	1.5KE20CA	17.1	19	21	1	27.7	54.2	1	0.090
1.5KE22A	1.5KE22CA	18.8	20.9	23.1	1	30.6	49	1	0.092
1.5KE24A	1.5KE24CA	20.5	22.8	25.2	1	33.2	45.2	1	0.094
1.5KE27A	1.5KE27CA	23.1	25.7	28.4	1	37.5	40	1	0.096
1.5KE30A	1.5KE30CA	25.6	28.5	31.5	1	41.4	36.2	1	0.097
1.5KE33A	1.5KE33CA	28.2	31.4	34.7	1	45.7	32.8	1	0.098
1.5KE36A	1.5KE36CA	30.8	34.2	37.8	1	49.9	30.1	1	0.099
1.5KE39A	1.5KE39CA	33.3	37.1	41	1	53.9	27.8	1	0.100
1.5KE43A	1.5KE43CA	36.8	40.9	45.2	1	59.3	25.3	1	0.101
1.5KE47A	1.5KE47CA	40.2	44.7	49.4	1	64.8	23.1	1	0.101
1.5KE51A	1.5KE51CA	43.6	48.5	53.6	1	70.1	21.4	1	0.102
1.5KE56A	1.5KE56CA	47.8	53.2	58.8	1	77	19.5	1	0.103
1.5KE62A	1.5KE62CA	53	58.9	65.1	1	85	17.6	1	0.104
1.5KE68A	1.5KE68CA	58.1	64.6	71.4	1	92	16.3	1	0.104
1.5KE75A	1.5KE75CA	64.1	71.3	78.8	1	104	14.6	1	0.105
1.5KE82A	1.5KE82CA	70.1	77.9	86.1	1	113	13.3	1	0.105
1.5KE91A	1.5KE91CA	77.8	86.5	95.5	1	125	12	1	0.106
1.5KE100A	1.5KE100CA	85.5	95	105	1	137	10.9	1	0.106
1.5KE110A	1.5KE110CA	94	105	116	1	152	9.9	1	0.107
1.5KE120A	1.5KE120CA	102	114	126	1	165	9.1	1	0.107

**ELECTRICAL CHARACTERISTIC** ( $T_A=25^{\circ}\text{C}$  unless otherwise specified)


Part Number		Reverse Stand-Off Voltage	Breakdown Voltage $V_{BR}$ @ $I_T$		Test Current	Maximum Clamping Voltage $V_C$ @ $I_{PP}$	Peak Pulse Current	Reverse Leakage $I_R$ @ $V_{RWM}$	Maximum Temperature Coefficient Of $V_{BR}$
			Min.	Max.					
Directional		$V_{RWM}$	$V_{BR}$		$I_T$	$V_C$	$I_{PP}$	$I_R$	-
Uni	Bi	V	V		mA	V	A	uA	%/ $^{\circ}\text{C}$
1.5KE130A	1.5KE130CA	111	124	137	1	179	8.4	1	0.107
1.5KE150A	1.5KE150CA	128	143	158	1	207	7.2	1	0.106
1.5KE160A	1.5KE160CA	136	152	168	1	219	6.8	1	0.108
1.5KE170A	1.5KE170CA	145	162	179	1	234	6.4	1	0.108
1.5KE180A	1.5KE180CA	154	171	189	1	246	6.1	1	0.108
1.5KE200A	1.5KE200CA	171	190	210	1	274	5.5	1	0.108
1.5KE220A	1.5KE220CA	185	209	231	1	328	4.6	1	0.108
1.5KE250A	1.5KE250CA	214	237	263	1	344	4.4	1	0.110
1.5KE300A	1.5KE300CA	256	285	315	1	414	3.6	1	0.110
1.5KE350A	1.5KE350CA	300	333	368	1	482	3.1	1	0.110
1.5KE400A	1.5KE400CA	342	380	420	1	548	2.7	1	0.110
1.5KE440A	1.5KE440CA	376	418	462	1	602	2.5	1	0.110
1.5KE480A	1.5KE480CA	408	456	504	1	658	2.3	1	0.110
1.5KE510A	1.5KE510CA	434	485	535	1	698	2.1	1	0.110
1.5KE530A	1.5KE530CA	450	503.5	556.5	1	725	2.1	1	0.110
1.5KE540A	1.5KE540CA	459	513	567	1	740	2.0	1	0.110
1.5KE550A	1.5KE550CA	467	522.5	577.5	1	760	2.0	1	0.110

Notes:


1.  $V_{BR}$  measured after  $I_T$  applied for 300us,  $I_T$ =square wave pulse or equivalent.
2. Surge current waveform per Fig. 3 and derate per Fig. 2.
3. All terms and symbols are consistent with ANSI/IEEE C62.35.
4. For Bi-directional types with  $V_R$  10 Volts and less the  $I_D$  limit is doubled.

**TYPICAL CHARACTERISTICS**


**Fig. 1 – Peak Pulse Power Rating Curve**




**Fig. 2 – Pulse Derating Curve**




**Fig. 3 – Pulse Waveform**




**Fig. 4 - Typical Junction Capacitance**



**Fig. 5 – Steady State Power Derating Curve**




**Fig. 6 - Maximum Non-repetitive Peak Forward Surge Current Unidirectional Only**




**TYPICAL CHARACTERISTICS**


**Fig. 7 – Incremental Clamping Voltage Curve (Unidirectional)**




**Fig. 8 – Incremental Clamping Voltage Curve (Unidirectional)**



**Fig. 9 – Incremental Clamping Voltage Curve (Bidirectional)**




**Fig. 10 – Incremental Clamping Voltage Curve (Bidirectional)**






**TYPICAL CHARACTERISTICS**

**Fig. 11 – Instantaneous Forward Voltage Characteristics Curve**



**Fig. 12 – Breakdown Voltage Temperature Coefficient Curve**



**Fig. 13 – Typical Transient Thermal Impedance**

