

## 16-Kbit SPI Bus Serial EEPROM

### Device Selection Table

| Part Number | Vcc Range | Page Size | Temp. Ranges | Packages          |
|-------------|-----------|-----------|--------------|-------------------|
| 25AA160C    | 1.8V-5.5V | 16 bytes  | I            | MS, P, SN, MN, ST |
| 25LC160C    | 2.5V-5.5V | 16 bytes  | I, E         | MS, P, SN, MN, ST |
| 25AA160D    | 1.8V-5.5V | 32 bytes  | I, E         | MS, P, SN, MN, ST |
| 25LC160D    | 2.5V-5.5V | 32 bytes  | I, E         | MS, P, SN, MN, ST |

### Features

- 10 MHz Maximum Clock Speed
- Low-Power CMOS Technology:
  - Maximum Write current: 5 mA at 5.5V
  - Read current: 5 mA at 5.5V, 10 MHz
  - Standby current: 5  $\mu$ A at 5.5V
- 2048 x 8-bit Organization
- 16-Byte Page ("C" version devices)
- 32-Byte Page ("D" version devices)
- Self-Timed Erase and Write Cycles (5 ms maximum)
- Block Write Protection:
  - Protect none, 1/4, 1/2 or all of array
- Built-In Write Protection:
  - Power-on/off data protection circuitry
  - Write enable latch
  - Write-protect pin
- Sequential Read
- High Reliability:
  - Endurance: >1M erase/write cycles
  - Data retention: >200 years
  - ESD protection: >4000V
- Temperature Ranges Supported:
  - Industrial (I): -40°C to +85°C
  - Extended (E): -40°C to +125°C
- RoHS Compliant
- Automotive AEC-Q100 Qualified

### Packages

- 8-Lead MSOP, 8-Lead PDIP, 8-Lead SOIC, 8-Lead TDFN and 8-Lead TSSOP

### Pin Function Table

| Name | Function           |
|------|--------------------|
| CS   | Chip Select Input  |
| SO   | Serial Data Output |
| WP   | Write-Protect Pin  |
| Vss  | Ground             |
| SI   | Serial Data Input  |
| SCK  | Serial Clock Input |
| HOLD | Hold Input         |
| Vcc  | Supply Voltage     |


### Description

The Microchip Technology Inc. 25XX160C/D<sup>(1)</sup> are 16-Kbit Serial Electrically Erasable PROMs (EEPROM). The memory is accessed via a simple Serial Peripheral Interface (SPI) compatible serial bus. The bus signals required are a clock input (SCK) plus separate data in (SI) and data out (SO) lines. Access to the device is controlled through a Chip Select (CS) input.

Communication to the device can be paused via the hold pin (HOLD). While the device is paused, transitions on its inputs will be ignored, with the exception of Chip Select, allowing the host to service higher priority interrupts.

**Note 1:** 25XX160C/D is used in this document as a generic part number for the 25AA160C/D and 25LC160C/D devices.

### Package Types (not to scale)



# 25AA160C/D, 25LC160C/D

## 1.0 ELECTRICAL CHARACTERISTICS

### Absolute Maximum Ratings<sup>(†)</sup>

|                                                     |                                |
|-----------------------------------------------------|--------------------------------|
| V <sub>CC</sub> .....                               | 6.5V                           |
| All inputs and outputs w.r.t. V <sub>SS</sub> ..... | -0.6V to V <sub>CC</sub> +1.0V |
| Storage temperature .....                           | -65°C to +150°C                |
| Ambient temperature under bias .....                | -40°C to +125°C                |
| ESD protection on all pins .....                    | 4 kV                           |

† **NOTICE:** Stresses above those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at those or any other conditions above those indicated in the operational listings of this specification is not implied. Exposure to maximum rating conditions for an extended period of time may affect device reliability.

**TABLE 1-1: DC CHARACTERISTICS**

| DC CHARACTERISTICS |           |                                               | Electrical Characteristics:<br>Industrial (I):   TA = -40°C to +85°C   Vcc = 1.8V to 5.5V<br>Extended (E):   TA = -40°C to +125°C   Vcc = 1.8V to 5.5V |         |       |                                                                     |
|--------------------|-----------|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|---------|-------|---------------------------------------------------------------------|
| Param. No.         | Symbol    | Characteristic                                | Min.                                                                                                                                                   | Max.    | Units | Test Conditions                                                     |
| D001               | VIH1      | High-Level Input Voltage                      | 0.7 Vcc                                                                                                                                                | Vcc + 1 | V     |                                                                     |
| D002               | VIL1      | Low-Level Input Voltage                       | -0.3                                                                                                                                                   | 0.3 Vcc | V     | Vcc ≥ 2.7V ( <b>Note 1</b> )                                        |
| D003               | VIL2      |                                               | -0.3                                                                                                                                                   | 0.2 Vcc | V     | Vcc < 2.7V ( <b>Note 1</b> )                                        |
| D004               | VOL1      | Low-Level Output Voltage                      | —                                                                                                                                                      | 0.4     | V     | IoL = 2.1 mA                                                        |
| D005               | VOL2      |                                               | —                                                                                                                                                      | 0.2     | V     | IoL = 1.0 mA, Vcc < 2.5V                                            |
| D006               | VOH       | High-Level Output Voltage                     | Vcc - 0.5                                                                                                                                              | —       | V     | IoH = -400 µA                                                       |
| D007               | ILI       | Input Leakage Current                         | —                                                                                                                                                      | ±1      | µA    | $\overline{CS} = V_{CC}$ , VIN = Vss or Vcc                         |
| D008               | ILO       | Output Leakage Current                        | —                                                                                                                                                      | ±1      | µA    | $\overline{CS} = V_{CC}$ , VOUT = Vss or Vcc                        |
| D009               | CINT      | Internal Capacitance (all inputs and outputs) | —                                                                                                                                                      | 7       | pF    | TA = +25°C, CLK = 1.0 MHz, Vcc = 5.0V ( <b>Note 1</b> )             |
| D010               | Icc Read  | Operating Current                             | —                                                                                                                                                      | 5       | mA    | Vcc = 5.5V; FCLK = 10.0 MHz; SO = Open                              |
|                    |           |                                               | —                                                                                                                                                      | 2.5     | mA    | Vcc = 2.5V; FCLK = 5.0 MHz; SO = Open                               |
| D011               | Icc Write |                                               | —                                                                                                                                                      | 5       | mA    | Vcc = 5.5V                                                          |
|                    |           |                                               | —                                                                                                                                                      | 3       | mA    | Vcc = 2.5V                                                          |
| D012               | Iccs      | Standby Current                               | —                                                                                                                                                      | 5       | µA    | $\overline{CS} = V_{CC} = 5.5V$ , Inputs tied to Vcc or Vss, +125°C |
|                    |           |                                               | —                                                                                                                                                      | 1       | µA    | $\overline{CS} = V_{CC} = 5.5V$ , Inputs tied to Vcc or Vss, +85°C  |

**Note 1:** This parameter is periodically sampled and not 100% tested.

# 25AA160C/D, 25LC160C/D

**TABLE 1-2: AC CHARACTERISTICS**

| AC CHARACTERISTICS |        |                             | Electrical Characteristics:<br>Industrial (I): TA = -40°C to +85°C VCC = 1.8V to 5.5V<br>Extended (E): TA = -40°C to +125°C VCC = 1.8V to 5.5V |      |       |                            |
|--------------------|--------|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|------|-------|----------------------------|
| Param. No.         | Symbol | Characteristic              | Min.                                                                                                                                           | Max. | Units | Test Conditions            |
| 1                  | FCLK   | Clock Frequency             | —                                                                                                                                              | 10   | MHz   | 4.5V ≤ VCC ≤ 5.5V          |
|                    |        |                             | —                                                                                                                                              | 5    | MHz   | 2.5V ≤ VCC < 4.5V          |
|                    |        |                             | —                                                                                                                                              | 3    | MHz   | 1.8V ≤ VCC < 2.5V          |
| 2                  | TCSS   | CS Setup Time               | 50                                                                                                                                             | —    | ns    | 4.5V ≤ VCC ≤ 5.5V          |
|                    |        |                             | 100                                                                                                                                            | —    | ns    | 2.5V ≤ VCC < 4.5V          |
|                    |        |                             | 150                                                                                                                                            | —    | ns    | 1.8V ≤ VCC < 2.5V          |
| 3                  | TCSH   | CS Hold Time                | 100                                                                                                                                            | —    | ns    | 4.5V ≤ VCC ≤ 5.5V          |
|                    |        |                             | 200                                                                                                                                            | —    | ns    | 2.5V ≤ VCC < 4.5V          |
|                    |        |                             | 250                                                                                                                                            | —    | ns    | 1.8V ≤ VCC < 2.5V          |
| 4                  | TCSD   | CS Disable Time             | 50                                                                                                                                             | —    | ns    |                            |
| 5                  | Tsu    | Data Setup Time             | 10                                                                                                                                             | —    | ns    | 4.5V ≤ VCC ≤ 5.5V          |
|                    |        |                             | 20                                                                                                                                             | —    | ns    | 2.5V ≤ VCC < 4.5V          |
|                    |        |                             | 30                                                                                                                                             | —    | ns    | 1.8V ≤ VCC < 2.5V          |
| 6                  | THD    | Data Hold Time              | 20                                                                                                                                             | —    | ns    | 4.5V ≤ VCC ≤ 5.5V          |
|                    |        |                             | 40                                                                                                                                             | —    | ns    | 2.5V ≤ VCC < 4.5V          |
|                    |        |                             | 50                                                                                                                                             | —    | ns    | 1.8V ≤ VCC < 2.5V          |
| 7                  | TR     | CLK Rise Time               | —                                                                                                                                              | 2    | μs    | Note 1                     |
| 8                  | TF     | CLK Fall Time               | —                                                                                                                                              | 2    | μs    | Note 1                     |
| 9                  | THI    | Clock High Time             | 50                                                                                                                                             | —    | ns    | 4.5V ≤ VCC ≤ 5.5V          |
|                    |        |                             | 100                                                                                                                                            | —    | ns    | 2.5V ≤ VCC < 4.5V          |
|                    |        |                             | 150                                                                                                                                            | —    | ns    | 1.8V ≤ VCC < 2.5V          |
| 10                 | TLO    | Clock Low Time              | 50                                                                                                                                             | —    | ns    | 4.5V ≤ VCC ≤ 5.5V          |
|                    |        |                             | 100                                                                                                                                            | —    | ns    | 2.5V ≤ VCC < 4.5V          |
|                    |        |                             | 150                                                                                                                                            | —    | ns    | 1.8V ≤ VCC < 2.5V          |
| 11                 | TCLD   | Clock Delay Time            | 50                                                                                                                                             | —    | ns    |                            |
| 12                 | TCLE   | Clock Enable Time           | 50                                                                                                                                             | —    | ns    |                            |
| 13                 | Tv     | Output Valid from Clock Low | —                                                                                                                                              | 50   | ns    | 4.5V ≤ VCC ≤ 5.5V          |
|                    |        |                             | —                                                                                                                                              | 100  | ns    | 2.5V ≤ VCC < 4.5V          |
|                    |        |                             | —                                                                                                                                              | 160  | ns    | 1.8V ≤ VCC < 2.5V          |
| 14                 | THO    | Output Hold Time            | 0                                                                                                                                              | —    | ns    | Note 1                     |
| 15                 | TDIS   | Output Disable Time         | —                                                                                                                                              | 40   | ns    | 4.5V ≤ VCC ≤ 5.5V (Note 1) |
|                    |        |                             | —                                                                                                                                              | 80   | ns    | 2.5V ≤ VCC ≤ 4.5V (Note 1) |
|                    |        |                             | —                                                                                                                                              | 160  | ns    | 1.8V ≤ VCC ≤ 2.5V (Note 1) |
| 16                 | THS    | HOLD Setup Time             | 20                                                                                                                                             | —    | ns    | 4.5V ≤ VCC ≤ 5.5V          |
|                    |        |                             | 40                                                                                                                                             | —    | ns    | 2.5V ≤ VCC < 4.5V          |
|                    |        |                             | 80                                                                                                                                             | —    | ns    | 1.8V ≤ VCC < 2.5V          |

**Note 1:** This parameter is periodically sampled and not 100% tested.

**2:** Twc begins on the rising edge of CS after a valid write sequence and ends when the internal write cycle is complete.

**3:** This parameter is not tested but ensured by characterization.

# 25AA160C/D, 25LC160C/D

**TABLE 1-2: AC CHARACTERISTICS (CONTINUED)**

| AC CHARACTERISTICS |          |                                               | Electrical Characteristics:                                          |      |                                         |                                                                     |
|--------------------|----------|-----------------------------------------------|----------------------------------------------------------------------|------|-----------------------------------------|---------------------------------------------------------------------|
|                    |          |                                               | Industrial (I): $T_A = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$ |      | $V_{CC} = 1.8\text{V}$ to $5.5\text{V}$ |                                                                     |
|                    |          |                                               | Extended (E): $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$  |      | $V_{CC} = 1.8\text{V}$ to $5.5\text{V}$ |                                                                     |
| Param. No.         | Symbol   | Characteristic                                | Min.                                                                 | Max. | Units                                   | Test Conditions                                                     |
| 17                 | $T_{HH}$ | $\overline{\text{HOLD}}$ Hold Time            | 20                                                                   | —    | ns                                      | $4.5\text{V} \leq V_{CC} \leq 5.5\text{V}$                          |
|                    |          |                                               | 40                                                                   | —    | ns                                      | $2.5\text{V} \leq V_{CC} < 4.5\text{V}$                             |
|                    |          |                                               | 80                                                                   | —    | ns                                      | $1.8\text{V} \leq V_{CC} < 2.5\text{V}$                             |
| 18                 | $T_{HZ}$ | $\overline{\text{HOLD}}$ Low to Output High-Z | —                                                                    | 30   | ns                                      | $4.5\text{V} \leq V_{CC} \leq 5.5\text{V}$ (Note 1)                 |
|                    |          |                                               | —                                                                    | 60   | ns                                      | $2.5\text{V} \leq V_{CC} < 4.5\text{V}$ (Note 1)                    |
|                    |          |                                               | —                                                                    | 160  | ns                                      | $1.8\text{V} \leq V_{CC} < 2.5\text{V}$ (Note 1)                    |
| 19                 | $T_{HV}$ | $\overline{\text{HOLD}}$ High to Output Valid | —                                                                    | 30   | ns                                      | $4.5\text{V} \leq V_{CC} \leq 5.5\text{V}$                          |
|                    |          |                                               | —                                                                    | 60   | ns                                      | $2.5\text{V} \leq V_{CC} < 4.5\text{V}$                             |
|                    |          |                                               | —                                                                    | 160  | ns                                      | $1.8\text{V} \leq V_{CC} < 2.5\text{V}$                             |
| 20                 | $T_{WC}$ | Internal Write Cycle Time                     | —                                                                    | 5    | ms                                      | Note 2                                                              |
| 21                 |          | Endurance                                     | 1M                                                                   | —    | E/W Cycles                              | $+25^{\circ}\text{C}$ , $V_{CC} = 5.5\text{V}$ , Page Mode (Note 3) |

**Note 1:** This parameter is periodically sampled and not 100% tested.

**2:**  $T_{WC}$  begins on the rising edge of  $\overline{\text{CS}}$  after a valid write sequence and ends when the internal write cycle is complete.

**3:** This parameter is not tested but ensured by characterization.

**TABLE 1-3: AC TEST CONDITIONS**


| AC Waveform                        |              |
|------------------------------------|--------------|
| $V_{LO} = 0.2\text{V}$             | —            |
| $V_{HI} = V_{CC} - 0.2\text{V}$    | Note 1       |
| $V_{HI} = 4.0\text{V}$             | Note 2       |
| $C_L = 50\text{ pF}$               | —            |
| Timing Measurement Reference Level |              |
| Input                              | $0.5 V_{CC}$ |
| Output                             | $0.5 V_{CC}$ |

**Note 1:** For  $V_{CC} \leq 4.0\text{V}$


**2:** For  $V_{CC} > 4.0\text{V}$

# 25AA160C/D, 25LC160C/D


**FIGURE 1-1: HOLD TIMING**



**FIGURE 1-2: SERIAL INPUT TIMING**



**FIGURE 1-3: SERIAL OUTPUT TIMING**



# 25AA160C/D, 25LC160C/D

## 2.0 PIN DESCRIPTIONS

The descriptions of the pins are listed in [Table 2-1](#).

**TABLE 2-1: PIN FUNCTION TABLE**

| Name                   | MSOP | PDIP | SOIC | TDFN <sup>(1)</sup> | TSSOP | Function           |
|------------------------|------|------|------|---------------------|-------|--------------------|
| $\overline{\text{CS}}$ | 1    | 1    | 1    | 1                   | 1     | Chip Select Input  |
| SO                     | 2    | 2    | 2    | 2                   | 2     | Serial Data Output |
| $\overline{\text{WP}}$ | 3    | 3    | 3    | 3                   | 3     | Write-Protect Pin  |
| Vss                    | 4    | 4    | 4    | 4                   | 4     | Ground             |
| SI                     | 5    | 5    | 5    | 5                   | 5     | Serial Data Input  |
| SCK                    | 6    | 6    | 6    | 6                   | 6     | Serial Clock Input |
| HOLD                   | 7    | 7    | 7    | 7                   | 7     | Hold Input         |
| Vcc                    | 8    | 8    | 8    | 8                   | 8     | Supply Voltage     |

**Note 1:** Exposed pad on TDFN package can be connected to VSS or left floating.

### 2.1 Chip Select ( $\overline{\text{CS}}$ )

A low level on this pin selects the device. A high level deselects the device and forces it into Standby mode. However, a programming cycle which is already initiated or in progress will be completed, regardless of  $\overline{\text{CS}}$  input signal. If  $\overline{\text{CS}}$  is brought high during a program cycle, the device will go into Standby mode as soon as the programming cycle is complete. When the device is deselected, SO goes to high-impedance state, allowing multiple parts to share the same SPI bus.

A low-to-high transition on  $\overline{\text{CS}}$  after a valid write sequence initiates an internal write cycle. After power-up, a low level on  $\overline{\text{CS}}$  is required prior to any sequence being initiated.

### 2.2 Serial Output (SO)

The SO pin is used to transfer data out of the 25XX160C/D. During a read cycle, data are shifted out on this pin after the falling edge of the serial clock.

### 2.3 Write-Protect ( $\overline{\text{WP}}$ )

This pin is used in conjunction with the WPEN bit in the STATUS register to prohibit writes to the nonvolatile bits in the STATUS register. When  $\overline{\text{WP}}$  is low and WPEN is high, writing to the nonvolatile bits in the STATUS register is disabled. All other operations function normally. When  $\overline{\text{WP}}$  is high, all functions, including writes to the nonvolatile bits in the STATUS register, operate normally. If the WPEN bit is set,  $\overline{\text{WP}}$  low during a STATUS register write sequence will disable writing to the STATUS register. If an internal write cycle has already begun,  $\overline{\text{WP}}$  going low will have no effect on the write. The  $\overline{\text{WP}}$  pin function is blocked when the WPEN bit in the STATUS register is low. This allows the user to install the 25XX160C/D in a system with  $\overline{\text{WP}}$  pin grounded and still be able to write to STATUS register. The  $\overline{\text{WP}}$  pin functions will be enabled when WPEN bit is set high.

### 2.4 Serial Input (SI)

The SI pin is used to transfer data into the device. It receives instructions, addresses and data. Data are latched on the rising edge of the serial clock.

### 2.5 Serial Clock (SCK)

The SCK is used to synchronize the communication between a host and the 25XX160C/D. Instructions, addresses or data present on the SI pin are latched on the rising edge of the clock input, while data on the SO pin are updated after the falling edge of the clock input.

### 2.6 Hold (HOLD)

The HOLD pin is used to suspend transmission to the 25XX160C/D while in the middle of a serial sequence without having to retransmit the entire sequence again. It must be held high any time this function is not being used. Once the device is selected and a serial sequence is underway, the HOLD pin may be pulled low to pause further serial communication without resetting the serial sequence.

The HOLD pin must be brought low while SCK is low, otherwise the HOLD function will not be invoked until the next SCK high-to-low transition. The 25XX160C/D must remain selected during this sequence. The SI and SCK levels are “don’t cares” during the time the device is paused and transitions on these pins will be ignored. To resume serial communication, HOLD must be brought high while the SCK pin is low; otherwise serial communication will not be resumed until the next SCK high-to-low transition.

The SO line will tri-state immediately upon a high-to-low transition of the HOLD pin and will begin outputting again immediately upon a subsequent low-to-high transition of the HOLD pin, independent of the state of SCK.



# 25AA160C/D, 25LC160C/D

## 3.2 Read Sequence


The device is selected by pulling  $\overline{\text{CS}}$  low. The 8-bit `READ` instruction is transmitted to the 25XX160C/D followed by the 16-bit address, with the five MSBs of the address being “don’t care” bits. See [Figure 3-1](#) for more details.

After the correct `READ` instruction and address are sent, the data stored in the memory at the selected address are shifted out on the `SO` pin. The data stored in the memory at the next address can be read sequentially by continuing to provide clock pulses.

The internal Address Pointer is automatically incremented to the next higher address after each byte of data is shifted out. When the highest address is reached (07FFh), the address counter rolls over to

address 0000h allowing the read cycle to be continued indefinitely. The read operation is terminated by raising the  $\overline{\text{CS}}$  pin ([Figure 3-1](#)).

**FIGURE 3-1: READ SEQUENCE**





## 3.3 Write Sequence

Prior to any attempt to write data to the 25XX160C/D, the write enable latch must be set by issuing the `WREN` instruction (Figure 3-4). This is done by setting  $\overline{CS}$  low and then clocking out the proper instruction into the 25XX160C/D. After all eight bits of the instruction are transmitted, the  $\overline{CS}$  must be brought high to set the write enable latch.


If the write operation is initiated immediately after the `WREN` instruction without  $\overline{CS}$  being brought high, the data will not be written to the array because the write enable latch will not have been properly set.

Once the write enable latch is set, the user may proceed by setting the  $\overline{CS}$  low, issuing a `WRITE` instruction, followed by the 16-bit address, with the five MSBs of the address being “don’t care” bits and then the data to be written. Up to 16 bytes (25XX160C) or 32 bytes (25XX160D) of data can be sent to the device before a write cycle is necessary. The only restriction is that all of the bytes must reside in the same page.

**Note:** Page write operations are limited to writing bytes within a single physical page, **regardless** of the number of bytes actually being written. Physical page boundaries start at addresses that are integer multiples of the page buffer size (or ‘page size’) and end at addresses that are integer multiples of page size – 1. If a Page Write command attempts to write across a physical page boundary, the result is that the data wrap around to the beginning of the current page (overwriting data previously stored there), instead of being written to the next page as might be expected. It is therefore necessary for the application software to prevent page write operations that would attempt to cross a page boundary.


For the data to be actually written to the array, the  $\overline{CS}$  must be brought high after the Least Significant bit (D0) of the  $n^{th}$  data byte has been clocked in. If  $\overline{CS}$  is brought high at any other time, the write operation will not be completed. Refer to Figure 3-2 and Figure 3-3 for more detailed illustrations on the byte write sequence and the page write sequence, respectively. While the write is in progress, the STATUS register may be read to check the status of the WPEN, WIP, WEL, BP1 and BP0 bits (Figure 3-6). A read attempt of a memory array location will not be possible during a write cycle. When the write cycle is completed, the write enable latch is reset.

**FIGURE 3-2: BYTE WRITE SEQUENCE**



# 25AA160C/D, 25LC160C/D

FIGURE 3-3: PAGE WRITE SEQUENCE




## 3.4 Write Enable (WREN) and Write Disable (WRDI)

The 25XX160C/D contains a write enable latch. See [Table 3-4](#) for the Write-Protect Functionality Matrix. This latch must be set before any write operation will be completed internally. The WREN instruction will set the latch and the WRDI will reset the latch.


The following is a list of conditions under which the write enable latch will be reset:

- Power-up
- WRDI instruction successfully executed
- WRSR instruction successfully executed
- WRITE instruction successfully executed

**FIGURE 3-4: WRITE ENABLE SEQUENCE (WREN)**



**FIGURE 3-5: WRITE DISABLE SEQUENCE (WRDI)**



# 25AA160C/D, 25LC160C/D

## 3.5 Read Status Register (RDSR) Instruction

The Read Status Register (RDSR) instruction provides access to the STATUS register. The STATUS register may be read at any time, even during a write cycle. The STATUS register is formatted as follows:

TABLE 3-2: STATUS REGISTER

|      |   |   |   |     |     |     |     |
|------|---|---|---|-----|-----|-----|-----|
| 7    | 6 | 5 | 4 | 3   | 2   | 1   | 0   |
| W/R  | – | – | – | W/R | W/R | R   | R   |
| WPEN | X | X | X | BP1 | BP0 | WEL | WIP |

**Note 1:** W/R = writable/readable. R = read-only.


The **Write-In-Process (WIP)** bit indicates whether the 25XX160C/D is busy with a write operation. When set to a '1', a write is in progress, when set to a '0', no write is in progress. This bit is read-only.

The **Write Enable Latch (WEL)** bit indicates the status of the write enable latch and is read-only. When set to a '1', the latch allows writes to the array, when set to a '0', the latch prohibits writes to the array. The state of this bit can always be updated via the WREN or WRDI commands, regardless of the state of write protection on the STATUS register. These commands are shown in Figure 3-4 and Figure 3-5.

The **Block Protection (BP0 and BP1)** bits indicate which blocks are currently write-protected. These bits are set by the user issuing the WRSR instruction. These bits are nonvolatile and are shown in Table 3-3.

See Figure 3-6 for the RDSR timing sequence.

FIGURE 3-6: READ STATUS REGISTER TIMING SEQUENCE (RDSR)



## 3.6 Write Status Register (WRSR) Instruction

The Write Status Register (WRSR) instruction allows the user to write to the nonvolatile bits in the STATUS register as shown in Table 3-2. The user is able to select one of four levels of protection for the array by writing to the appropriate bits in the STATUS register. The array is divided up into four segments. The user has the ability to write-protect none, one, two or all four of the segments of the array. The partitioning is controlled as shown in Table 3-3.

The Write-Protect Enable (WPEN) bit is a nonvolatile bit that is available as an enable bit for the  $\overline{WP}$  pin. The Write-Protect ( $\overline{WP}$ ) pin and the Write-Protect Enable (WPEN) bit in the STATUS register control the programmable hardware write-protect feature.

Hardware write protection is enabled when  $\overline{WP}$  pin is low and the WPEN bit is high. Hardware write protection is disabled when either the  $\overline{WP}$  pin is high or the WPEN bit is low. When the chip is hardware write-protected, only writes to nonvolatile bits in the STATUS register are disabled. See Table 3-4 for a matrix of functionality on the WPEN bit.

See Figure 3-7 for the WRSR timing sequence.

**TABLE 3-3: ARRAY PROTECTION**


| BP1 | BP0 | Array Addresses Write-Protected |
|-----|-----|---------------------------------|
| 0   | 0   | none                            |
| 0   | 1   | upper 1/4 (0600h-07FFh)         |
| 1   | 0   | upper 1/2 (0400h-07FFh)         |
| 1   | 1   | all (0000h-07FFh)               |

**TABLE 3-4: WRITE-PROTECT FUNCTIONALITY MATRIX**

| WEL (SR bit 1) | WPEN (SR bit 7) | $\overline{WP}$ (pin 3) | Protected Blocks | Unprotected Blocks | STATUS Register |
|----------------|-----------------|-------------------------|------------------|--------------------|-----------------|
| 0              | x               | x                       | Protected        | Protected          | Protected       |
| 1              | 0               | x                       | Protected        | Writable           | Writable        |
| 1              | 1               | 0 (low)                 | Protected        | Writable           | Protected       |
| 1              | 1               | 1 (high)                | Protected        | Writable           | Writable        |

**Note 1:** x = don't care

**FIGURE 3-7: WRITE STATUS REGISTER TIMING SEQUENCE (WRSR)**



# 25AA160C/D, 25LC160C/D

---

## 4.0 DATA PROTECTION

The following protection has been implemented to prevent inadvertent writes to the array:

- The write enable latch is reset on power-up
- A write enable instruction must be issued to set the write enable latch
- After a byte write, page write or STATUS register write, the write enable latch is reset
- $\overline{CS}$  must be set high after the proper number of clock cycles to start an internal write cycle
- Access to the array during an internal write cycle is ignored and programming is continued

## 5.0 POWER-ON STATE

The 25XX160C/D powers on in the following state:


- The device is in low-power Standby mode ( $\overline{CS} = 1$ )
- The write enable latch is reset
- SO is in high-impedance state
- A high-to-low-level transition on  $\overline{CS}$  is required to enter active state

# 25AA160C/D, 25LC160C/D


## 6.0 PACKAGING INFORMATION

### 6.1 Package Marking Information


8-Lead MSOP (150 mil)




Example




8-Lead PDIP (300 mil)




Example




8-Lead SOIC




Example




8-Lead 2x3 TDFN




Example



8-Lead TSSOP



Example



| Part Number | 1 <sup>st</sup> Line Marking Codes |          |          |         |         |       |
|-------------|------------------------------------|----------|----------|---------|---------|-------|
|             | MSOP                               | PDIP     | SOIC     | TDFN    |         | TSSOP |
|             |                                    |          |          | I-Temp. | E-Temp. |       |
| 25AA160C    | 5AACT                              | 25AA160C | 25AA16CT | C51     | —       | 5AAC  |
| 25AA160D    | 5AADT                              | 25AA160D | 25AA16DT | C61     | EF2     | 5AAD  |
| 25LC160C    | 5LACT                              | 25LC160C | 25LC16CT | C54     | C55     | 5LAC  |
| 25LC160D    | 5LADT                              | 25LC160D | 25LC16DT | C64     | C65     | 5LAD  |

# 25AA160C/D, 25LC160C/D

---

|                |        |                                                                  |
|----------------|--------|------------------------------------------------------------------|
| <b>Legend:</b> | XX...X | Part number or part number code                                  |
|                | T      | Temperature (I, E)                                               |
|                | Y      | Year code (last digit of calendar year)                          |
|                | YY     | Year code (last 2 digits of calendar year)                       |
|                | WW     | Week code (week of January 1 is week '01')                       |
|                | NNN    | Alphanumeric traceability code (2 characters for small packages) |
|                | e3     | RoHS-compliant JEDEC® designator for Matte Tin (Sn)              |

**Note:** For very small packages with no room for the RoHS-compliant JEDEC® designator e3, the marking will only appear on the outer carton or reel label.

**Note:** In the event the full Microchip part number cannot be marked on one line, it will be carried over to the next line, thus limiting the number of available characters for customer-specific information.






# 25AA160C/D, 25LC160C/D

## 8-Lead Plastic Micro Small Outline Package (MS) [MSOP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



| Units                    |        | MILLIMETERS |      |      |
|--------------------------|--------|-------------|------|------|
| Dimension Limits         |        | MIN         | NOM  | MAX  |
| Number of Pins           | N      |             | 8    |      |
| Pitch                    | e      | 0.65 BSC    |      |      |
| Overall Height           | A      | -           | -    | 1.10 |
| Molded Package Thickness | A2     | 0.75        | 0.85 | 0.95 |
| Standoff                 | A1     | 0.00        | -    | 0.15 |
| Overall Width            | E      | 4.90 BSC    |      |      |
| Molded Package Width     | E1     | 3.00 BSC    |      |      |
| Overall Length           | D      | 3.00 BSC    |      |      |
| Foot Length              | L      | 0.40        | 0.60 | 0.80 |
| Footprint                | L1     | 0.95 REF    |      |      |
| Foot Angle               | $\phi$ | 0°          | -    | 8°   |
| Lead Thickness           | c      | 0.08        | -    | 0.23 |
| Lead Width               | b      | 0.22        | -    | 0.40 |

### Notes:


- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.15mm per side.
- Dimensioning and tolerancing per ASME Y14.5M.  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.  
REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-111C Sheet 2 of 2

# 25AA160C/D, 25LC160C/D

## 8-Lead Plastic Micro Small Outline Package (MS) [MSOP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

| Dimension Limits        | Units | MILLIMETERS |      |      |
|-------------------------|-------|-------------|------|------|
|                         |       | MIN         | NOM  | MAX  |
| Contact Pitch           | E     | 0.65 BSC    |      |      |
| Contact Pad Spacing     | C     |             | 4.40 |      |
| Overall Width           | Z     |             |      | 5.85 |
| Contact Pad Width (X8)  | X1    |             |      | 0.45 |
| Contact Pad Length (X8) | Y1    |             |      | 1.45 |
| Distance Between Pads   | G1    | 2.95        |      |      |
| Distance Between Pads   | GX    | 0.20        |      |      |

**Notes:**

1. Dimensioning and tolerancing per ASME Y14.5M


BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing No. C04-2111A

# 25AA160C/D, 25LC160C/D

## 8-Lead Plastic Dual In-Line (P) - 300 mil Body [PDIP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Microchip Technology Drawing No. C04-018-P Rev E Sheet 1 of 2

# 25AA160C/D, 25LC160C/D

## 8-Lead Plastic Dual In-Line (P) - 300 mil Body [PDIP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>

### ALTERNATE LEAD DESIGN (NOTE 5)



| Units                      |      | INCHES   |      |      |
|----------------------------|------|----------|------|------|
| Dimension Limits           |      | MIN      | NOM  | MAX  |
| Number of Pins             | N    | 8        |      |      |
| Pitch                      | e    | .100 BSC |      |      |
| Top to Seating Plane       | A    | -        | -    | .210 |
| Molded Package Thickness   | A2   | .115     | .130 | .195 |
| Base to Seating Plane      | A1   | .015     | -    | -    |
| Shoulder to Shoulder Width | E    | .290     | .310 | .325 |
| Molded Package Width       | E1   | .240     | .250 | .280 |
| Overall Length             | D    | .348     | .365 | .400 |
| Tip to Seating Plane       | L    | .115     | .130 | .150 |
| Lead Thickness             | c    | .008     | .010 | .015 |
| Upper Lead Width           | b1   | .040     | .060 | .070 |
| Lower Lead Width           | b    | .014     | .018 | .022 |
| Overall Row Spacing        | § eB | -        | -    | .430 |

#### Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- § Significant Characteristic
- Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed .010" per side.
- Dimensioning and tolerancing per ASME Y14.5M  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- Lead design above seating plane may vary, based on assembly vendor.


Microchip Technology Drawing No. C04-018-P Rev E Sheet 2 of 2



# 25AA160C/D, 25LC160C/D

## 8-Lead Plastic Small Outline (SN) - Narrow, 3.90 mm (.150 In.) Body [SOIC]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



| Units                    |    | MILLIMETERS |     |      |
|--------------------------|----|-------------|-----|------|
| Dimension Limits         |    | MIN         | NOM | MAX  |
| Number of Pins           | N  | 8           |     |      |
| Pitch                    | e  | 1.27 BSC    |     |      |
| Overall Height           | A  | -           | -   | 1.75 |
| Molded Package Thickness | A2 | 1.25        | -   | -    |
| Standoff §               | A1 | 0.10        | -   | 0.25 |
| Overall Width            | E  | 6.00 BSC    |     |      |
| Molded Package Width     | E1 | 3.90 BSC    |     |      |
| Overall Length           | D  | 4.90 BSC    |     |      |
| Chamfer (Optional)       | h  | 0.25        | -   | 0.50 |
| Foot Length              | L  | 0.40        | -   | 1.27 |
| Footprint                | L1 | 1.04 REF    |     |      |
| Foot Angle               | φ  | 0°          | -   | 8°   |
| Lead Thickness           | c  | 0.17        | -   | 0.25 |
| Lead Width               | b  | 0.31        | -   | 0.51 |
| Mold Draft Angle Top     | α  | 5°          | -   | 15°  |
| Mold Draft Angle Bottom  | β  | 5°          | -   | 15°  |

### Notes:


- Pin 1 visual index feature may vary, but must be located within the hatched area.
- § Significant Characteristic
- Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.15mm per side.
- Dimensioning and tolerancing per ASME Y14.5M  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.  
REF: Reference Dimension, usually without tolerance, for information purposes only.
- Datums A & B to be determined at Datum H.

Microchip Technology Drawing No. C04-057-SN Rev F Sheet 2 of 2

# 25AA160C/D, 25LC160C/D

## 8-Lead Plastic Small Outline (SN) - Narrow, 3.90 mm (.150 In.) Body [SOIC]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



### RECOMMENDED LAND PATTERN

| Units                   |    | MILLIMETERS |      |      |
|-------------------------|----|-------------|------|------|
| Dimension Limits        |    | MIN         | NOM  | MAX  |
| Contact Pitch           | E  | 1.27 BSC    |      |      |
| Contact Pad Spacing     | C  |             | 5.40 |      |
| Contact Pad Width (X8)  | X1 |             |      | 0.60 |
| Contact Pad Length (X8) | Y1 |             |      | 1.55 |

#### Notes:

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.


Microchip Technology Drawing C04-2057-SN Rev F



# 25AA160C/D, 25LC160C/D

## 8-Lead Plastic Dual Flat, No Lead Package (MN) – 2x3x0.8 mm Body [TDFN] With 1.4x1.3 mm Exposed Pad (JEDEC Package type WDFN)

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Microchip Technology Drawing No. C04-129-MN Rev E Sheet 1 of 2

# 25AA160C/D, 25LC160C/D

## 8-Lead Plastic Dual Flat, No Lead Package (MN) – 2x3x0.8 mm Body [TDFN] With 1.4x1.3 mm Exposed Pad (JEDEC Package type WDFN)

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



|                        |    | Units | MILLIMETERS |      |      |
|------------------------|----|-------|-------------|------|------|
| Dimension Limits       |    |       | MIN         | NOM  | MAX  |
| Number of Pins         | N  |       | 8           |      |      |
| Pitch                  | e  |       | 0.50 BSC    |      |      |
| Overall Height         | A  |       | 0.70        | 0.75 | 0.80 |
| Standoff               | A1 |       | 0.00        | 0.02 | 0.05 |
| Contact Thickness      | A3 |       | 0.20 REF    |      |      |
| Overall Length         | D  |       | 2.00 BSC    |      |      |
| Overall Width          | E  |       | 3.00 BSC    |      |      |
| Exposed Pad Length     | D2 |       | 1.35        | 1.40 | 1.45 |
| Exposed Pad Width      | E2 |       | 1.25        | 1.30 | 1.35 |
| Contact Width          | b  |       | 0.20        | 0.25 | 0.30 |
| Contact Length         | L  |       | 0.25        | 0.30 | 0.45 |
| Contact-to-Exposed Pad | K  |       | 0.20        | -    | -    |

### Notes:


- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package may have one or more exposed tie bars at ends.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.  
REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing No. C04-129-MN Rev E Sheet 2 of 2

# 25AA160C/D, 25LC160C/D

## 8-Lead Plastic Dual Flat, No Lead Package (MN) – 2x3x0.8 mm Body [TDFN] With 1.4x1.3 mm Exposed Pad (JEDEC Package type WDFN)

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

| Units                      |    | MILLIMETERS |          |      |
|----------------------------|----|-------------|----------|------|
| Dimension Limits           |    | MIN         | NOM      | MAX  |
| Contact Pitch              | E  |             | 0.50 BSC |      |
| Optional Center Pad Width  | X2 |             |          | 1.60 |
| Optional Center Pad Length | Y2 |             |          | 1.50 |
| Contact Pad Spacing        | C  |             | 2.90     |      |
| Contact Pad Width (X8)     | X1 |             |          | 0.25 |
| Contact Pad Length (X8)    | Y1 |             |          | 0.85 |
| Thermal Via Diameter       | V  |             | 0.30     |      |
| Thermal Via Pitch          | EV |             | 1.00     |      |

**Notes:**


1. Dimensioning and tolerancing per ASME Y14.5M  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing No. C04-129-MN Rev. B


# 25AA160C/D, 25LC160C/D

## 8-Lead Plastic Thin Shrink Small Outline (ST) - 4.4 mm Body [TSSOP]


**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



TOP VIEW



SIDE VIEW




VIEW A-A

Microchip Technology Drawing C04-086 Rev C Sheet 1 of 2

# 25AA160C/D, 25LC160C/D

## 8-Lead Plastic Thin Shrink Small Outline (ST) - 4.4 mm Body [TSSOP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



|                          |        | Units | MILLIMETERS |          |      |
|--------------------------|--------|-------|-------------|----------|------|
| Dimension Limits         |        |       | MIN         | NOM      | MAX  |
| Number of Pins           | N      |       | 8           |          |      |
| Pitch                    | e      |       | 0.65 BSC    |          |      |
| Overall Height           | A      |       | -           | -        | 1.20 |
| Molded Package Thickness | A2     |       | 0.80        | 1.00     | 1.05 |
| Standoff                 | A1     |       | 0.05        | -        | -    |
| Overall Width            | E      |       |             | 6.40 BSC |      |
| Molded Package Width     | E1     |       | 4.30        | 4.40     | 4.50 |
| Overall Length           | D      |       | 2.90        | 3.00     | 3.10 |
| Foot Length              | L      |       | 0.45        | 0.60     | 0.75 |
| Footprint                | L1     |       | 1.00 REF    |          |      |
| Lead Thickness           | c      |       | 0.09        | -        | 0.25 |
| Foot Angle               | $\phi$ |       | 0°          | 4°       | 8°   |
| Lead Width               | b      |       | 0.19        | -        | 0.30 |

### Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.20mm per side.
- Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.


REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-086 Rev C Sheet 2 of 2

# 25AA160C/D, 25LC160C/D

## 8-Lead Plastic Thin Shrink Small Outline (ST) - 4.4 mm Body [TSSOP]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



### RECOMMENDED LAND PATTERN

| Units                          |    | MILLIMETERS |      |      |
|--------------------------------|----|-------------|------|------|
| Dimension Limits               |    | MIN         | NOM  | MAX  |
| Contact Pitch                  | E  | 0.65 BSC    |      |      |
| Contact Pad Spacing            | C  |             | 5.80 |      |
| Contact Pad Width (X8)         | X1 |             |      | 0.45 |
| Contact Pad Length (X8)        | Y1 |             |      | 1.50 |
| Contact Pad to Center Pad (X6) | G1 | 0.20        |      |      |

#### Notes:

1. Dimensioning and tolerancing per ASME Y14.5M  
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-2086 Rev B

## APPENDIX A: REVISION HISTORY

### Revision C (11/2021)

Added Product Identification System section for Automotive; Updated PDIP, SOIC, TDFN and TSSOP package drawings; Replaced terminology “Master” and “Slave” with “Host” and “Client”, respectively; Replaced “Automotive (E):” designation with “Extended (E):” designation; Reformatted some sections for better readability.

### Revision B (01/2013)

Revised Automotive E-temp; Revised Table 1-2, Param. No. 21; Updated Package Info.

### Revision A (4/2009)

Initial release of this document.

# 25AA160C/D, 25LC160C/D

---

## THE MICROCHIP WEBSITE

Microchip provides online support via our website at [www.microchip.com](http://www.microchip.com). This website is used as a means to make files and information easily available to customers. Accessible by using your favorite Internet browser, the website contains the following information:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQ), technical support requests, online discussion groups, Microchip consultant program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

## CUSTOMER CHANGE NOTIFICATION SERVICE

Microchip's customer notification service helps keep customers current on Microchip products. Subscribers will receive e-mail notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, access the Microchip website at [www.microchip.com](http://www.microchip.com). Under "Support", click on "Customer Change Notification" and follow the registration instructions.

## CUSTOMER SUPPORT

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Field Application Engineer (FAE)
- Technical Support

Customers should contact their distributor, representative or Field Application Engineer (FAE) for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in the back of this document.

**Technical support is available through the website at:** <http://microchip.com/support>



# 25AA160C/D, 25LC160C/D

## PRODUCT IDENTIFICATION SYSTEM (NON-AUTOMOTIVE)

To order or obtain information, e.g., on pricing or delivery, refer to the factory or the listed sales office.

| <b>PART NO.</b>                                                                                                                                                                                                                                                                                                                                                                 |                             | <b>X<sup>(1)</sup></b> | <b>-X</b>                | <b>/XX</b>     | <b>Examples</b>                                                                                               |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|------------------------|--------------------------|----------------|---------------------------------------------------------------------------------------------------------------|
| <b>Device</b>                                                                                                                                                                                                                                                                                                                                                                   | <b>Tape and Reel Option</b> |                        | <b>Temperature Range</b> | <b>Package</b> |                                                                                                               |
| <b>Device:</b><br>25AA160C = 16-Kbit, 1.8V, 16-Byte Page SPI Serial EEPROM<br>25AA160D = 16-Kbit, 1.8V, 32-Byte Page SPI Serial EEPROM<br>25LC160C = 16-Kbit, 2.5V, 16-Byte Page SPI Serial EEPROM<br>25LC160D = 16-Kbit, 2.5V, 32-Byte Page SPI Serial EEPROM                                                                                                                  |                             |                        |                          |                |                                                                                                               |
| <b>Tape and Reel Option:</b><br>Blank = Standard packaging (tube)<br>T = Tape and Reel <sup>(1)</sup>                                                                                                                                                                                                                                                                           |                             |                        |                          |                |                                                                                                               |
| <b>Temperature Range:</b><br>I = -40°C to +85°C (Industrial)<br>E = -40°C to +125°C (Extended)                                                                                                                                                                                                                                                                                  |                             |                        |                          |                |                                                                                                               |
| <b>Package:</b><br>MS = Plastic Micro Small Outline – 8-Lead (MSOP)<br>P = Plastic Dual In-Line – 300 mil Body, 8-Lead (PDIP)<br>SN = Plastic Small Outline - Narrow, 3.90 mm (.150 In) Body, 8-Lead (SOIC)<br>MNY <sup>(2)</sup> = Plastic Dual Flat, No Lead Package – 2x3x0.8 mm Body, 8-Lead (TDFN)<br>ST = Plastic Thin Shrink Small Outline – 4x4 mm Body, 8-Lead (TSSOP) |                             |                        |                          |                |                                                                                                               |
|                                                                                                                                                                                                                                                                                                                                                                                 |                             |                        |                          |                | a) 25AA160C-I/MS: 16-Kbit, 16-byte page, 1.8V Serial EEPROM, Industrial temp., MSOP package.                  |
|                                                                                                                                                                                                                                                                                                                                                                                 |                             |                        |                          |                | b) 25AA160CT-I/SN: 16-Kbit, 16-byte page, 1.8V Serial EEPROM, Tape and Reel, Industrial temp., SOIC package.  |
|                                                                                                                                                                                                                                                                                                                                                                                 |                             |                        |                          |                | c) 25LC160DT-I/MNY: 16-Kbit, 32-byte page, 2.5V Serial EEPROM, Tape and Reel, Industrial temp., TDFN package. |
|                                                                                                                                                                                                                                                                                                                                                                                 |                             |                        |                          |                | d) 25LC160DT-I/ST: 16-Kbit, 32-byte page, 2.5V Serial EEPROM, Tape and Reel, Industrial temp., TSSOP package. |
|                                                                                                                                                                                                                                                                                                                                                                                 |                             |                        |                          |                | e) 25AA160DT-E/SN: 16-Kbit, 32-byte page, 1.8V Serial EEPROM, Tape and Reel, Extended temp., SOIC package.    |
| <b>Note 1:</b> Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.                                                                                             |                             |                        |                          |                |                                                                                                               |
| <b>Note 2:</b> "Y" indicates a Nickel Palladium Gold (NiPdAu) finish.                                                                                                                                                                                                                                                                                                           |                             |                        |                          |                |                                                                                                               |

# 25AA160C/D, 25LC160C/D

## PRODUCT IDENTIFICATION SYSTEM (AUTOMOTIVE)

To order or obtain information, e.g., on pricing or delivery, refer to the factory or the listed sales office.

| PART NO.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                      | X <sup>(1)</sup>  | -X                                                                    | /XX     | XXX <sup>(3,4)</sup> | Examples |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-------------------|-----------------------------------------------------------------------|---------|----------------------|----------|---------|----------|---|-----------------------------------------------|--|----------|---|-----------------------------------------------|--|----------|---|-----------------------------------------------|--|----------|---|-----------------------------------------------|-----------------------|-------|---|---------------------------|--|---|---|------------------------------|--------------------|---|---|----------------------------------|--|---|---|-----------------------------------|----------|----|---|---------------------------------------------|--|----|---|-----------------------------------------------------------------------|--|--------------------|---|---------------------------------------------------------------------|--|----|---|-----------------------------------------------------------------|---------------------------|--------|---|----------------------------------|--|--------|---|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Tape and Reel Option | Temperature Range | Package                                                               | Variant |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <table><tr><td>Device:</td><td>25AA160C</td><td>=</td><td>16-Kbit, 1.8V, 16-Byte Page SPI Serial EEPROM</td></tr><tr><td></td><td>25AA160D</td><td>=</td><td>16-Kbit, 1.8V, 32-Byte Page SPI Serial EEPROM</td></tr><tr><td></td><td>25LC160C</td><td>=</td><td>16-Kbit, 2.5V, 16-Byte Page SPI Serial EEPROM</td></tr><tr><td></td><td>25LC160D</td><td>=</td><td>16-Kbit, 2.5V, 32-Byte Page SPI Serial EEPROM</td></tr><tr><td>Tape and Reel Option:</td><td>Blank</td><td>=</td><td>Standard packaging (tube)</td></tr><tr><td></td><td>T</td><td>=</td><td>Tape and Reel<sup>(1)</sup></td></tr><tr><td>Temperature Range:</td><td>I</td><td>=</td><td>-40°C to+85°C (AEC-Q100 Grade 3)</td></tr><tr><td></td><td>E</td><td>=</td><td>-40°C to+125°C (AEC-Q100 Grade 1)</td></tr><tr><td>Package:</td><td>MS</td><td>=</td><td>Plastic Micro Small Outline – 8-Lead (MSOP)</td></tr><tr><td></td><td>SN</td><td>=</td><td>Plastic Small Outline - Narrow, 3.90 mm (.150 In) Body, 8-Lead (SOIC)</td></tr><tr><td></td><td>MNY<sup>(2)</sup></td><td>=</td><td>Plastic Dual Flat, No Lead Package – 2x3x0.8 mm Body, 8-Lead (TDFN)</td></tr><tr><td></td><td>ST</td><td>=</td><td>Plastic Thin Shrink Small Outline – 4x4 mm Body, 8-Lead (TSSOP)</td></tr><tr><td>Variant:<sup>(3,4)</sup></td><td>16KVAO</td><td>=</td><td>Standard Automotive, 16K Process</td></tr><tr><td></td><td>16KVXX</td><td>=</td><td>Customer-Specific Automotive, 16K Process</td></tr></table> |                      |                   |                                                                       |         |                      |          | Device: | 25AA160C | = | 16-Kbit, 1.8V, 16-Byte Page SPI Serial EEPROM |  | 25AA160D | = | 16-Kbit, 1.8V, 32-Byte Page SPI Serial EEPROM |  | 25LC160C | = | 16-Kbit, 2.5V, 16-Byte Page SPI Serial EEPROM |  | 25LC160D | = | 16-Kbit, 2.5V, 32-Byte Page SPI Serial EEPROM | Tape and Reel Option: | Blank | = | Standard packaging (tube) |  | T | = | Tape and Reel <sup>(1)</sup> | Temperature Range: | I | = | -40°C to+85°C (AEC-Q100 Grade 3) |  | E | = | -40°C to+125°C (AEC-Q100 Grade 1) | Package: | MS | = | Plastic Micro Small Outline – 8-Lead (MSOP) |  | SN | = | Plastic Small Outline - Narrow, 3.90 mm (.150 In) Body, 8-Lead (SOIC) |  | MNY <sup>(2)</sup> | = | Plastic Dual Flat, No Lead Package – 2x3x0.8 mm Body, 8-Lead (TDFN) |  | ST | = | Plastic Thin Shrink Small Outline – 4x4 mm Body, 8-Lead (TSSOP) | Variant: <sup>(3,4)</sup> | 16KVAO | = | Standard Automotive, 16K Process |  | 16KVXX | = | Customer-Specific Automotive, 16K Process | <p>a) 25AA160D-E/SN16KVAO: 16-Kbit, 32-byte page, 1.8V Serial EEPROM, Automotive Grade 1, SOIC package.</p> <p>b) 25AA160DT-E/SN16KVAO: 16-Kbit, 32-byte page, 1.8V Serial EEPROM, Tape and Reel, Automotive Grade 1, SOIC package.</p> <p>c) 25LC160C-I/SN16KVAO: 16-Kbit, 16-byte page, 2.5V Serial EEPROM, Automotive Grade 3, SOIC package.</p> <p>d) 25LC160DT-I/MNY16KVAO: 16-Kbit, 32-byte page, 2.5V Serial EEPROM, Tape and Reel, Automotive Grade 3, TDFN package.</p> <p>e) 25LC160D-E/MNY16KVAO: 16-Kbit, 32-byte page, 2.5V Serial EEPROM, Automotive Grade 1, TDFN package.</p> <p>f) 25LC160D-E/ST16KVAO: 16-Kbit, 32-byte page, 2.5V Serial EEPROM, Automotive Grade 1, TSSOP package.</p> <p>g) 25LC160DT-E/ST16KVAO: 16-Kbit, 32-byte page, 2.5V Serial EEPROM, Tape and Reel, Automotive Grade 1, TSSOP package.</p> <p>h) 25LC160C-E/SN16KVAO: 16-Kbit, 16-byte page, 2.5V Serial EEPROM, Automotive Grade 1, SOIC package.</p> <p><b>Note 1:</b> Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.</p> <p><b>2:</b> “Y” indicates a Nickel Palladium Gold (NiPdAu) finish.</p> <p><b>3:</b> The VAO/VXX automotive variants have been designed, manufactured, tested and qualified in accordance with AEC-Q100 requirements for automotive applications.</p> <p><b>4:</b> For customers requesting a PPAP, a customer-specific part number will be generated and provided. A PPAP is not provided for VAO part numbers.</p> |
| Device:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 25AA160C             | =                 | 16-Kbit, 1.8V, 16-Byte Page SPI Serial EEPROM                         |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 25AA160D             | =                 | 16-Kbit, 1.8V, 32-Byte Page SPI Serial EEPROM                         |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 25LC160C             | =                 | 16-Kbit, 2.5V, 16-Byte Page SPI Serial EEPROM                         |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 25LC160D             | =                 | 16-Kbit, 2.5V, 32-Byte Page SPI Serial EEPROM                         |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Tape and Reel Option:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Blank                | =                 | Standard packaging (tube)                                             |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | T                    | =                 | Tape and Reel <sup>(1)</sup>                                          |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Temperature Range:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | I                    | =                 | -40°C to+85°C (AEC-Q100 Grade 3)                                      |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | E                    | =                 | -40°C to+125°C (AEC-Q100 Grade 1)                                     |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Package:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | MS                   | =                 | Plastic Micro Small Outline – 8-Lead (MSOP)                           |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | SN                   | =                 | Plastic Small Outline - Narrow, 3.90 mm (.150 In) Body, 8-Lead (SOIC) |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | MNY <sup>(2)</sup>   | =                 | Plastic Dual Flat, No Lead Package – 2x3x0.8 mm Body, 8-Lead (TDFN)   |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | ST                   | =                 | Plastic Thin Shrink Small Outline – 4x4 mm Body, 8-Lead (TSSOP)       |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Variant: <sup>(3,4)</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 16KVAO               | =                 | Standard Automotive, 16K Process                                      |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 16KVXX               | =                 | Customer-Specific Automotive, 16K Process                             |         |                      |          |         |          |   |                                               |  |          |   |                                               |  |          |   |                                               |  |          |   |                                               |                       |       |   |                           |  |   |   |                              |                    |   |   |                                  |  |   |   |                                   |          |    |   |                                             |  |    |   |                                                                       |  |                    |   |                                                                     |  |    |   |                                                                 |                           |        |   |                                  |  |        |   |                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

---

**Note the following details of the code protection feature on Microchip products:**

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
  - Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
  - Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
  - Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.
- 

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at <https://www.microchip.com/en-us/support/design-help/client-support-services>.

THIS INFORMATION IS PROVIDED BY MICROCHIP “AS IS”. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP’S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer’s risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

For information regarding Microchip’s Quality Management Systems, please visit [www.microchip.com/quality](http://www.microchip.com/quality).

**Trademarks**

The Microchip name and logo, the Microchip logo, Adaptec, AnyRate, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Klear, LANCheck, LinkMD, maxStylus, maxTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzr, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, IntelliMOS, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, QuietWire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, TrueTime, WinPath, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, GridTime, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, NVm Express, NVMe, Omniscient Code Generation, PICDEM, PICDEM.net, PICKit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQL, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, Symmcom, and Trusted Time are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2009-2021, Microchip Technology Incorporated and its subsidiaries.

All Rights Reserved.

ISBN: 978-1-5224-9262-7

## Worldwide Sales and Service

### AMERICAS

**Corporate Office**  
2355 West Chandler Blvd.  
Chandler, AZ 85224-6199  
Tel: 480-792-7200  
Fax: 480-792-7277  
Technical Support:  
<http://www.microchip.com/support>  
Web Address:  
[www.microchip.com](http://www.microchip.com)

**Atlanta**  
Duluth, GA  
Tel: 678-957-9614  
Fax: 678-957-1455

**Austin, TX**  
Tel: 512-257-3370

**Boston**  
Westborough, MA  
Tel: 774-760-0087  
Fax: 774-760-0088

**Chicago**  
Itasca, IL  
Tel: 630-285-0071  
Fax: 630-285-0075

**Dallas**  
Addison, TX  
Tel: 972-818-7423  
Fax: 972-818-2924

**Detroit**  
Novi, MI  
Tel: 248-848-4000

**Houston, TX**  
Tel: 281-894-5983

**Indianapolis**  
Noblesville, IN  
Tel: 317-773-8323  
Fax: 317-773-5453  
Tel: 317-536-2380

**Los Angeles**  
Mission Viejo, CA  
Tel: 949-462-9523  
Fax: 949-462-9608  
Tel: 951-273-7800

**Raleigh, NC**  
Tel: 919-844-7510

**New York, NY**  
Tel: 631-435-6000

**San Jose, CA**  
Tel: 408-735-9110  
Tel: 408-436-4270

**Canada - Toronto**  
Tel: 905-695-1980  
Fax: 905-695-2078

### ASIA/PACIFIC

**Australia - Sydney**  
Tel: 61-2-9868-6733

**China - Beijing**  
Tel: 86-10-8569-7000

**China - Chengdu**  
Tel: 86-28-8665-5511

**China - Chongqing**  
Tel: 86-23-8980-9588

**China - Dongguan**  
Tel: 86-769-8702-9880

**China - Guangzhou**  
Tel: 86-20-8755-8029

**China - Hangzhou**  
Tel: 86-571-8792-8115

**China - Hong Kong SAR**  
Tel: 852-2943-5100

**China - Nanjing**  
Tel: 86-25-8473-2460

**China - Qingdao**  
Tel: 86-532-8502-7355

**China - Shanghai**  
Tel: 86-21-3326-8000

**China - Shenyang**  
Tel: 86-24-2334-2829

**China - Shenzhen**  
Tel: 86-755-8864-2200

**China - Suzhou**  
Tel: 86-186-6233-1526

**China - Wuhan**  
Tel: 86-27-5980-5300

**China - Xian**  
Tel: 86-29-8833-7252

**China - Xiamen**  
Tel: 86-592-2388138

**China - Zhuhai**  
Tel: 86-756-3210040

### ASIA/PACIFIC

**India - Bangalore**  
Tel: 91-80-3090-4444

**India - New Delhi**  
Tel: 91-11-4160-8631

**India - Pune**  
Tel: 91-20-4121-0141

**Japan - Osaka**  
Tel: 81-6-6152-7160

**Japan - Tokyo**  
Tel: 81-3-6880-3770

**Korea - Daegu**  
Tel: 82-53-744-4301

**Korea - Seoul**  
Tel: 82-2-554-7200

**Malaysia - Kuala Lumpur**  
Tel: 60-3-7651-7906

**Malaysia - Penang**  
Tel: 60-4-227-8870

**Philippines - Manila**  
Tel: 63-2-634-9065

**Singapore**  
Tel: 65-6334-8870

**Taiwan - Hsin Chu**  
Tel: 886-3-577-8366

**Taiwan - Kaohsiung**  
Tel: 886-7-213-7830

**Taiwan - Taipei**  
Tel: 886-2-2508-8600

**Thailand - Bangkok**  
Tel: 66-2-694-1351

**Vietnam - Ho Chi Minh**  
Tel: 84-28-5448-2100

### EUROPE

**Austria - Wels**  
Tel: 43-7242-2244-39  
Fax: 43-7242-2244-393

**Denmark - Copenhagen**  
Tel: 45-4485-5910  
Fax: 45-4485-2829

**Finland - Espoo**  
Tel: 358-9-4520-820

**France - Paris**  
Tel: 33-1-69-53-63-20  
Fax: 33-1-69-30-90-79

**Germany - Garching**  
Tel: 49-8931-9700

**Germany - Haan**  
Tel: 49-2129-3766400

**Germany - Heilbronn**  
Tel: 49-7131-72400

**Germany - Karlsruhe**  
Tel: 49-721-625370

**Germany - Munich**  
Tel: 49-89-627-144-0  
Fax: 49-89-627-144-44

**Germany - Rosenheim**  
Tel: 49-8031-354-560

**Israel - Ra'anana**  
Tel: 972-9-744-7705

**Italy - Milan**  
Tel: 39-0331-742611  
Fax: 39-0331-466781

**Italy - Padova**  
Tel: 39-049-7625286

**Netherlands - Drunen**  
Tel: 31-416-690399  
Fax: 31-416-690340

**Norway - Trondheim**  
Tel: 47-7288-4388

**Poland - Warsaw**  
Tel: 48-22-3325737

**Romania - Bucharest**  
Tel: 40-21-407-87-50

**Spain - Madrid**  
Tel: 34-91-708-08-90  
Fax: 34-91-708-08-91

**Sweden - Gothenberg**  
Tel: 46-31-704-60-40

**Sweden - Stockholm**  
Tel: 46-8-5090-4654

**UK - Wokingham**  
Tel: 44-118-921-5800  
Fax: 44-118-921-5820