






## 68V N-Channel Trench MOSFET(Preliminary)

|                                                                                                                                                                                                                                                                                                                                                                                                                       |         |                                                                                                                                                                                                                                                 |         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| <b>General Description</b> <ul style="list-style-type: none"><li>● Trench Power Technology</li><li>● Low <math>R_{DS(ON)}</math></li><li>● Low Gate Charge</li><li>● Optimized for Fast-switching Applications`</li></ul> <b>Applications</b> <ul style="list-style-type: none"><li>● Synchronous Rectification in DC/DC and AC/DC Converters</li><li>● Isolated DC/DC Converters in Telecom and Industrial</li></ul> |         | <b>Product Summary</b><br><br>$V_{DS}$ 68V<br>$I_D$ (at $V_{GS}=10V$ ) 95A<br>$R_{DS(ON)}$ (at $V_{GS}=10V$ ) < 7.5m $\Omega$<br><br>100% UIS Tested<br><br> |         |
| <br>TO-251                                                                                                                                                                                                                                                                                                                           |         | <br>TO-252                                                                                                                                                     |         |
|                                                                                                                                                                                                                                                                                                                                    |         |                                                                                                                                                                                                                                                 |         |
| Device                                                                                                                                                                                                                                                                                                                                                                                                                | Package | Form                                                                                                                                                                                                                                            | Marking |
| TTD95N68A                                                                                                                                                                                                                                                                                                                                                                                                             | TO-252  | Tape&Reel                                                                                                                                                                                                                                       | 95N68A  |
| TTU95N68A                                                                                                                                                                                                                                                                                                                                                                                                             | TO-251  | Tape&Reel                                                                                                                                                                                                                                       | 95N68A  |

| Absolute Maximum Ratings ( $T_A = 25^{\circ}C$ unless otherwise noted) |                      |                |            |             |
|------------------------------------------------------------------------|----------------------|----------------|------------|-------------|
| Parameter                                                              |                      | Symbol         | Maximum    | Units       |
| Drain-Source Voltage                                                   |                      | $V_{DS}$       | 68         | V           |
| Gate-Source Voltage                                                    |                      | $V_{GS}$       | $\pm 20$   | V           |
| Continuous Drain Current                                               | $T_C = 25^{\circ}C$  | $I_D$          | 46         | A           |
|                                                                        | $T_C = 100^{\circ}C$ |                | 46         |             |
| Pulsed Drain Current <sup>A</sup>                                      |                      | $I_{DM}$       | 285        | A           |
| Avalanche Current <sup>A</sup>                                         |                      | $I_{AS}$       | 37         | A           |
| Single Pulse Avalanche Energy $L = 0.3mH$ <sup>A</sup>                 |                      | $E_{AS}$       | 380        | mJ          |
| Power Dissipation <sup>C</sup>                                         | $T_C = 25^{\circ}C$  | $P_D$          | 130.5      | W           |
|                                                                        | $T_C = 100^{\circ}C$ |                | 65.5       |             |
| Operating Junction and Storage Temperature Range                       |                      | $T_J, T_{STG}$ | -55 to 175 | $^{\circ}C$ |

| Thermal Characteristics     |              |            |         |               |
|-----------------------------|--------------|------------|---------|---------------|
| Parameter                   |              | Symbol     | Maximum | Units         |
| Maximum Junction-to-Case    | Steady-State | $R_{thJC}$ | 1.15    | $^{\circ}C/W$ |
| Maximum Junction-to-Ambient | Steady-State | $R_{thJA}$ | 100     |               |

**Electrical Characteristics( $T_J = 25^\circ\text{C}$  unless otherwise noted)**

| Symbol               | Parameter                                          | Conditions                                                                         |                       | Value |      |      | Units |
|----------------------|----------------------------------------------------|------------------------------------------------------------------------------------|-----------------------|-------|------|------|-------|
|                      |                                                    |                                                                                    |                       | Min   | Typ  | Max  |       |
| STATIC PARAMETERS    |                                                    |                                                                                    |                       |       |      |      |       |
| BV <sub>DSS</sub>    | Drain-Source Breakdown Voltage                     | I <sub>D</sub> =250μA,V <sub>GS</sub> =0V                                          |                       | 68    | --   | --   | V     |
| I <sub>DSS</sub>     | Zero Gate Voltage Drain Current                    | V <sub>DS</sub> =68V, V <sub>GS</sub> =0V                                          | T <sub>J</sub> =25°C  | --    | --   | 1    | μA    |
|                      |                                                    |                                                                                    | T <sub>J</sub> =100°C | --    | --   | 25   |       |
| I <sub>GSS</sub>     | Gate-Body Leakage Current                          | V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V                                         |                       | --    | --   | ±100 | nA    |
| V <sub>GS(th)</sub>  | Gate Threshold Voltage                             | V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA                           |                       | 2     | 3    | 4    | V     |
| R <sub>DS(ON)</sub>  | Static Drain-Source On-Resistance                  | V <sub>GS</sub> =10V, I <sub>D</sub> =30A                                          |                       | --    | 6.5  | 7.5  | mΩ    |
| g <sub>FS</sub>      | Forward Transconductance                           | V <sub>DS</sub> = 5V, I <sub>D</sub> =20A                                          |                       | --    | 30   | --   | S     |
| V <sub>SD</sub>      | Diode Forward Voltage                              | I <sub>S</sub> =20A, V <sub>GS</sub> =0V                                           |                       | --    | --   | 1    | V     |
| I <sub>S</sub>       | Maximum Body-Diode Continuous Current <sup>B</sup> |                                                                                    |                       | --    | --   | 46   | A     |
| DYNAMIC PARAMETERS   |                                                    |                                                                                    |                       |       |      |      |       |
| C <sub>iss</sub>     | Input Capacitance                                  | V <sub>GS</sub> =0V, V <sub>DS</sub> =30V, f =1MHz <sub>Z</sub>                    |                       | --    | 4169 | --   | pF    |
| C <sub>oss</sub>     | Output Capacitance                                 |                                                                                    |                       | --    | 274  | --   |       |
| C <sub>rss</sub>     | Reverse Transfer Capacitance                       |                                                                                    |                       | --    | 222  | --   |       |
| SWITCHING PARAMETERS |                                                    |                                                                                    |                       |       |      |      |       |
| Q <sub>g</sub> (10V) | Total Gate Charge                                  | V <sub>GS</sub> =10V,V <sub>DS</sub> =30V, I <sub>D</sub> =30A                     |                       | --    | 70   | --   | nC    |
| Q <sub>gs</sub>      | Gate Source Charge                                 |                                                                                    |                       | --    | 20   | --   |       |
| Q <sub>gd</sub>      | Gate Drain Charge                                  |                                                                                    |                       | --    | 18   | --   |       |
| t <sub>D(on)</sub>   | Turn-On Delay Time                                 | V <sub>GS</sub> =10V,V <sub>DS</sub> =30V, I <sub>D</sub> =30A, R <sub>G</sub> =3Ω |                       | --    | 15   | --   | ns    |
| t <sub>r</sub>       | Turn-On Rise Time                                  |                                                                                    |                       | --    | 94   | --   |       |
| T <sub>D(off)</sub>  | Turn-Off Delay Time                                |                                                                                    |                       | --    | 46   | --   |       |
| t <sub>f</sub>       | Turn-Off Fall Time                                 |                                                                                    |                       | --    | 32   | --   |       |
| t <sub>rr</sub>      | Body Diode Reverse Recovery Time                   | I <sub>F</sub> =20A, di/dt =100A/μs                                                |                       | --    | 78   | --   | ns    |
| Q <sub>rr</sub>      | Body Diode Reverse Recovery Charge                 |                                                                                    |                       | --    | 51   | --   | nC    |

A. Single pulse width limited by maximum junction temperature.

B. The maximum current rating is package limited.

C. The power dissipation  $P_D$  is based on  $T_{J(MAX)} = 175^\circ\text{C}$ , using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.



Typical Characteristics  $T_J = 25^\circ\text{C}$ , unless otherwise noted




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current




Figure 4: Capacitance Characteristics




Figure 5: Gate Charge Characteristics




Figure 6: Body Diode Forward Voltage



Typical Characteristics  $T_j = 25^\circ\text{C}$ , unless otherwise noted




Figure 7: On-Resistance vs. Junction Temperature




Figure 8:  $V_{GS(th)}$  vs. Junction Temperature




Figure 9: Normalized Transient Thermal Resistance




Figure 10: Safe Operating Area



Figure A: Gate Charge Test Circuit and Waveform




Figure B: Resistive Switching Test Circuit and Waveform





Figure C: Unclamped Inductive Switching Test Circuit and Waveform






**TO-251(T)**






## TO-252(E)



| Symbol | Dimensions In Millimeters |      | Dimensions In Inches |       |
|--------|---------------------------|------|----------------------|-------|
|        | Min.                      | Max. | Min.                 | Max.  |
| A      | 2.10                      | 2.50 | 0.083                | 0.098 |
| A1     | 0                         | 0.15 | 0.000                | 0.006 |
| A2     | 0.76                      | 1.36 | 0.030                | 0.054 |
| b      | 0.61                      | 0.85 | 0.024                | 0.033 |
| b1     | 0.71                      | 0.91 | 0.028                | 0.036 |
| b2     | 5.04                      | 5.64 | 0.198                | 0.222 |
| c      | 0.508 TYP.                |      | 0.02 TYP.            |       |
| c1     | 0.508 TYP.                |      | 0.02 TYP.            |       |
| D      | 5.8                       | 6.3  | 0.228                | 0.248 |
| D1     | 5                         | 5.6  | 0.197                | 0.220 |
| E      | 6.3                       | 6.9  | 0.248                | 0.272 |
| E1     | 4.55                      | 5.15 | 0.179                | 0.203 |
| e      | 2.286 TYP.                |      | 0.09 TYP.            |       |
| H      | 9.65                      | 10.4 | 0.380                | 0.409 |
| L      | 1.4                       | 1.7  | 0.055                | 0.067 |
| L1     | 2.90 REF.                 |      | 0.114 REF.           |       |
| L2     | 0.75                      | 1.35 | 0.030                | 0.053 |
| L3     | 0.6                       | 1.2  | 0.024                | 0.047 |
| θ      | 0°                        | 10°  | 0°                   | 10°   |
| θ1     | 5°                        | 9°   | 5°                   | 9°    |
| θ2     | 25° REF.                  |      | 25° REF.             |       |

关键尺寸

|   |    |   |   |   |    |   |   |   |    |
|---|----|---|---|---|----|---|---|---|----|
| A | A1 | b | D | E | E1 | e | H | D | L1 |
|---|----|---|---|---|----|---|---|---|----|


**TO-252(H)**

| Unit: mm |         |      |
|----------|---------|------|
| Symbol   | Min.    | Max. |
| A        | 2.20    | 2.40 |
| A1       | 0.00    | 0.20 |
| A2       | 0.97    | 1.17 |
| b        | 0.68    | 0.90 |
| b3       | 5.20    | 5.50 |
| c        | 0.43    | 0.63 |
| D        | 5.98    | 6.22 |
| D1       | 5.30REF |      |
| E        | 6.40    | 6.80 |
| E1       | 4.63    | -    |

| Unit: mm |          |       |
|----------|----------|-------|
| Symbol   | Min.     | Max.  |
| e        | 2.286BSC |       |
| H        | 9.40     | 10.50 |
| L        | 1.38     | 1.75  |
| L1       | 2.90REF  |       |
| L2       | 0.51BSC  |       |
| L3       | 0.88     | 1.28  |
| L4       | -        | 1.00  |
| L5       | 1.65     | 1.95  |
| $\theta$ | 0°       | 8°    |






## TO-252(T)




| SYMBOL | MIN      | NOM   | MAX   |
|--------|----------|-------|-------|
| A      | 6.50     | 6.60  | 6.70  |
| A1     | 5.16     | 5.31  | 5.46  |
| A2     | 4.83 REF |       |       |
| A3     | 5.30 REF |       |       |
| B      | 9.77     | 9.97  | 10.17 |
| B1     | 6.00     | 6.10  | 6.20  |
| B2     | 2.60     | 2.80  | 3.00  |
| B3     | 0.70     | 0.80  | 0.90  |
| C      | 0.41     | —     | 0.61  |
| c      | 0.40     | 0.50  | 0.60  |
| D      | 2.20     | 2.30  | 2.40  |
| E      | 2.186    | 2.286 | 2.386 |
| F1     | 0.67     | —     | 0.87  |
| f1     | 0.66     | 0.76  | 0.86  |
| F2     | 0.76     | 0.86  | 0.96  |
| H      | 0.00     | —     | 0.30  |
| h      | 0.00     | —     | 0.20  |
| L      | 6.50     | 6.60  | 6.70  |
| øP     | 1.10     | 1.20  | 1.30  |
| Q1°    | 0°       | —     | 8°    |
| Q2°    | 6°       | 7°    | 8°    |



## TO-252(Q)



DETAIL I



| SYMBOL | MIN   | NOM   | MAX   |
|--------|-------|-------|-------|
| A      | 2.29  | 2.30  | 2.31  |
| A1     | 0.00  | 0.07  | 0.15  |
| A2     | 1.020 | 1.025 | 1.030 |
| b      | 0.645 | 0.670 | 0.695 |
| b1     | 0.67  | 0.77  | 0.87  |
| c      | 0.523 | 0.528 | 0.533 |
| c1     | 0.498 | 0.508 | 0.518 |
| D      | 6.09  | 6.10  | 6.11  |
| D1     | 5.244 | 5.249 | 5.254 |
| E      | 6.50  | 6.60  | 6.70  |
| E1     | 5.284 | 5.334 | 5.384 |
| E2     | 4.284 | 4.334 | 4.312 |
| e      | 4.821 | 4.826 | 4.831 |
| e1     | 2.281 | 2.286 | 2.291 |
| e2     | 4.059 | 4.064 | 4.069 |
| H      | 9.8   | 10.0  | 10.2  |
| H1     | 1.5   | 1.6   | 1.7   |
| h      | 1.316 | 1.321 | 1.326 |
| h1     | 0.757 | 0.762 | 0.767 |
| L      | 1.4   | 1.5   | 1.6   |
| L1     | 0.50  | 0.51  | 0.52  |
| L2     | 0.8   | 0.9   | 1.0   |
| L3     | 2.88  | 2.888 | 2.893 |



## Disclaimer

All product specifications and data are subject to change without notice.

For documents and material available from this datasheet, Wuxi Unigroup does not warrant or assume any legal liability or responsibility for the accuracy, completeness of any product or technology disclosed hereunder.

No license, express or implied, by estoppels or otherwise, to any intellectual property rights is granted by this document or by any conduct of Wuxi Unigroup.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling Wuxi Unigroup products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Wuxi Unigroup for any damages arising or resulting from such use or sale.

Wuxi Unigroup disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Wuxi Unigroup's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

Wuxi Unigroup Microelectronics CO., LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

In the event that any or all Wuxi Unigroup products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

Information (including circuit diagrams and circuit parameters) herein is for example only. It is not guaranteed for volume production. Wuxi Unigroup believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.