

STARPOWER

SEMICONDUCTOR

IGBT

GD400HFQ120C2SD

1200V/400A 2 in one-package

General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as electronic welder and inductive heating.


Features

- Low $V_{CE(sat)}$ Trench IGBT technology
- 10 μ s short circuit capability
- $V_{CE(sat)}$ with positive temperature coefficient
- Maximum junction temperature 175°C
- Low inductance case
- Fast & soft reverse recovery anti-parallel FWD
- Isolated copper baseplate using DBC technology

Typical Applications

- Switching mode power supply
- Inductive heating
- Electronic welder

Equivalent Circuit Schematic



Absolute Maximum Ratings $T_C=25^{\circ}\text{C}$ unless otherwise noted**IGBT**

Symbol	Description	Values	Unit
V_{CES}	Collector-Emitter Voltage	1200	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current @ $T_C=25^{\circ}\text{C}$	769	A
	@ $T_C=100^{\circ}\text{C}$	400	
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	800	A
P_D	Maximum Power Dissipation @ $T_{vj}=175^{\circ}\text{C}$	2272	W

Diode

Symbol	Description	Values	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current	400	A
I_{FM}	Diode Maximum Forward Current $t_p=1\text{ms}$	800	A

Module

Symbol	Description	Value	Unit
T_{vjmax}	Maximum Junction Temperature	175	$^{\circ}\text{C}$
T_{vjop}	Operating Junction Temperature	-40 to +150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-40 to +125	$^{\circ}\text{C}$
V_{ISO}	Isolation Voltage RMS, $f=50\text{Hz}, t=1\text{min}$	2500	V

IGBT Characteristics $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=400\text{A}, V_{GE}=15\text{V}, T_{vj}=25^\circ\text{C}$		1.85	2.30	V
		$I_C=400\text{A}, V_{GE}=15\text{V}, T_{vj}=125^\circ\text{C}$		2.25		
		$I_C=400\text{A}, V_{GE}=15\text{V}, T_{vj}=150^\circ\text{C}$		2.35		
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=16.00\text{mA}, V_{CE}=V_{GE}, T_{vj}=25^\circ\text{C}$	5.6	6.2	6.8	V
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_{vj}=25^\circ\text{C}$			1.0	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_{vj}=25^\circ\text{C}$			400	nA
R_{Gint}	Internal Gate Resistance			0.5		Ω
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}, f=100\text{KHz}, V_{GE}=0\text{V}$		43.2		nF
C_{res}	Reverse Transfer Capacitance				1.18	
Q_G	Gate Charge	$V_{GE}=-15\dots+15\text{V}$		3.36		μC
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=400\text{A}, R_G=2\Omega, L_S=45\text{nH}, V_{GE}=\pm 15\text{V}, T_{vj}=25^\circ\text{C}$		288		ns
t_r	Rise Time			72		ns
$t_{d(off)}$	Turn-Off Delay Time			314		ns
t_f	Fall Time			55		ns
E_{on}	Turn-On Switching Loss			43.6		mJ
E_{off}	Turn-Off Switching Loss			12.4		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=400\text{A}, R_G=2\Omega, L_S=45\text{nH}, V_{GE}=\pm 15\text{V}, T_{vj}=125^\circ\text{C}$		291		ns
t_r	Rise Time			76		ns
$t_{d(off)}$	Turn-Off Delay Time			351		ns
t_f	Fall Time			88		ns
E_{on}	Turn-On Switching Loss			57.6		mJ
E_{off}	Turn-Off Switching Loss			17.1		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=400\text{A}, R_G=2\Omega, L_S=45\text{nH}, V_{GE}=\pm 15\text{V}, T_{vj}=150^\circ\text{C}$		293		ns
t_r	Rise Time			78		ns
$t_{d(off)}$	Turn-Off Delay Time			365		ns
t_f	Fall Time			92		ns
E_{on}	Turn-On Switching Loss			62.8		mJ
E_{off}	Turn-Off Switching Loss			18.6		mJ
I_{SC}	SC Data	$t_p \leq 10\mu\text{s}, V_{GE}=15\text{V}, T_{vj}=150^\circ\text{C}, V_{CC}=800\text{V}, V_{CEM} \leq 1200\text{V}$		1500		A

Diode Characteristics $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_F	Diode Forward Voltage	$I_F=400\text{A}, V_{GE}=0\text{V}, T_{vj}=25^\circ\text{C}$		1.85	2.30	V
		$I_F=400\text{A}, V_{GE}=0\text{V}, T_{vj}=125^\circ\text{C}$		1.90		
		$I_F=400\text{A}, V_{GE}=0\text{V}, T_{vj}=150^\circ\text{C}$		1.95		
Q_r	Recovered Charge	$V_R=600\text{V}, I_F=400\text{A},$ $-di/dt=4130\text{A}/\mu\text{s}, V_{GE}=-15\text{V},$ $L_S=45\text{nH}, T_{vj}=25^\circ\text{C}$		38.8		μC
I_{RM}	Peak Reverse Recovery Current			252		A
E_{rec}	Reverse Recovery Energy			11.2		mJ
Q_r	Recovered Charge	$V_R=600\text{V}, I_F=400\text{A},$ $-di/dt=3860\text{A}/\mu\text{s}, V_{GE}=-15\text{V},$ $L_S=45\text{nH}, T_{vj}=125^\circ\text{C}$		61.9		μC
I_{RM}	Peak Reverse Recovery Current			255		A
E_{rec}	Reverse Recovery Energy			18.7		mJ
Q_r	Recovered Charge	$V_R=600\text{V}, I_F=400\text{A},$ $-di/dt=3720\text{A}/\mu\text{s}, V_{GE}=-15\text{V},$ $L_S=45\text{nH}, T_{vj}=150^\circ\text{C}$		75.9		μC
I_{RM}	Peak Reverse Recovery Current			257		A
E_{rec}	Reverse Recovery Energy			20.5		mJ

Module Characteristics $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
L_{CE}	Stray Inductance			20	nH
$R_{CC'+EE'}$	Module Lead Resistance, Terminal to Chip		0.35		m Ω
R_{thJC}	Junction-to-Case (per IGBT)			0.066	K/W
	Junction-to-Case (per Diode)			0.115	
R_{thCH}	Case-to-Heatsink (per IGBT)		0.031		K/W
	Case-to-Heatsink (per Diode)		0.055		
	Case-to-Heatsink (per Module)		0.010		
M	Terminal Connection Torque, Screw M6	2.5		5.0	N.m
	Mounting Torque, Screw M6	3.0		5.0	
G	Weight of Module		300		g




Fig 1. IGBT Output Characteristics




Fig 2. IGBT Transfer Characteristics




Fig 3. IGBT Switching Loss vs. I_C




Fig 4. IGBT Switching Loss vs. R_G




Fig 5. RBSOA




Fig 6. IGBT Transient Thermal Impedance




Fig 7. Diode Forward Characteristics




Fig 8. Diode Switching Loss vs. I_F




Fig 9. Diode Switching Loss vs. R_G






Fig 10. Diode Transient Thermal Impedance

Circuit Schematic



Package Dimensions

Dimensions in Millimeters



Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.cc), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.