


Features

- Low saturation
- Complement to FMMT589

HF

Mechanical Data

- Case: SOT-23
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
FMMT489	SOT-23	3000 pcs / Tape & Reel	489

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V _{CB0}	50	V
Collector-Emitter Breakdown Voltage	V _{CEO}	30	V
Emitter-Base Breakdown Voltage	V _{EBO}	7	V
Collector Current (Continuous)	I _C	1	A
Peak Pulse Current	I _{CM}	2	A
Base Current	I _B	0.2	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation (T _A = 25°C) ^{*1}	P _D	0.5	W
Thermal Resistance Junction-to-Air ^{*1}	R _{θJA}	250	°C/W
Thermal Resistance Junction-to-Lead ^{*2}	R _{θJL}	197	°C/W
Junction Temperature	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Notes:

1. For a device mounted with the collector lead on 15mm x 15mm 1oz copper that is on a single-sided 1.6mm FR4 PCB; device is measured under still air conditions whilst operating in a steady-state
2. Thermal resistance from junction to solder-point (at the end of the collector lead)

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 100\mu\text{A}, I_E = 0$	50	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 10\text{mA}, I_B = 0$	30	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 100\mu\text{A}, I_C = 0$	7	-	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB} = 30\text{V}, I_E = 0$	-	-	0.1	μA
Emitter Cut-off Current	I_{EBO}	$V_{EB} = 6\text{V}, I_C = 0$	-	-	0.1	μA
Collector-Emitter Cutoff Current	I_{CES}	$V_{CES} = 30\text{V}$	-	-	0.1	μA
DC Current Gain	h_{FE}	$V_{CE} = 2\text{V}, I_C = 1\text{mA}$	100	-	-	-
		$V_{CE} = 2\text{V}, I_C = 1\text{A}$	100	-	300	-
		$V_{CE} = 2\text{V}, I_C = 2\text{A}$	60	-	-	-
		$V_{CE} = 2\text{V}, I_C = 4\text{A}$	20	-	-	-
Collector-emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 1\text{A}, I_B = 0.1\text{A}$	-	-	0.3	V
		$I_C = 2\text{A}, I_B = 0.2\text{A}$	-	-	0.6	V
Base-emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 1\text{A}, I_B = 0.1\text{A}$	-	-	1.1	V
Base-emitter On Voltage	$V_{BE(on)}$	$I_C = 1\text{A}, V_{CE} = 2\text{V}$	-	-	1.0	V
Output Capacity	C_{ob}	$V_{CB} = 10\text{V}, f = 1\text{MHz}$	-	-	10	pF
Current-Gain—Bandwidth Product	f_T	$I_C = 0.05\text{A}, V_{CE} = 10\text{V}$ $f = 100\text{MHz}$	150	-	-	MHz

Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C






Fig 4 $V_{BE(on)}$ vs. I_C

Package Outline Dimensions (Unit: mm)



Package Outline Dimensions (Unit: mm)



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.