


Features


- Low-power rectification
- For switching power supply
- Ultra low V_F
- $I_F=0.7A$ guaranteed despite the size



Marking and pin assignment



SOT-323 top view



Schematic diagram



Halogen-Free

Maximum Ratings($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Limit	Unit
V_{RM}	Non-Repetitive Peak Reverse Voltage	25	V
V_R	DC Blocking voltage	20	V
I_o	Average Rectified Output Current	700	mA
P_D	Power Dissipation	150	mW
T_J	Operating Junction Temperature Range	-40 ~ +125	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-55~ +150	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS($T_a=25^{\circ}\text{C}$ unless otherwise specified)


Symbol	Parameter	Condition	Min	Typ	Max	Unit
$V_{(BR)}$	Reverse breakdown voltage	$I_R=200\mu\text{A}$	20	--	--	V
I_R	Reverse voltage leakage current	$V_R=20\text{V}$	--	--	200	μA
V_F	Forward voltage	$I_F=700\text{mA}$	--	--	0.49	V

Ordering Information (Example)


Type	Package	Marking	Minimum Package(pcs)	Inner Box Quantity(pcs)	Outer Carton Quantity(pcs)	Delivery Mode
RB461F	SOT-323	3B	3,000	45,000	180,000	7"reel

Typical Operating Characteristics


Forward Characteristics




Reverse Characteristics




Capacitance Characteristics



Power Derating Curve



SOT-323 Package information



Symbol	Dimensions in Millimeters(mm)		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650TYP		0.026TYP	
e1	1.200	1.400	0.047	0.055
L	0.525REF		0.021REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°