



CRG50T120CX3SDQ

General Description:

Using owner proprietary trench design and advanced Field Stop (FS) technology, offering superior conduction and switching performances. RoHS Compliant.

Features:

- Qualified to AEC-Q101
- Short Circuit Withstand Time 10 μ s
- FS Trench Technology, Positive temperature coefficient
- Low saturation voltage:


$V_{CE(sat)}$ TYP=1.72V @ I_C =50A, V_{GE} =15V;

Applications


- Electric Automotive Air-Condition Compressor
- PTC heater
- General Inverter

V_{CES}	1200	V
I_C	50	A
P_{tot} ($T_C=25^{\circ}C$)	565	W
$V_{CE(sat)}$	1.72	V

Outline : TO-247Plus



Inner Circuit:



Package Parameters

Type	Marking	Package	Packing
CRG50T120CX3SDQ	G50T120CX3SDQ	TO-247Plus	Tube

Absolute Maximum Ratings ($T_C = 25^\circ\text{C}$ unless otherwise specified):

Symbol	Parameter	Rating	Unit
V_{CES}	Collector-Emitter Voltage	1200	V
V_{GES}	Gate- Emitter Voltage	± 20	V
V_{GES}	Gate- Emitter Voltage ($t_p \leq 10\mu\text{s}, D < 0.01$)	± 30	V
I_C	Collector Current @ $T_C = 25^\circ\text{C}$	100	A
	Collector Current @ $T_C = 100^\circ\text{C}$	50	
I_{CM}^{a1}	Pulsed Collector Current	200	A
I_F	Diode Continuous Forward Current @ $T_C = 25^\circ\text{C}$	100	A
	Diode Continuous Forward Current @ $T_C = 100^\circ\text{C}$	50	
I_{FM}	Diode Maximum Forward Current	200	A
T_{SC}	Short Circuit Withstand Time @ $V_{GE}=15\text{V}, V_{CE}=600\text{V}$	10	μs
P_D	Power Dissipation @ $T_C = 25^\circ\text{C}$	565	W
	Power Dissipation @ $T_C = 100^\circ\text{C}$	282.5	
T_{vjop}^{a2}	Operating Junction temperature range	$-40 \sim 175$	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	$-55 \sim 150$	$^\circ\text{C}$
T_L	Maximum Temperature for Soldering	270	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R\theta_{JC}$	Thermal Resistance, Junction to case for IGBT	--	0.26	$^\circ\text{C}/\text{W}$
$R\theta_{JC}$	Thermal Resistance, Junction to case for Diode	--	0.52	$^\circ\text{C}/\text{W}$
$R\theta_{JA}$	Thermal Resistance, Junction to Ambient	--	40	$^\circ\text{C}/\text{W}$

Electrical Characteristics of the IGBT ($T_C = 25^\circ\text{C}$ unless otherwise specified):

Symbol	Parameter	Conditions	Value			Unit
			Min.	Typ	Max.	
OFF Characteristics						
V _{(BR)CES}	Collector-Emitter Breakdown Voltage	V _{GE} =0V,I _{CE} =250uA	1200	--	--	V
I _{CES}	Collector Cut-off Current	V _{GE} =0V,V _{CE} =1200V	--	--	100	uA
I _{GES(F)}	Gate-Emitter Forward Leakage Current	V _{GE} =+20V	--	--	+250	nA
I _{GES(R)}	Gate-Emitter Reverse Leakage Current	V _{GE} =-20V	--	--	-250	nA
ON Characteristics						
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C =50A ,V _{GE} =15V @ T _C = 25 °C	--	1.72	2.4	V
		I _C =50A ,V _{GE} =15V @ T _C =175 °C	--	2.50	--	V

V _{GE(th)}	Gate - Emitter Threshold Voltage	I _C =250uA ,V _{CE} =V _{GE}	4.5	5.65	7.0	V
Pulse width tp≤300μs,δ≤2%						
Dynamic Characteristics						
C _{ies}	Input Capacitance	V _{CE} =30V,V _{GE} =0V f=1MHz	--	3311	--	pF
C _{oes}	Output Capacitance		--	207	--	
C _{res}	Reverse Transfer Capacitance		--	82	--	
Switching Characteristics						
t _{d(on)}	Turn-on Delay Time	V _{CE} =600V,I _C =50A, R _g =10Ω,V _{GE} =15V, Inductive Load, T _j =25℃,	--	41	--	ns
t _r	Rise Time		--	42.7	--	
t _{d(off)}	Turn-Off Delay Time		--	253	--	
t _f	Fall Time		--	83.6	--	
E _{on}	Turn-On Switching Loss		--	4.68	--	mJ
E _{off}	Turn-Off Switching Loss	--	2.46	--		
E _{ts}	Total Switching Loss	--	7.14	--		
t _{d(on)}	Turn-on Delay Time	V _{CE} =600V,I _C =50A, R _g =10Ω,V _{GE} =15V, Inductive Load, T _j =175℃	--	40.5	--	ns
t _r	Rise Time		--	44	--	
t _{d(off)}	Turn-Off Delay Time		--	275	--	
t _f	Fall Time		--	140	--	
E _{on}	Turn-On Switching Loss		--	5.98	--	mJ
E _{off}	Turn-Off Switching Loss	--	3.08	--		
E _{ts}	Total Switching Loss	--	9.06	--		
Q _g	Total Gate Charge	V _{CE} =600V,I _C =50A, V _{GE} =15V,	--	168	--	nC
Q _{ge}	Gate to Emitter Charge		--	30	--	
Q _{gc}	Gate to Collector Charge		--	91	--	
Electrical Characteristics of the DIODE						
V _F	Diode Forward Voltage	I _F =50A TC=25℃	--	2.0	3.2	V
		I _F =50A TC=175℃	--	1.76	--	V
t _{rr}	Reverse Recovery Time	I _F =50A di/dt=100A/μS	--	86	--	ns
I _{rrm}	Reverse Recovery Current		--	4.8	--	A
Q _{rr}	Reverse Recovery Charge		--	208	--	nC

Notes:

a1: Repetitive rating; pulse width limited by maximum junction temperature

a2: Overload condition, it is allowed to operate under the maximum junction temperature $T_{vjop} = 175^\circ C$, the maximum duty cycle is less than 20% (lasting for 60s at most)

Typical Performance Characteristics




Figure 1. Output Characteristics




Figure 2. Output Characteristics




Figure 3. Saturation Voltage Characteristics




Figure 4. Saturation Voltage -T_C Characteristics




Figure 5. Capacitance Characteristics




Figure 6. Switching Loss-R_G Characteristics




Figure 7. Switching Time- R_G Characteristics




Figure 8. Switching Time- R_G Characteristics




Figure 9. Switching Loss- T_c Characteristics




Figure 10. Switching Time- T_c Characteristics




Figure 11. Switching Time- T_c Characteristics




Figure 12. Switching Loss- I_C Characteristics




Figure 13. Switching Time- I_C Characteristics




Figure 14. Switching Time- I_C Characteristics




Figure 15. Diode Forward Characteristics




Figure 16. Collector Current- T_C Characteristics
($T_J \leq 175^\circ C$)




Figure 17. Power Dissipation- T_C Characteristics
($T_J \leq 175^\circ C$)




Figure 18. Gate Charge Characteristics




Figure 19. Threshold Voltage -Tc Characteristics




Figure 20. Breakdown Voltage-Tc Characteristics




Figure 21. Forward Bias Safe Operating Area





Figure 22. IGBT Transient Thermal Impedance

Package Information



项 目	规范(mm)	
	MIN	MAX
A	4.85	5.15
A1	1.85	2.15
A2	2.15	2.65
b	1.07	1.33
b1	1.90	2.46
b2	1.90	2.16
b3	2.82	3.43
C	0.55	0.70
D	20.75	21.15
D1	16.20	16.90
E	15.50	16.10
E1	13.01	13.51
E3	1.25	1.65
e	5.44 (BSC)	
R	1.80	2.20
L	19.60	20.40
L1	4.00	4.48

TO-247Plus Package

**The name and content of poisonous and harmful material in products**

Part's Name Limit	Hazardous Substance									
	Pb	Hg	Cd	Cr(VI)	PBB	PBDE	DIBP	DEHP	DBP	BBP
	≤0.1%	≤0.1%	≤0.01%	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%
Lead Frame	○	○	○	○	○	○	○	○	○	○
Molding	○	○	○	○	○	○	○	○	○	○
Chip	○	○	○	○	○	○	○	○	○	○
Wire Bonding	○	○	○	○	○	○	○	○	○	○
Solder	×	○	○	○	○	○	○	○	○	○
Note	○: Means the hazardous material is under the criterion of 2011/65/EU. ×: Means the hazardous material exceeds the criterion of 2011/65/EU. The plumbum element of solder exist in products presently, but within the allowed range of Eurogroup's RoHS.									

Disclaimer:

1. CRM reserves the right to change any product or information in this Specification at any time without prior notice.
2. The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.
3. The product is not intended for use in applications that require extraordinary levels of quality and reliability, such as aviation/aerospace and life-support devices or systems.
4. Any and all semiconductor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.

WUXI CHINA RESOURCES HUAJING MICROELECTRONICS CO., LTD.

Add: No.14 Liangxi RD. Wuxi, Jiangsu, China **Mail:** 214061 <https://www.crmicro.com>
Tel: 0510-85807228 **Fax:** 0510-85800864

Marketing Part: **Post:** 214061 **Tel / Fax:** 0510-85807228-3663/5508
0510-85800360 (Fax)

Application and Service: **Post:** 214061 **Tel / Fax:** 0510-85807228-3399 / 2227