







Features

- Fast switching speed
- High conductance

HF

Mechanical Data

- Case: SOT-23
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
MMBD1201	SOT-23	3000 pcs / Tape & Reel	A01
MMBD1202	SOT-23	3000 pcs / Tape & Reel	A02
MMBD1203	SOT-23	3000 pcs / Tape & Reel	A03
MMBD1204	SOT-23	3000 pcs / Tape & Reel	A04
MMBD1205	SOT-23	3000 pcs / Tape & Reel	A05

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Repetitive Peak Reverse Voltage	V _{RRM}	100	V
Working Peak Reverse Voltage	V _{RWM}	100	V
DC Blocking Voltage	V _R	100	V
Forward Continuous Current	I _F	600	mA
Repetitive Peak Forward Current	I _{FRM}	700	mA
Forward Surge Current, t _p = 1s	I _{FSM}	1	A
Forward Surge Current, t _p = 1ms	I _{FSM}	2	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation ^{*1}	P_D	350	mW
Thermal Resistance Junction-to-Air ^{*1}	$R_{\theta JA}$	357	°C/W
Operating Junction Temperature Range	T_J	-55 ~ +150	°C
Storage Temperature Range	T_{STG}	-55 ~ +150	°C

Note 1: The data tested by surface mounted on glass epoxy PCB 1.6" X 1.6" X 0.06"; mounting pad for the collector lead min. 0.93 in²

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Reverse Breakdown Voltage	$V_{(BR)R}$	$I_R = 100\mu\text{A}$	100	-	-	V
Forward Voltage	V_F	$I_F = 1\text{mA}$	0.55	-	0.62	V
		$I_F = 10\text{mA}$	0.66	-	0.74	V
		$I_F = 100\text{mA}$	0.82	-	0.92	V
		$I_F = 200\text{mA}$	0.87	-	1.00	V
		$I_F = 300\text{mA}$	-	-	1.1	V
Maximum Peak Reverse Current	I_R	$V_R = 20\text{V}$	-	-	25	nA
		$V_R = 50\text{V}$	-	-	50	nA
		$V_R = 50\text{V}, T_J = 150^\circ\text{C}$	-	-	50	μA
Total Capacitance	C_J	$V_R = 0\text{V}, f = 1.0\text{MHz}$	-	-	2	pF
Reverse Recovery Time	t_{rr}	$I_F = I_R = 10\text{mA}$ $I_{rr} = 0.1 \times I_R, R_L = 100\Omega$	-	-	4	ns

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Typical Reverse Characteristic




Fig 2 Typical Forward Characteristics




Fig 3 Capacitance vs. Reverse Voltage






Fig 4 Power Derating Curve

Package Outline Dimensions (Unit: mm)



Package Outline Dimensions (Unit: mm)



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.