

# AZSR165

## 65 AMP POWER RELAY

### FEATURES

- Up to 80 Amp switching capability
- Wide contact gap of  $\geq 3.0$  mm
- Clearance and creepage of  $\geq 10$  mm
- 5 kV dielectric strength, 10 kV surge withstand voltage
- UL Class F insulation (155°C)
- UL / CUR E365652
- TÜV B0887930008
- CQC 17002178200



### CONTACTS

<b>Arrangement</b>	SPST-N.O. (1 Form A)
<b>Ratings (max.)</b> switched power switched current carrying current switched voltage	(resistive load) 43200 VA 80 A 65 A 690 VAC
<b>Rated Loads</b> UL/CUR/TÜV/CQC	80 A at 540 VAC, resistive, 85°C, 1k cycles <sup>[1][2]</sup> 10 A make - 65 A carry - 10 A break at 690 VAC, resistive, 85°C, 100k cycles <sup>[1]</sup> 20 A make - 65 A carry - 20 A break at 690 VAC, resistive, 85°C, 30k cycles <sup>[1]</sup> 20 A make - 65 A carry - 20 A break at 690 VAC, resistive, 85°C, 100k cycles <sup>[2]</sup>
<b>Contact materials</b>	AgNi - silver nickel <sup>[1]</sup> AgSnO <sub>2</sub> - silver tin oxide <sup>[2]</sup>
<b>Contact gap</b>	$\geq 3.0$ mm
<b>Contact resistance</b> initial typical	$\leq 10$ m $\Omega$ (10 A - voltage drop method) < 1 m $\Omega$ (65 A - voltage drop method) <sup>[1]</sup>

### COIL

<b>Nominal coil DC voltages</b>	6, 9, 12, 24
<b>Dropout voltage</b>	$\geq 5\%$ of nominal coil voltage
<b>Holding voltage</b>	$\geq 40\%$ of nominal coil voltage
<b>Coil power</b> nominal at pickup voltage holding power	2.2 W 1.25 W 360 mW
<b>Temperature Rise</b>	70 K (126°F) at nominal coil voltage
<b>Max. temperature</b>	Class F insulation - 155°C (311°F)

### GENERAL DATA

<b>Life Expectancy</b> mechanical electrical	(minimum operations) $1 \times 10^6$ see UL/CUR/TÜV/CQC ratings
<b>Operate Time</b> max. typical	(at nominal coil voltage) 40 ms < 25 ms
<b>Release Time</b> max. typical	(at nominal coil voltage) 10 ms (without coil suppression) < 5 ms (suppression with Z-diode at $2 \times U_{nom.}$ )
<b>Dielectric Strength</b>	(at sea level for 1 min.) 5000 V <sub>RMS</sub> coil to contact 2500 V <sub>RMS</sub> between open contacts
<b>Surge Voltage</b> coil to contact	10 kV (at 1.2 x 50 $\mu$ s)
<b>Insulation Resistance</b>	1000 M $\Omega$ (min.) at 20°C, 500 VDC, 50% RH
<b>Creepage</b> coil to contact	$\geq 10.0$ mm
<b>Clearance</b> coil to contact	$\geq 10.0$ mm
<b>Temperature Range</b> operating	(at nominal coil voltage) -40°C (-40°F) to 85°C (185°F)
<b>Vibration resistance</b>	1.5 mm (0.062") DA at 10–55 Hz
<b>Shock resistance</b>	10 g
<b>Enclosure</b> type material group flammability	P.B.T. polyester RT II, flux proof IIla UL94 V-0
<b>Terminals</b>	Tinned copper alloy, P. C.
<b>Soldering</b> max. temperature max. time	270 °C (518°F) 5 seconds
<b>Cleaning</b> max. solvent temp. max. immersion time	80°C (176°F) 30 seconds
<b>Dimensions</b> length width height	38.0 mm (1.496") 33.0 mm (1.300") 41.5 mm (1.634")
<b>Weight</b>	76 grams (approx.)
<b>Packing unit in pcs</b>	10 per plastic tube / 150 per carton box
<b>Compliance</b>	UL 508, IEC 61810-1, RoHS, REACH

**ZETTLER**



# AZSR165

## DISCLAIMER

This product specification is to be used in conjunction with the application notes which can be downloaded from the regional ZETTLER relay websites. The specification provides an overview of the most significant part features. Any individual applications and operating conditions are not taken into consideration. It is recommended to test the product under application conditions. Responsibility for the application remains with the customer. Proper operation and service life cannot be guaranteed if the part is operated outside the specified limits.

## ZETTLER GROUP

Building on a foundation of more than a century of expertise in German precision engineering, ZETTLER Group is a world-class enterprise, engaged in the design, manufacturing, sales and distribution of electronic components. Our industry leadership is based on a unique combination of engineering competence and global scale.

For more information on other ZETTLER Group companies, please visit [ZETTLER-group.com](http://ZETTLER-group.com). For support on this product or other ZETTLER relays, please visit one of the group sites below.

## SITES FOR ZETTLER RELAYS

### NORTH AMERICA

American Zettler, Inc.  
[www.azettler.com](http://www.azettler.com)  
[sales@azettler.com](mailto:sales@azettler.com)

### EUROPE

Zettler Electronics, GmbH  
[www.zettlerelectronics.com](http://www.zettlerelectronics.com)  
[office@zettlerelectronics.com](mailto:office@zettlerelectronics.com)

Zettler Electronics, Poland  
[www.zettlerelectronics.pl](http://www.zettlerelectronics.pl)  
[office@zettlerelectronics.pl](mailto:office@zettlerelectronics.pl)

### CHINA

Zettler Group, China  
[www.zettlercn.com](http://www.zettlercn.com)  
[relay@zettlercn.com](mailto:relay@zettlercn.com)

### ASIA PACIFIC

Zettler Electronics (HK) Ltd.  
[www.zettlerhk.com](http://www.zettlerhk.com)  
[sales@zettlerhk.com](mailto:sales@zettlerhk.com)



**ZETTLER**