

SWITCHING MODE POWER SUPPLY APPLICATION.
CONVERTER & CHOPPER APPLICATION.

FEATURES

- Average Output Rectified Current
: $I_O=20A$.
- Repetitive Peak Reverse Voltage
: $V_{RRM}=200V$.
- Low Forward Voltage.
- Low Reverse Current.
- Molding Compound Flammability Rating : UL 94V-0
- Pb-Free, Halogen-Free, RoHs Compliant

MAXIMUM RATING (Ta=25°C)



CHARACTERISTIC	SYMBOL	RATING	UNIT
Repetitive Peak Reverse Voltage	V_{RRM}	200	V
Average Output Rectified Current (Tc=110°C) (Note)	I_O	20	A
Peak One Cycle Surge Forward Current (Non-Repetitive 60Hz)	I_{FSM}	150	A
Junction Temperature	T_j	-40 150	°C
Storage Temperature Range	T_{stg}	-55 150	°C

Note : average forward current of centertap full wave connection.


ELECTRICAL CHARACTERISTICS (Ta=25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Peak Forward Voltage (Note)	V_{FM}	$I_{FM}=1A$	-	0.50	-	V
		$I_{FM}=10A$	-	0.80	0.85	
Repetitive Peak Reverse Current (Note)	I_{RRM}	$V_{RRM}=200V$	-	5	150	μA
Total Capacitance (Note)	C_T	$V_R=0V, f=1MHz$	-	930	-	pF
Reverse Recovery Time (Note)	t_{rr}	$I_F=1A, V_R=30V, di/dt=-50A/\mu s$	-	25	-	nS
Thermal Resistance (Note)	$R_{th(j-c)}$	Juction to Case	-	-	4	°C/W


Note : A value of one cell




$I_F - V_F$




$I_R - V_R$



$C_T - V_R$



$I_{FSM} - \text{CYCLE CHARACTERISTICS}$



$P_D - T_C$

