

SWITCHING MODE POWER SUPPLY APPLICATION. CONVERTER & CHOPPER APPLICATION.



FEATURES

- Average Output Rectified Current
: $I_O=20A$.
- Repetitive Peak Reverse Voltage
: $V_{RRM}=200V$.
- Low Forward Voltage.
- Low Reverse Current.
- Molding Compound Flammability Rating : UL 94V-0
- Pb-Free, Halogen-Free, RoHs Compliant

MAXIMUM RATING ($T_a=25^{\circ}C$)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Repetitive Peak Reverse Voltage	V_{RRM}	200	V
Average Output Rectified Current (Note)	I_O	20	A
Peak One Cycle Surge Forward Current (Non-Repetitive 60Hz)	I_{FSM}	150	A
Junction Temperature	T_j	-40 150	$^{\circ}C$
Storage Temperature Range	T_{stg}	-55 150	$^{\circ}C$

Note : average forward current of centertap full wave connection.



ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}C$)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Peak Forward Voltage (Note)	V_{FM}	$I_{FM}=1A$	-	0.52	-	V
		$I_{FM}=5A$	-	0.85	-	
		$I_{FM}=10A$	-	1.21	1.4	
Repetitive Peak Reverse Current (Note)	I_{RRM}	$V_{RRM}=200V$	-	-	100	μA
Junction Capacitance (Note)	C_J	$V_R=0V, f=1MHz$	-	1	-	nF
Thermal Resistance (Note)	$R_{th(j-c)}$	Juction to Case	-	-	4	$^{\circ}C/W$

Note : A value of one cell

TMBRF20200CT

