



# 2mm SOCKET STRIPS SMM SERIES

Works with:  
TMM, TMMH, MTMM,  
MMT, LTMM, TW, FTW,  
TCMD

## Features

- Four-finger contacts provide reliability and performance when mating with square terminals.
- Slotted tails provide added adhesion of solder paste and additional joint strength after reflow.
- "Solder stop" is designed into the contact to prevent wicking.
- High temperature LCP body is ideal for vapor phase or infrared soldering.
- Optional alignment/retention clips.

## Specifications:

**SMM HI-TEMP**

**Insulator Material:**  
Black Liquid Crystal Polymer

**Contact Material:**  
BeCu

**Operating Temp Range:**  
-65°C to +125°C

**Max Processing Temp:**  
230°C for 60 seconds

**Plating:**  
Sn or Au over  
50µ" (1,27µm) Ni

**SMT Lead Coplanarity:**  
.004" (0,10mm) max

**Contact Resistance:**  
10 mΩ max

**Insertion Depth:**  
.080" (2,03mm)  
to .120" (3,05mm)

**Insertion Force:**  
4.5 oz (1,25N) average

**Withdrawal Force:**  
3.0 oz (0,83N) average

**Max Cycles:**  
100 with 10µ" (0,25µm) Au

**Note:**  
Some lengths, styles and options are non-standard, non-returnable.

<b>SMM</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>LEAD STYLE</b>	<b>PLATING OPTION</b>	<b>ROW OPTION</b>	<b>LOCKING OPTION</b>
<b>01 thru 40</b> 			<b>-S</b> =30µ" (0,76µm) Gold contact 150µ" (3,81µm) Tin tail	<b>-S</b> = Single Row  <b>-D</b> = Double Row	<b>-P</b> = Pick & Place Pad  -S Row (4,95) X (7,62) X (3,00) -D Row (5,71) X (10,01) X (3,94)	<b>-XX</b> = Polarized Position Specify "XX" for position number.  <b>-TR</b> = Tape & Reel Packaging (Style -02 only)
			<b>-01</b> =Through Hole 			
			<b>-02</b> =Surface Mount (02 pins per row minimum) 	<b>TAPE &amp; REEL AVAILABILITY</b> No tooling charges. 125 piece minimum order. Order any quantity above minimum. In-house design, manufacture. Quick turn-around. Call Samtec for specifications and ordering information.		

**POLARIZING KEY**  
Specify PK-07 for polarizing key. Also polarizes TCSD Series IDC Cable.

**APPLICATION SPECIFIC OPTION**  
Locking clip option available. Call Samtec.

