











130 ... 230 MHz
class C for FM mobile applications

TYPE	PACKAGE	CONFIG.	V _{CC} (V)	P _{out} min (W)	f _o (MHz)	P _{in} (W)	G _p min (dB)	η _c min (%)		
SD 1134-5	.280 4LSL (B)	CE	7,5	0,5	150	0,1	7	—		
SD 1080-2	XO-72 SL	CE	7,5	0,75	175	0,1	8	—	TO-46 (CB-401)	TO-220 (CB-402)
SD 1115-2	TO-117 SL	CE	7,5	2	175	0,25	8	—		
SD 1012-4	.280 4LSL (B)	CE	7,5	2,5	175	0,79	5	—		
SD 1135-3	.280 4LSL (B)	CE	7,5	2,5	150	0,22	11	—		
2N 4427	TO-39	CE	12	1	175	0,1	10	—		
SD 1484-10	TO-46	CE	12,5	1	175	0,1	10	—	TO-39 (CB-7)	TO-60 (CB-27)
SD 1127	TO-39	CE	12,5	4	175	0,4	10	—		
2N 6080	.380 4L STUD	CE	12,5	4	175	0,25	12	60		
SD 1574	TO-220	CE	12,5	5	175	0,5	10	—		
SD 1012-3	.380 4LFL	CE	12,5	6	175	0,25	9	—		
SD 1133	.380 4L STUD	CE	12,5	10	175	1	10	—		
SD 1143	.380 4L STUD	CE	12,5	10	175	1	10	—		
SD 1143-1	.380 4LFL	CE	12,5	10	175	1	10	—		
2N 6081	.380 4L STUD	CE	12,5	15	175	3,5	6,3	60		XO-72 SL (CB-301)
SD 1014-6	.380 4LFL	CE	12,5	15	175	3,5	6,3	—		
SD 1575	TO-220	CE	12,5	15	175	4	6,3	—		
2N 6082	.380 4L STUD	CE	12,5	25	175	6	6,2	50		
SD 1229-1	.380 4LFL	CE	12,5	25	175	7,9	5	—		
SD 1272	.380 4L STUD	CE	12,5	25	175	3	9,2	—		TO-117 SL (CB-299)
SD 1272-2	.380 4LFL	CE	12,5	25	175	3	9,2	—		
SD 1274	.380 4L STUD	CE	12,5	30	175	3	10	—		
SD 1274-1	.380 4L FL	CE	12,5	30	175	3	10	—		
2N 6083	.380 4L STUD	CE	12,5	30	175	8,1	5,7	50		
SD 1577	TO-220	CE	12,5	30	175	9	5,2	—		
2N 6084	.380 4L STUD	CE	12,5	40	175	14	4,5	50		.280 4L SL (B) (CB-304)
SD 1018-6	.380 4LFL	CE	12,5	40	175	14	4,5	70		
SD 1018-15	.380 4LFL	CE	12	40	175	12	4,5	70		
SD 1278	.380 4L STUD	CE	12,5	40	175	10	6	—		
SD 1275	.380 4L STUD	CE	12,5	40	175	5	9	—		
SD 1275-1	.380 4L FL	CE	12,5	40	175	5	9	—		
SD 1428*	.500 6LFL	CE	12,5	45	175	11,3	6,5	50		.380 4L FL (CB-305)
SD 1477*	.500 6LFL	CE	12,5	100	175	25	6	—		
SD 1441*	.500 6LFL	CE	12,5	150	175	40	5	—		
SD 1021	.380 4L STUD	CE	12,5	5,5	230	1,3	6,2	60		
SD 1022	.380 4L STUD	CE	12,5	30	230	5,5	7,4	60		.380 4L STUD (CB-298)
2N 5589	.380 NARROW 4L STUD	CE	13,6	3	175	0,2	8,2	50		
2N 3924	TO-39	CE	13,6	4	175	1	6	70		
2N 3926	TO-60	CE	13,6	7	175	1,7	5,4	70		
2N 5590	.380 4L STUD	CE	13,6	10	175	2,3	5,2	50		
2N 3927	TO-60	CE	13,6	12	175	4	4,8	80		.380 NARROW 4L STUD (CB-400)
2N 5591	.380 4L STUD	CE	13,6	25	175	8,3	4,4	50		
SD 1273	.380 4L STUD	CE	13,6	40	160	5	9	55		
2N 3553	TO-39	CE	28	2,5	175	0,25	10	—		
2N 5641	.380 NARROW 4L STUD	CE	28	7	175	0,45	8,4	60		
2N 3632	TO-60	CE	28	13,5	175	3,5	5,8	—		
2N 5642	.380 4L STUD	CE	28	20	175	1,4	8,2	60		
2N 5643	.380 4L STUD	CE	28	40	175	6,6	7,6	60		
THB 94	.500 4LFL	CE	28	50 §	175	10	7	65		.500 4L FL (CB-290)
THY 94	.550 4L STUD	CE	28	50 §	175	10	7	65		
TH 564	.500 6LFL	CE	28	150	175	15	10	60		.500 6L FL (CB-297)
* Internally input matched. § : Typical value.										.550 4L STUD (CB-291)