

# THYRISTOR(Through Hole/Isolated)

## SMG16C60F


**SanRex** Thyristor **SMG16C60F** is designed for full wave AC control applications. It can be used as an ON/OFF function or for phase control operation.

### Typical Applications

- Home Appliances : Electric Blankets, Starter for FL, other control applications
- Industrial Use : SMPS, Solenoid for Breakers, Motor Controls, Heater Controls, other control applications

### Features

- $I_{T(AV)}=16A$
- High Surge Current
- Low Voltage Drop
- Lead-Free Package



### Maximum Ratings


( $T_j=25^{\circ}C$  unless otherwise specified)

| Symbol       | Item                                | Reference                                                              | Ratings         | Unit             |
|--------------|-------------------------------------|------------------------------------------------------------------------|-----------------|------------------|
| $V_{RRM}$    | Repetitive Peak Reverse Voltage     |                                                                        | 600             | V                |
| $V_{RSM}$    | Non-Repetitive Peak Reverse Voltage |                                                                        | 720             | V                |
| $V_{DRM}$    | Repetitive Peak Off-State Voltage   |                                                                        | 600             | V                |
| $I_{T(AV)}$  | Average On-State Current            | Single phase, half wave, $180^{\circ}$ , conduction, $T_c=58^{\circ}C$ | 16              | A                |
| $I_{T(RMS)}$ | R.M.S. On-State Current             | Single phase, half wave, $180^{\circ}$ , conduction, $T_c=58^{\circ}C$ | 25.1            | A                |
| $I_{TSM}$    | Surge On-State Current              | 50Hz/60Hz, $\frac{1}{2}$ cycle Peak value, non-repetitive              | 240/263         | A                |
| $I^2t$       | $I^2t$                              |                                                                        | 288             | A <sup>2</sup> S |
| $P_{GM}$     | Peak Gate Power Dissipation         |                                                                        | 5               | W                |
| $P_{G(AV)}$  | Average Gate Power Dissipation      |                                                                        | 0.5             | W                |
| $I_{FGM}$    | Peak Gate Current                   |                                                                        | 2               | A                |
| $V_{FGM}$    | Peak Gate Voltage (Forward)         |                                                                        | 6               | V                |
| $V_{RGM}$    | Peak Gate Voltage (Reverse)         |                                                                        | 10              | V                |
| $V_{ISO}$    | Isolation Breakdown (R.M.S.)        | A.C 1minute                                                            | 1500            | V                |
| $T_j$        | Operating Junction Temperature      |                                                                        | $-40 \sim +125$ | $^{\circ}C$      |
| $T_{stg}$    | Storage Temperature                 |                                                                        | $-40 \sim +150$ | $^{\circ}C$      |
|              | Mass                                |                                                                        | 2               | g                |


### Electrical Characteristics

| Symbol        | Item                              | Reference                                  | Ratings |      |      | Unit          |
|---------------|-----------------------------------|--------------------------------------------|---------|------|------|---------------|
|               |                                   |                                            | Min.    | Typ. | Max. |               |
| $I_{DRM}$     | Repetitive Peak Off-State Current | $T_j=125^{\circ}C, V_D=V_{DRM}$            |         |      | 2    | mA            |
| $I_{RRM}$     | Repetitive Peak Reverse Current   | $T_j=125^{\circ}C, V_R=V_{RRM}$            |         |      | 2    | mA            |
| $V_{TM}$      | Peak On-State Voltage             | $I_T=35A$ , Inst. measurement              |         |      | 1.5  | V             |
| $I_{GT}$      | Gate Trigger Current              | $V_D=6V, R_L=10\Omega$                     |         |      | 30   | mA            |
| $V_{GT}$      | Gate Trigger Voltage              |                                            |         |      | 1.4  | V             |
| $V_{GD}$      | Non-Trigger Gate Voltage          | $T_j=125^{\circ}C, V_D=\frac{1}{2}V_{DRM}$ | 0.2     |      |      | V             |
| $I_H$         | Holding Current                   |                                            |         | 15   |      | mA            |
| $R_{th(j-c)}$ | Thermal Resistance                | Junction to case                           |         |      | 3    | $^{\circ}C/W$ |


## Gate Characteristics




## On-State Voltage Max




## Average On-State Current vs Power Dissipation (Single phase half wave)




## Average On-State Current vs Ambient Temperature (Single phase half wave)




## Surge On-State Current Rating (Non-Repetitive)



## Maximum Transient Thermal Impedance Characteristics



## $I_{GT} - T_j$ [Change Rate] (Typical)



## $V_{GT} - T_j$ (Typical)

