

**CMOS Low Phase Noise VCXO (for 45-90MHz Fund Xtal)**


**FEATURES**

- 45MHz to 90MHz Fundamental Mode Crystal.
- Output range: 45MHz – 90MHz (no PLL).
- CMOS outputs.
- Integrated variable capacitors.
- Supports 3.3V-Power Supply.
- Available in die form.
- Thickness 10 mil.


**DESCRIPTIONS**

PLL520-70 is a VCXO IC specifically designed to pull frequency fundamental crystals from 45MHz to 90MHz, with CMOS outputs. Its design was optimized to tolerate higher limits of interelectrodes capacitance and bonding capacitance to improve yield. It achieves very low current into the crystal resulting in better overall stability. Its internal varicaps allow an on chip frequency pulling, controlled by the VCON input.

**BLOCK DIAGRAM**



**DIE CONFIGURATION**



**DIE SPECIFICATIONS**

Name	Value
Size	62 x 65 mil
Reverse side	GND
Pad dimensions	80 micron x 80 micron
Thickness	10 mil

**DRIVE\_SEL AND OE\_CTRL TABLE**

Pad #19 DRIVE_SEL	Output Drive
0	High Drive CMOS
1	Standard CMOS (default)

Pad #30 OE_CTRL	State
0	Tri-state
1	Output enabled (default)

**CMOS Low Phase Noise VCXO (for 45-90MHz Fund Xtal)**
**ELECTRICAL SPECIFICATIONS**
**1. Absolute Maximum Ratings**

PARAMETERS	SYMBOL	MIN.	MAX.	UNITS
Supply Voltage	$V_{DD}$		7	V
Input Voltage, dc	$V_I$	$V_{SS}-0.5$	$V_{DD}+0.5$	V
Output Voltage, dc	$V_O$	$V_{SS}-0.5$	$V_{DD}+0.5$	V
Storage Temperature	$T_S$	-65	150	°C
Ambient Operating Temperature*	$T_A$	-40	85	°C
Junction Temperature	$T_J$		125	°C
Lead Temperature (soldering, 10s)			260	°C
Input Static Discharge Voltage Protection			2	kV

Exposure of the device under conditions beyond the limits specified by Maximum Ratings for extended periods may cause permanent damage to the device and affect product reliability. These conditions represent a stress rating only, and functional operations of the device at these or any other conditions above the operational limits noted in this specification is not implied.

\* **Note:** Operating Temperature is guaranteed by design for all parts (COMMERCIAL and INDUSTRIAL), but tested for INDUSTRIAL grade only.

**2. Crystal Specifications**

PARAMETERS	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Built-in Capacitance	CX+	45MHz to 90MHz (VDD=3.3V)			2	pF
	CX-				2	
Inter-electrode capacitance	$C_0$			3.6		
C0/C1 ratio (gamma)	$\gamma$				250	-
Oscillation Frequency	OF	Fund.	45		90	MHz

**3. Voltage Control Crystal Oscillator**

PARAMETERS	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
VCXO Stabilization Time *	$T_{VCXOSTB}$	From power valid		10		ms
VCXO Tuning Range		XTAL $C_0/C_1 < 250$	200*			ppm
CLK output pullability		$0V \leq VCON \leq 3.3V$ at room temperature		$\pm 100^*$		ppm
On-chip Varicaps control range		$VCON = 0$ to 3.3V		4 – 18*		pF
Linearity				5*	10*	%
VCXO Tuning Characteristic				65		ppm/V
VCON input impedance				60		k $\Omega$
VCON modulation BW		$0V \leq VCON \leq 3.3V, -3dB$	25			kHz

**Note:** Parameters denoted with an asterisk (\*) represent nominal characterization data and are not production tested to any specific limits.

**CMOS Low Phase Noise VCXO (for 45-90MHz Fund Xtal)**
**4. General Electrical Specifications**

PARAMETERS	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Supply Current (Loaded Outputs)	$I_{DD}$				40	mA
Operating Voltage	$V_{DD}$		3.13		3.47	V
Output Clock Duty Cycle		@ 1.4V	45	50	55	%
Short Circuit Current				±50		mA

**5. Jitter specifications**

PARAMETERS	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Period jitter RMS	77.76MHz		3.5*		ps
Period jitter peak-to-peak	77.76MHz		24*		ps
Integrated jitter RMS	Integrated 12 kHz to 20 MHz at 77.76MHz		0.5*		ps

\*: To be measured

**6. Phase noise specifications**

PARAMETERS	FREQUENCY	@ 10Hz	@100Hz	@1kHz	@10kHz	@100kHz	UNITS
Phase Noise relative to carrier	77.76MHz	-75	-95	-125	-145	-155	dBc/Hz

Note: Phase Noise at VCON = 0V – to be measured

**7. CMOS Output Electrical Specifications**

PARAMETERS	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output High Voltage	$V_{OH}$	$I_{OH} = -12mA$ (Standard drive)	2.4			V
Output Low Voltage	$V_{OL}$	$I_{LO} = 12mA$ (Standard drive)			0.4	V
Output High Voltage at CMOS level	$V_{OHC}$	$I_{OH} = -4mA$ (Standard drive)	$V_{DD} - 0.4$			V
Output drive current		At TTL level (High drive)	36	51		mA
		At TTL level (Standard drive)	12	17		mA

**8. CMOS Switching Characteristics**

PARAMETERS	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output Clock Rise/Fall Time (Standard Drive)		0.8V ~ 2.0V with 10 pF load		1.15		ns
		0.3V ~ 3.0V with 15 pF load		3.7		
Output Clock Rise/Fall Time (High Drive)		0.8V ~ 2.0V with 10 pF load		0.5		
		0.3V ~ 3.0V with 15 pF load		1.5		

**CMOS Low Phase Noise VCXO (for 45-90MHz Fund Xtal)**
**PAD ASSIGNMENT**

Pad #	Name	X (μm)	Y (μm)
1	<i>Optional GND</i>	248	109
2	<i>Optional GND</i>	361	109
3	<i>Optional GND</i>	473	109
4	<i>Optional GND</i>	587	109
5	GND	702	109
6	<i>Reserved</i>	874	109
7	<i>Optional GNDBUF</i>	1042	109
8	<i>Optional GNDBUF</i>	1171	109
9	<i>Not connected</i>	1400	125
10	<i>Not connected</i>	1400	259
11	CMOS OUT	1400	476
12	VDDBUF	1400	616
13	<i>Optional VDDBUF</i>	1400	716
14	<i>Not connected</i>	1400	871
15	<i>Not connected</i>	1400	1089
16	<i>Optional CMOS OUT</i>	1400	1227
17	GNDBUF	1389	1365
18	<i>Reserved</i>	1232	1365
19	DRIVE_SEL	1042	1365
20	<i>Not connected</i>	854	1365
21	<i>Optional VDD</i>	659	1365
22	<i>Optional VDD</i>	559	1365
23	VDD	459	1365
24	<i>Optional VDD</i>	358	1365
25	<i>Not connected</i>	194	1365
26	XIN	109	1223
27	XOUT	109	1017
28	<i>Not connected</i>	109	858
29	<i>Not connected</i>	109	646
30	OE_CTRL	109	397
31	VCON	109	181

Note: for optimal Phase Noise performance, it is recommended to bond all optional VDD and GND pads.

**CMOS Low Phase Noise VCXO (for 45-90MHz Fund Xtal)**

**ORDERING INFORMATION**

***For part ordering, please contact our Sales Department:***


47745 Fremont Blvd., Fremont, CA 94538, USA

Tel: (510) 492-0990 Fax: (510) 492-0991

**PART NUMBER**

The order number for this device is a combination of the following:

Device number, Package type and Operating temperature range



*PhaseLink Corporation, reserves the right to make changes in its products or specifications, or both at any time without notice. The information furnished by Phaselink is believed to be accurate and reliable. However, PhaseLink makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of whatever nature resulting from the use of, or reliance upon this product.*

**LIFE SUPPORT POLICY:** *PhaseLink's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of PhaseLink Corporation.*