



PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
25	10mΩ	55A



1. GATE
2. DRAIN
3. SOURCE

ABSOLUTE MAXIMUM RATINGS (T_C = 25 °C Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current	T _C = 25 °C	I_D	55	A
	T _C = 100 °C		36	
Pulsed Drain Current ¹		I_{DM}	140	
Avalanche Current		I_{AR}	20	
Avalanche Energy	L = 0.1mH	E_{AS}	140	mJ
Repetitive Avalanche Energy ²	L = 0.05mH	E_{AR}	5.6	
Power Dissipation	T _C = 25 °C	P_D	60	W
	T _C = 100 °C		38	
Operating Junction & Storage Temperature Range		T _j , T _{stg}	-55 to 150	°C
Lead Temperature (¹ / ₁₆ " from case for 10 sec.)		T _L	275	

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{θJC}$		2.5	°C / W
Junction-to-Ambient	$R_{θJA}$		65	
Case-to-Heatsink	$R_{θCS}$	0.7		

¹Pulse width limited by maximum junction temperature.

²Duty cycle ≤ 1%

ELECTRICAL CHARACTERISTICS (T_C = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	25			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	1	1.5	3	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0V, V_{GS} = \pm 20V$			±250	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 20V, V_{GS} = 0V$			25	μA
		$V_{DS} = 20V, V_{GS} = 0V, T_J = 125 °C$			250	

On-State Drain Current ¹	$I_{D(ON)}$	$V_{DS} = 10V, V_{GS} = 10V$	55			A
Drain-Source On-State Resistance ¹	$R_{DS(ON)}$	$V_{GS} = 7V, I_D = 24A$		11	14	mΩ
		$V_{GS} = 10V, I_D = 30A$		10	13	
Forward Transconductance ¹	g_{fs}	$V_{DS} = 15V, I_D = 30A$		16		S
DYNAMIC						
Input Capacitance	C_{iss}	$V_{GS} = 0V, V_{DS} = 15V, f = 1MHz$		2700		pF
Output Capacitance	C_{oss}			500		
Reverse Transfer Capacitance	C_{rss}			200		
Total Gate Charge ²	Q_g	$V_{DS} = 0.5V_{(BR)DSS}, V_{GS} = 10V, I_D = 30A$		25		nC
Gate-Source Charge ²	Q_{gs}			7		
Gate-Drain Charge ²	Q_{gd}			11		
Turn-On Delay Time ²	$t_{d(on)}$	$V_{DS} = 15V, R_L = 1\Omega, I_D \cong 30A, V_{GS} = 10V, R_{GS} = 2.5\Omega$		7		nS
Rise Time ²	t_r			7		
Turn-Off Delay Time ²	$t_{d(off)}$			24		
Fall Time ²	t_f			6		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T_C = 25 °C)						
Continuous Current	I_S			55		A
Pulsed Current ³	I_{SM}			150		
Forward Voltage ¹	V_{SD}	$I_F = I_S, V_{GS} = 0V$		1.3		V
Reverse Recovery Time	t_{rr}	$I_F = I_S, di_F/dt = 100A / \mu S$		37		nS
Peak Reverse Recovery Current	$I_{RM(REC)}$			200		A
Reverse Recovery Charge	Q_{rr}			0.043		μC

¹Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

²Independent of operating temperature.

³Pulse width limited by maximum junction temperature.

REMARK: THE PRODUCT MARKED WITH “P55N02LD”, DATE CODE or LOT #

TO-252 (DPAK) MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	9.35		10.1	H		0.8	
B	2.2		2.4	I	6.4		6.6
C	0.48		0.6	J	5.2		5.4
D	0.89		1.5	K	0.6		1
E	0.45		0.6	L	0.64		0.9
F	0.03		0.23	M	4.4		4.6
G	6		6.2	N			

