

PJP7N65 / PJF7N65

650V N-Channel Enhancement Mode MOSFET

FEATURES

- 7A , 650V, $R_{DS(ON)}=1.4\Omega@V_{GS}=10V, I_D=3.5A$
- Low ON Resistance
- Fast Switching
- Low Gate Charge
- Fully Characterized Avalanche Voltage and Current
- Specially Designed for AC Adapter, Battery Charge and SMPS
- In compliance with EU RoHs 2002/95/EC Directives

MECHANICAL DATA


- Case: TO-220AB / ITO-220AB Molded Plastic
- Terminals : Solderable per MIL-STD-750,Method 2026

ORDERING INFORMATION


TYPE	MARKING	PACKAGE	PACKING
PJP7N65	P7N65	TO-220AB	50PCS/TUBE
PJF7N65	F7N65	ITO-220AB	50PCS/TUBE

TO-220AB / ITO-220AB


TO-220AB



ITO-220AB



INTERNAL SCHEMATIC DIAGRAM



Maximum RATINGS and Thermal Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	Symbol	PJP7N65	PJF7N65	Units
Drain-Source Voltage	V_{DS}	650		V
Gate-Source Voltage	V_{GS}	± 30		V
Continuous Drain Current	I_D	7	7	A
Pulsed Drain Current ¹⁾	I_{DM}	28	28	A
Maximum Power Dissipation Derating Factor	P_D	125 1.0	45 0.36	W
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 to +150		$^{\circ}\text{C}$
Avalanche Energy with Single Pulse $I_{AS}=7A, V_{DD}=50V, L=15.7mH$	E_{AS}	420		mJ
Junction-to-Case Thermal Resistance	$R_{\theta JC}$	1.0	2.78	$^{\circ}\text{C/W}$
Junction-to Ambient Thermal Resistance	$R_{\theta JA}$	62.5	100	$^{\circ}\text{C/W}$

Note : 1 Maximum DC current limited by the package

PANJIT RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN,FUNCTIONS AND RELIABILITY WITHOUT NOTICE



PJP7N65 / PJF7N65

ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Units
Static						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	650	-	-	V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250uA	2.0	-	4.0	V
Drain-Source On-State Resistance	R _{DS(on)}	V _{GS} = 10V, I _D = 3.5A	-	1.1	1.4	Ω
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =650V, V _{GS} =0V	-	-	10	uA
Gate Body Leakage	I _{GSS}	V _{GS} =±30V, V _{DS} =0V	-	-	±100	nA
Dynamic						
Total Gate Charge	Q _g	V _{DS} =520V, I _D =7A, V _{GS} =10V	-	25.7	36.2	nC
Gate-Source Charge	Q _{gs}		-	7.5	-	
Gate-Drain Charge	Q _{gd}		-	8.8	-	
Turn-On Delay Time	t _{d(on)}	V _{DD} =325V, I _D =7A V _{GS} =10V, R _G =25Ω	-	13.2	18.8	ns
Turn-On Rise Time	t _r		-	18.2	26.5	
Turn-Off Delay Time	t _{d(off)}		-	33.6	52	
Turn-Off Fall Time	t _f		-	17.8	26	
Input Capacitance	C _{iss}	V _{DS} =25V, V _{GS} =0V f=1.0MH _Z	-	1100	1450	pF
Output Capacitance	C _{oss}		-	106	150	
Reverse Transfer Capacitance	C _{rss}		-	8	16	
Source-Drain Diode						
Max. Diode Forward Current	I _S	-	-	-	7.0	A
Max.Pulsed Source Current	I _{SM}	-	-	-	28	A
Diode Forward Voltage	V _{SD}	I _S =7A , V _{GS} =0V	-	-	1.4	V
Reverse Recovery Time	t _{rr}	V _{GS} =0V, I _F =7A di/dt=100A/us	-	365	-	ns
Reverse Recovery Charge	Q _{rr}		-	3.4	-	uC

NOTE : Plus Test : Pluse Width ≤ 300us, Duty Cycle ≤ 2%.

PJP7N65 / PJF7N65

Typical Characteristics Curves ($T_a=25^\circ\text{C}$, unless otherwise noted)




Fig.1 Output Characteristic




Fig.2 Transfer Characteristic




Fig.3 On Resistance vs Drain Current




Fig.4 On Resistance vs Gate to Source Voltage




Fig.5 On Resistance vs Junction Temperature




Fig.6 Capacitance

PJP7N65 / PJF7N65

Typical Characteristics Curves ($T_a=25^\circ\text{C}$, unless otherwise noted)




Fig. 7 Gate Charge Waveform




Fig.8 Source-Drain Diode Forward Voltage




Fig.9 Breakdown Voltage vs Junction Temperature



PJP7N65 / PJF7N65

LEGAL STATEMENT

Copyright PanJit International, Inc 2009

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.