

Your right power solution for LCD TV, NB PC & various IT/AV applications

0405B series- Model: 0405B24216

216W 24V/9A



Features

- ⊙ Best solution for TV 32"
- ⊙ Universal AC input
- ⊙ Efficiency: 85% @full load typical
- ⊙ PFC >0.9 @240VAC
- ⊙ High MTBF & Life

Safety



Environmental

Operating Temperature: 0°C to +40°C
Storage Temperature: -40°C to +70°C

Electrical specification

INPUT

AC input range	88 ~280VAC
Frequency	47 to 63Hz
Inrush current	200A @230VAC, cold start , 25°C
Input current	3.0A rms @100VAC full load
Efficiency	85% @full load typical
EMI/FRI	FCC part 15, subpart B Class B EN55022(CISPR22) Class B
Power saving	<1W/240VAC @ no load
Leakage current	0.5 mA max. @ 254Vac/ 50Hz

OUTPUT

Output rating (V/A)	24V/9A
Voltage regulation	23.4 ~ 24.6V
Max. Power (Po)	216W
Hold-up time	10ms. typical at full load ,115VAC
Over voltage protection	32V max. @ latch mode
Short CKT protection	shut down & auto recovery mode
Over temperature	Optional @shut down mode
Protection	

Outline Drawing (mm)



Output DC cable plug: Optional

*Specifications subject to change without notice.