

ABSOLUTE MAXIMUM RATING per LED

SSA-009

PARAMETER	Value	Units
Reverse Voltage	6	V
Forward Current	30	mA
Surage Current (t>10us)	1	A
Storage Temperature Range	-55 to +100	°C
Junction Temperature (Tj)	100	°C
Total Power Dissipation @ 25 °C	100	mW
Thermal Resistance Juction to Air	400	K/W

ELECTRICAL CHARACTERISTICS (Tamb=25°C)

Parameter	Unit	Colour			
		Orange	HERed	Yellow	Green
Peak Wavelength λ_p	nm	605	635	586	565
Forward Voltage Vf (If = 10mA)	Volts Max	3	3	3	3
Reverse Current Ir (Vr = 6Volts)	μ A Max		10	10	10
Luminous Intensity (If = 10mA)	Mcd min	1.6	2.5	2.5	4

Ordering Information

To specify your requirement, please state:

- 1 SSA -009
- 2 The combination of LEDs or I.R. products, in order.

SSA-009X

where X = O = All Orange, H = All HERed , Y = All Yellow, G = All Green

For mixed colours specify from left to right . E.g. SSA-009 HHGYGRR

1st Element to 8th Element

Custom part numbers will be issued for these combinations.

BEDFORD OPTO TECHNOLOGY LTD
1,BIGGAR BUSINESS PARK , BIGGAR,LANARKSHIRE ML12 6FX
Tel: +44 (0) 1899 221221 Fax: +44 (0) 1899 221009
Website: bot.co.uk E-mail: bill@bot.co.uk