

# MOTOROLA Semiconductors

3501 ED BLUESTEIN BLVD., AUSTIN, TEXAS 78721


## Advance Information

### 1.5 AND 2.0 MHz COMPONENTS FOR THE M6800 MICROCOMPUTER SYSTEM

The eight devices described in this data sheet extend the operating frequency of the M6800 Microcomputer Family. The block diagrams and device operation are the same as for the basic M6800-series components.

- Fully Hardware and Software Compatible with the M6800 Family
- Power Dissipation Approximately 20% Lower Than on Standard MC6800 Series
- Clock Specification Improved for Reduced Complexity of Clock Generator/Driver Circuitry
- The MC6821 and its higher-frequency versions provide drive capability of two TTL loads on all A- and B-side buffers, improving the drive capability of the MC6820.

M6800 MICROCOMPUTER FAMILY  
BLOCK DIAGRAM



1.5 MHz

2.0 MHz

## MC68A00•MC68B00

MPU

## MC68A21•MC68B21

PIA

## MC68A50•MC68B50

ACIA


## MCM68A10•MCM68B10

RAM

## MOS

(N-CHANNEL, SILICON-GATE)

### MICROPROCESSOR SYSTEM COMPONENTS



P SUFFIX  
PLASTIC PACKAGE  
CASE 711

NOT SHOWN: L SUFFIX  
CERAMIC PACKAGE  
CASE 715

For additional information on these devices—including block diagrams, signal descriptions, device operation and pin assignments—refer to the *M6800 Microcomputer System Design Data* brochure.

# **MICROPROCESSING UNIT (MPU)** **MC68A00 • MC68B00**

## **ELECTRICAL CHARACTERISTICS** ( $V_{CC} = 5.0 \text{ V}$ , $\pm 5\%$ , $V_{SS} = 0$ , $T_A = 0$ to $70^\circ\text{C}$ unless otherwise noted.)

| Characteristic                                                                                                                                                                                                                                                                                                     | Symbol                                                                                                                                    | Min                                                                                      | Typ                                     | Max                              | Unit                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-----------------------------------------|----------------------------------|------------------------------------|
| Input High Voltage<br>Logic<br>$\phi 1, \phi 2$                                                                                                                                                                                                                                                                    | $V_{IH}$<br>$V_{IHC}$                                                                                                                     | $V_{SS} + 2.0$<br>$V_{CC} - 0.6$                                                         | —<br>—                                  | $V_{CC}$<br>$V_{CC} + 0.3$       | Vdc                                |
| Input Low Voltage<br>Logic<br>$\phi 1, \phi 2$                                                                                                                                                                                                                                                                     | $V_{IL}$<br>$V_{ILC}$                                                                                                                     | $V_{SS} - 0.3$<br>$V_{SS} - 0.3$                                                         | —<br>—                                  | $V_{SS} + 0.8$<br>$V_{SS} + 0.4$ | Vdc                                |
| Input Leakage Current<br>( $V_{in} = 0$ to $5.25 \text{ V}$ , $V_{CC} = \text{max}$ )<br>( $V_{in} = 0$ to $5.25 \text{ V}$ , $V_{CC} = 0.0 \text{ V}$ )<br>Logic*<br>$\phi 1, \phi 2$                                                                                                                             | $I_{in}$                                                                                                                                  | —<br>—                                                                                   | 1.0<br>—                                | 2.5<br>100                       | $\mu\text{Adc}$                    |
| Three-State (Off State) Input Current<br>( $V_{in} = 0.4$ to $2.4 \text{ V}$ , $V_{CC} = \text{max}$ )<br>D0–D7<br>A0–A15, R/W                                                                                                                                                                                     | $I_{TSI}$                                                                                                                                 | —<br>—                                                                                   | 2.0<br>—                                | 10<br>100                        | $\mu\text{Adc}$                    |
| Output High Voltage<br>( $I_{Load} = -205 \mu\text{Adc}$ , $V_{CC} = \text{min}$ )<br>( $I_{Load} = -145 \mu\text{Adc}$ , $V_{CC} = \text{min}$ )<br>( $I_{Load} = -100 \mu\text{Adc}$ , $V_{CC} = \text{min}$ )<br>D0–D7<br>A0–A15, R/W, VMA<br>BA                                                                | $V_{OH}$                                                                                                                                  | $V_{SS} + 2.4$<br>$V_{SS} + 2.4$<br>$V_{SS} + 2.4$                                       | —<br>—<br>—                             | —<br>—<br>—                      | Vdc                                |
| Output Low Voltage<br>( $I_{Load} = 1.6 \text{ mAdc}$ , $V_{CC} = \text{min}$ )                                                                                                                                                                                                                                    | $V_{OL}$                                                                                                                                  | —                                                                                        | —                                       | $V_{SS} + 0.4$                   | Vdc                                |
| Power Dissipation                                                                                                                                                                                                                                                                                                  | $P_D$                                                                                                                                     | —                                                                                        | 0.5                                     | 1.0                              | W                                  |
| Capacitance #<br>( $V_{in} = 0$ , $T_A = 25^\circ\text{C}$ , $f = 1.0 \text{ MHz}$ )<br>$\phi 1$<br>$\phi 2$<br>D0–D7<br>Logic Inputs<br>A0–A15, R/W, VMA                                                                                                                                                          | $C_{in}$<br><br><br><br><br><br><br>$C_{out}$                                                                                             | —<br>—<br>—<br>—                                                                         | —<br>—<br>10<br>6.5                     | 35<br>70<br>12.5<br>10           | pF                                 |
| Frequency of Operation<br>MC68A00<br>MC68B00                                                                                                                                                                                                                                                                       | $f$                                                                                                                                       | 0.1<br>0.1                                                                               | —<br>—                                  | 1.5<br>2.0                       | MHz                                |
| Clock Timing (Figure 1)<br>Cycle Time<br>Clock Pulse Width<br>(Measured at $V_{CC} - 0.6 \text{ V}$ )<br>Total $\phi 1$ and $\phi 2$ Up Time<br>Rise and Fall Times<br>(Measured between $V_{SS} + 0.4$ and $V_{CC} - 0.6$ )<br>Delay Time or Clock Separation<br>(Measured at $V_{OV} = V_{SS} + 0.6 \text{ V}$ ) | MC68A00<br>MC68B00<br>$\phi 1, \phi 2$ — MC68A00<br>$\phi 1, \phi 2$ — MC68B00<br>MC68A00<br>MC68B00<br>$t_{\phi r}, t_{\phi f}$<br>$t_d$ | $t_{cyc}$<br>$t_{cyc}$<br>$PW_{\phi H}$<br>$t_{ut}$<br>$t_{\phi r}, t_{\phi f}$<br>$t_d$ | 0.666<br>0.50<br>230<br>600<br>5.0<br>0 | —<br>—<br>—<br>—<br>—<br>—       | 10<br>10<br>9500<br>ns<br>ns<br>ns |

\*Except IRQ and NMI, which require a  $3.0 \text{ k}\Omega$  pullup load resistor for wire-OR capability at optimum operation.

#Capacitances are periodically sampled rather than 100% tested.



## READ/WRITE TIMING

| Characteristic                                                        | Symbol               | MC68A00 |     |            | MC68B00 |     |            | Unit |
|-----------------------------------------------------------------------|----------------------|---------|-----|------------|---------|-----|------------|------|
|                                                                       |                      | Min     | Typ | Max        | Min     | Typ | Max        |      |
| Address Delay<br>C = 90 pF<br>C = 30 pF                               | $t_{AD}$             | —       | —   | 180<br>165 | —       | —   | 150<br>135 | ns   |
| Peripheral Read Access Time<br>$t_{ac} = t_{ut} - (t_{AD} + t_{DSR})$ | $t_{acc}$            | —       | —   | 360        | —       | —   | 250        | ns   |
| Data Setup Time (Read)                                                | $t_{DSR}$            | 60      | —   | —          | 40      | —   | —          | ns   |
| Input Data Hold Time                                                  | $t_H$                | 10      | —   | —          | 10      | —   | —          | ns   |
| Output Data Hold Time                                                 | $t_H$                | 10      | 25  | —          | 10      | 25  | —          | ns   |
| Address Hold Time (Address, R/W, VMA)                                 | $t_{AH}$             | 10      | 75  | —          | 10      | 75  | —          | ns   |
| Enable High Time for DBE Input                                        | $t_{EH}$             | 280     | —   | —          | 220     | —   | —          | ns   |
| Data Delay Time (Write)                                               | $t_{DDW}$            | —       | 165 | 200        | —       | —   | 160        | ns   |
| Processor Controls                                                    |                      |         |     |            |         |     |            |      |
| Processor Control Setup Time                                          | $t_{PCS}$            | 200     | —   | —          | 200     | —   | —          | ns   |
| Processor Control Rise and Fall Time                                  | $t_{PCr}, t_{PCf}$   | —       | —   | 100        | —       | —   | 100        | ns   |
| Bus Available Delay                                                   | $t_{BA}$             | —       | —   | 270        | —       | —   | 270        | ns   |
| Three-State Enable                                                    | $t_{TSE}$            | —       | —   | 40         | —       | —   | 40         | ns   |
| Three-State Delay                                                     | $t_{TSD}$            | —       | —   | 270        | —       | —   | 270        | ns   |
| Data Bus Enable Down Time During $\phi 1$ Up Time                     | $t_{DBE}$            | 150     | —   | —          | 70      | —   | —          | ns   |
| Data Bus Enable Rise and Fall Times                                   | $t_{DBEr}, t_{DBEf}$ | —       | —   | 25         | —       | —   | 25         | ns   |

FIGURE 1 — CLOCK TIMING WAVEFORM





FIGURE 2 — READ/WRITE TIMING WAVEFORM



# PERIPHERAL INTERFACE ADAPTER (PIA) MC68A21 • MC68B21

## **ELECTRICAL CHARACTERISTICS** ( $V_{CC} = 5.0 \text{ V} \pm 5\%$ , $V_{SS} = 0$ , $T_A = 0 \text{ to } 70^\circ\text{C}$ unless otherwise noted.)

| Characteristic                                                                                                                                                                                                                             | Symbol                                | Min                              | Typ              | Max                              | Unit                                          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|----------------------------------|------------------|----------------------------------|-----------------------------------------------|
| Input High Voltage                                                                                                                                                                                                                         | $V_{IH}$                              | $V_{SS} + 2.0$                   | —                | $V_{CC}$                         | Vdc                                           |
| Input Low Voltage                                                                                                                                                                                                                          | $V_{IL}$                              | $V_{SS} - 0.3$                   | —                | $V_{SS} + 0.8$                   | Vdc                                           |
| Input Leakage Current<br>( $V_{in} = 0 \text{ to } 5.25 \text{ Vdc}$ )<br>R/W, $\overline{\text{Reset}}$ , RS0, RS1, CS0, $\overline{\text{CS2}}$ , CS1,<br>CA1, CB1, Enable                                                               | $I_{in}$                              | —                                | 1.0              | 2.5                              | $\mu\text{A}$                                 |
| Three-State (Off State) Input Current<br>( $V_{in} = 0.4 \text{ to } 2.4 \text{ Vdc}$ )<br>D0–D7, PB0–PB7, CB2                                                                                                                             | $I_{TSI}$                             | —                                | 2.0              | 10                               | $\mu\text{A}$                                 |
| Input High Current<br>( $V_{IH} = 2.4 \text{ Vdc}$ )<br>PA0–PA7, CA2                                                                                                                                                                       | $I_{IH}$                              | –200                             | –400             | —                                | $\mu\text{A}$                                 |
| Input Low Current<br>( $V_{IL} = 0.4 \text{ Vdc}$ )<br>PA0–PA7, CA2                                                                                                                                                                        | $I_{IL}$                              | —                                | –1.3             | –2.4                             | $\text{mA}$                                   |
| Output High Voltage<br>( $I_{Load} = -205 \mu\text{A}$ )<br>( $I_{Load} = -200 \mu\text{A}$ )<br>D0–D7<br>Other Outputs                                                                                                                    | $V_{OH}$                              | $V_{SS} + 2.4$<br>$V_{SS} + 2.4$ | —<br>—           | —<br>—                           | Vdc                                           |
| Output Low Voltage<br>( $I_{Load} = 1.6 \text{ mA}$ )<br>( $I_{Load} = 3.2 \text{ mA}$ )<br>D0–D7<br>Other Outputs                                                                                                                         | $V_{OL}$                              | —<br>—                           | —<br>—           | $V_{SS} + 0.4$<br>$V_{SS} + 0.4$ | Vdc                                           |
| Output High Current (Sourcing)<br>( $V_{OH} = 2.4 \text{ Vdc}$ )<br>D0–D7<br>Other Outputs<br>( $V_O = 1.5 \text{ Vdc}$ , the current for driving other<br>than TTL, e.g., Darlington Base)<br>PB0–PB7, CB2                                | $I_{OH}$                              | –205<br>–100<br>–1.0             | —<br>—<br>–2.5   | —<br>—<br>–10                    | $\mu\text{A}$<br>$\mu\text{A}$<br>$\text{mA}$ |
| Output Leakage Current (Off State)<br>( $V_{OH} = 2.4 \text{ Vdc}$ )<br>IRQA, IRQB                                                                                                                                                         | $I_{LOH}$                             | —                                | 1.0              | 10                               | $\mu\text{A}$                                 |
| Power Dissipation                                                                                                                                                                                                                          | $P_D$                                 | —                                | —                | 550                              | mW                                            |
| Capacitance<br>( $V_{in} = 0$ , $T_A = 25^\circ\text{C}$ , $f = 1.0 \text{ MHz}$ )<br>D0–D7<br>PA0–PA7, PB0–PB7, CA2, CB2<br>Enable, R/W, $\overline{\text{Reset}}$ , RS0, RS1, CS0, CS1, $\overline{\text{CS2}}$ , CA1, CB1<br>IRQA, IRQB | $C_{in}$<br><br><br><br><br>$C_{out}$ | —<br>—<br>—<br>—                 | —<br>—<br>—<br>— | 12.5<br>10<br>7.5<br>5.0         | pF<br><br><br>pF                              |

### NOTE:

The PA0–PA7 Peripheral Data lines and the CA2 Peripheral Control line can drive two standard TTL loads. In the input mode, the internal pullup resistor on these lines represents a maximum of 1.5 standard TTL loads.



**TIMING CHARACTERISTICS** ( $V_{CC} = 5.0\text{ V} \pm 5\%$ ,  $V_{SS} = 0$ ,  $T_A = 0$  to  $70^\circ\text{C}$  unless otherwise noted.)

| Characteristic                                                                                                                        | Symbol     | MC68A21 |       | MC68B21 |      | Unit          |
|---------------------------------------------------------------------------------------------------------------------------------------|------------|---------|-------|---------|------|---------------|
|                                                                                                                                       |            | Min     | Max   | Min     | Max  |               |
| Peripheral Data Setup Time                                                                                                            | $t_{PDSU}$ | 135     | —     | 100     | —    | ns            |
| Peripheral Data Hold Time                                                                                                             | $t_{PDH}$  | 0       | —     | 0       | —    | ns            |
| Delay Time, Enable negative transition to CA2 negative transition                                                                     | $t_{CA2}$  | —       | 0.670 | —       | 0.5  | $\mu\text{s}$ |
| Delay Time, Enable negative transition to CA2 positive transition                                                                     | $t_{RS1}$  | —       | 0.670 | —       | 0.5  | $\mu\text{s}$ |
| Rise and Fall Times for CA1 and CA2 input signals                                                                                     | $t_r, t_f$ | —       | 1.0   | —       | 1.0  | $\mu\text{s}$ |
| Delay Time from CA1 active transition to CA2 positive transition                                                                      | $t_{RS2}$  | —       | 1.35  | —       | 1.0  | $\mu\text{s}$ |
| Delay Time, Enable negative transition to Peripheral Data Valid                                                                       | $t_{PDW}$  | —       | 0.670 | —       | 0.5  | $\mu\text{s}$ |
| Delay Time, Enable negative transition to Peripheral CMOS Data Valid<br>( $V_{CC} = 30\%$ , $V_{CC}$ ; Figure 6, Load C) PA0–PA7, CA2 | $t_{CMOS}$ | —       | 1.35  | —       | 1.0  | $\mu\text{s}$ |
| Delay Time, Enable positive transition to CB2 negative transition                                                                     | $t_{CB2}$  | —       | 0.670 | —       | 0.5  | $\mu\text{s}$ |
| Delay Time, Peripheral Data Valid to CB2 negative transition                                                                          | $t_{DC}$   | 20      | —     | 20      | —    | ns            |
| Delay Time, Enable positive transition to CB2 positive transition                                                                     | $t_{RS1}$  | —       | 0.670 | —       | 0.5  | $\mu\text{s}$ |
| Peripheral Control Output Pulse Width, CA2/CB2                                                                                        | $PW_{CT}$  | 550     | —     | 550     | —    | ns            |
| Rise and Fall Time for CB1 and CB2 input signals                                                                                      | $t_r, t_f$ | —       | 1.0   | —       | 1.0  | $\mu\text{s}$ |
| Delay Time, CB1 active transition to CB2 positive transition                                                                          | $t_{RS2}$  | —       | 1.35  | —       | 1.0  | $\mu\text{s}$ |
| Interrupt Release Time, IRQA and IRQB                                                                                                 | $t_{IR}$   | —       | 1.1   | —       | 0.85 | $\mu\text{s}$ |
| Interrupt Response Time                                                                                                               | $t_{RS3}$  | —       | 1.0   | —       | 1.0  | $\mu\text{s}$ |
| Interrupt Input Pulse Width                                                                                                           | $PW_I$     | 500     | —     | 500     | —    | ns            |
| Reset Low Time*                                                                                                                       | $t_{RL}$   | 0.66    | —     | 0.5     | —    | $\mu\text{s}$ |

\*The Reset line must be high a minimum of 1.0  $\mu\text{s}$  before addressing the PIA.

**BUS TIMING CHARACTERISTICS** ( $V_{CC} = 5.0\text{ V} \pm 5\%$ ,  $V_{SS} = 0$ ,  $T_A = 0$  to  $70^\circ\text{C}$  unless otherwise noted.)**READ**

| Characteristic                                                  | Symbol           | MC68A21 |     | MC68B21 |     | Unit          |
|-----------------------------------------------------------------|------------------|---------|-----|---------|-----|---------------|
|                                                                 |                  | Min     | Max | Min     | Max |               |
| Enable Cycle Time                                               | $t_{cycE}$       | 0.666   | —   | 0.50    | —   | $\mu\text{s}$ |
| Enable Pulse Width, High                                        | $PW_{EH}$        | 0.280   | —   | 0.22    | —   | $\mu\text{s}$ |
| Enable Pulse Width, Low                                         | $PW_{EL}$        | 0.280   | —   | 0.21    | —   | $\mu\text{s}$ |
| Setup Time, Address and R/W Valid to Enable positive transition | $t_{AS}$         | 140     | —   | 70      | —   | ns            |
| Data Delay Time                                                 | $t_{DDR}$        | —       | 220 | —       | 180 | ns            |
| Data Hold Time                                                  | $t_H$            | 10      | —   | 10      | —   | ns            |
| Address Hold Time                                               | $t_{AH}$         | 10      | —   | 10      | —   | ns            |
| Rise and Fall Time for Enable input                             | $t_{Er}, t_{Ef}$ | —       | 25  | —       | 25  | ns            |

**WRITE**




|                                                                 |                  |       |    |      |    |               |
|-----------------------------------------------------------------|------------------|-------|----|------|----|---------------|
| Enable Cycle Time                                               | $t_{cycE}$       | 0.666 | —  | 0.50 | —  | $\mu\text{s}$ |
| Enable Pulse Width, High                                        | $PW_{EH}$        | 0.280 | —  | 0.22 | —  | $\mu\text{s}$ |
| Enable Pulse Width, Low                                         | $PW_{EL}$        | 0.280 | —  | 0.21 | —  | $\mu\text{s}$ |
| Setup Time, Address and R/W Valid to Enable positive transition | $t_{AS}$         | 140   | —  | 70   | —  | ns            |
| Data Setup Time                                                 | $t_{DSW}$        | 80    | —  | 60   | —  | ns            |
| Data Hold Time                                                  | $t_H$            | 10    | —  | 10   | —  | ns            |
| Address Hold Time                                               | $t_{AH}$         | 10    | —  | 10   | —  | ns            |
| Rise and Fall Time for Enable input                             | $t_{Er}, t_{Ef}$ | —     | 25 | —    | 25 | ns            |







**NOTES:**

1. Figures shown are only those needed to define new measurements *not* specified on the MC6820 data sheet (page 39 of M6800 Microcomputer System Design Data). Refer to that data sheet, or to the new MC6821 data sheet, for further information.

2. On all tests, measurements on the Enable pulse are at 0.8 V and 2.0 V.

**FIGURE 3 — PERIPHERAL DATA HOLD TIME (Read Mode)****FIGURE 4 — PERIPHERAL CONTROL OUTPUT PULSE WIDTH****FIGURE 5 — INTERRUPT PULSE WIDTH and  $\overline{\text{IRQ}}$  RESPONSE**

\* Assumes Interrupt Enable Bits are set.

**FIGURE 6 — BUS TIMING TEST LOADS**

# **ASYNCHRONOUS COMMUNICATIONS INTERFACE ADAPTER (ACIA)** **MC68A50 • MC68B50**

## **ELECTRICAL CHARACTERISTICS** ( $V_{CC} = 5.0\text{ V} \pm 5\%$ , $V_{SS} = 0$ , $T_A = 0$ to $70^\circ\text{C}$ unless otherwise noted.)

| Characteristic                                                                                                                                                                                                | Symbol     | Min                              | Typ       | Max            | Unit            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|----------------------------------|-----------|----------------|-----------------|
| Input High Voltage                                                                                                                                                                                            | $V_{IH}$   | $V_{SS} + 2.0$                   | —         | $V_{CC}$       | Vdc             |
| Input Low Voltage                                                                                                                                                                                             | $V_{IL}$   | $V_{SS} - 0.3$                   | —         | $V_{SS} + 0.8$ | Vdc             |
| Input Leakage Current<br>( $V_{in} = 0$ to $5.25\text{ Vdc}$ )                                                                                                                                                | $I_{in}$   | —                                | 1.0       | 2.5            | $\mu\text{Adc}$ |
| Three-State (Off State) Input Current<br>( $V_{in} = 0.4$ to $2.4\text{ Vdc}$ )                                                                                                                               | $I_{TSI}$  | —                                | 2.0       | 10             | $\mu\text{Adc}$ |
| Output High Voltage<br>( $I_{Load} = -205\text{ }\mu\text{Adc}$ , Enable Pulse Width $< 25\text{ }\mu\text{s}$ )<br>( $I_{Load} = -100\text{ }\mu\text{Adc}$ , Enable Pulse Width $< 25\text{ }\mu\text{s}$ ) | $V_{OH}$   | $V_{SS} + 2.4$<br>$V_{SS} + 2.4$ | —<br>—    | —<br>—         | Vdc             |
| Output Low Voltage<br>( $I_{Load} = 1.6\text{ mAdc}$ , Enable Pulse Width $< 25\text{ }\mu\text{s}$ )                                                                                                         | $V_{OL}$   | —                                | —         | $V_{SS} + 0.4$ | Vdc             |
| Output Leakage Current (Off State)<br>( $V_{OH} = 2.4\text{ Vdc}$ )                                                                                                                                           | $I_{LOH}$  | —                                | 1.0       | 10             | $\mu\text{Adc}$ |
| Power Dissipation                                                                                                                                                                                             | $P_D$      | —                                | 300       | 525            | mW              |
| Capacitance<br>( $V_{in} = 0$ , $T_A = 25^\circ\text{C}$ , $f = 1.0\text{ MHz}$ )                                                                                                                             | $C_{in}$   | —                                | 10<br>7.0 | 12.5<br>7.5    | pF              |
|                                                                                                                                                                                                               | $C_{out}$  | —                                | —         | 10<br>5.0      | pF              |
| Minimum Clock Pulse Width, Low<br>$\div 16, \div 64$ Modes                                                                                                                                                    | $PW_{CL}$  | 600                              | —         | —              | ns              |
| Minimum Clock Pulse Width, High<br>$\div 16, \div 64$ Modes                                                                                                                                                   | $PW_{CH}$  | 600                              | —         | —              | ns              |
| Clock Frequency<br>$\div 1$ Mode<br>$\div 16, \div 64$ Modes                                                                                                                                                  | $f_C$      | —                                | —         | 500<br>800     | kHz             |
| Clock-to-Data Delay for Transmitter                                                                                                                                                                           | $t_{TDD}$  | —                                | —         | 1.0            | $\mu\text{s}$   |
| Receive Data Setup Time<br>$\div 1$ Mode                                                                                                                                                                      | $t_{RDSU}$ | 500                              | —         | —              | ns              |
| Receive Data Hold Time<br>$\div 1$ Mode                                                                                                                                                                       | $t_{RDH}$  | 500                              | —         | —              | ns              |
| Interrupt Request Release Time                                                                                                                                                                                | $t_{IR}$   | —                                | —         | 1.2            | $\mu\text{s}$   |
| Request-to-Send Delay Time                                                                                                                                                                                    | $t_{RTS}$  | —                                | —         | 1.0            | $\mu\text{s}$   |
| Input Transition Times (Except Enable)                                                                                                                                                                        | $t_r, t_f$ | —                                | —         | 1.0*           | $\mu\text{s}$   |

\*1.0  $\mu\text{s}$  or 10% of the pulse width, whichever is smaller.

## **BUS TIMING CHARACTERISTICS** ( $V_{CC} = 5.0\text{ V} \pm 5\%$ , $V_{SS} = 0$ , $T_A = 0$ to $70^\circ\text{C}$ unless otherwise noted.)

### **READ**

| Characteristic                                                  | Symbol           | MC68A50 |     | MC68B50 |     | Unit          |
|-----------------------------------------------------------------|------------------|---------|-----|---------|-----|---------------|
|                                                                 |                  | Min     | Max | Min     | Max |               |
| Enable Cycle Time                                               | $t_{cycE}$       | 0.666   | —   | 0.50    | —   | $\mu\text{s}$ |
| Enable Pulse Width, High                                        | $PW_{EH}$        | 0.28    | 25  | 0.22    | 25  | $\mu\text{s}$ |
| Enable Pulse Width, Low                                         | $PW_{EL}$        | 0.28    | —   | 0.21    | —   | $\mu\text{s}$ |
| Setup Time, Address and R/W Valid to Enable positive transition | $t_{AS}$         | 140     | —   | 70      | —   | ns            |
| Data Delay Time                                                 | $t_{DDR}$        | —       | 220 | —       | 180 | ns            |
| Data Hold Time                                                  | $t_H$            | 10      | —   | 10      | —   | ns            |
| Address Hold Time                                               | $t_{AH}$         | 10      | —   | 10      | —   | ns            |
| Rise and Fall Time for Enable input                             | $t_{Er}, t_{Ef}$ | —       | 25  | —       | 25  | ns            |

### **WRITE**

|                                                                 |                  |       |    |      |    |               |
|-----------------------------------------------------------------|------------------|-------|----|------|----|---------------|
| Enable Cycle Time                                               | $t_{cycE}$       | 0.666 | —  | 0.50 | —  | $\mu\text{s}$ |
| Enable Pulse Width, High                                        | $PW_{EH}$        | 0.28  | 25 | 0.22 | 25 | $\mu\text{s}$ |
| Enable Pulse Width, Low                                         | $PW_{EL}$        | 0.28  | —  | 0.21 | —  | $\mu\text{s}$ |
| Setup Time, Address and R/W Valid to Enable positive transition | $t_{AS}$         | 140   | —  | 70   | —  | ns            |
| Data Setup Time                                                 | $t_{DSW}$        | 80    | —  | 60   | —  | ns            |
| Data Hold Time                                                  | $t_H$            | 10    | —  | 10   | —  | ns            |
| Address Hold Time                                               | $t_{AH}$         | 10    | —  | 10   | —  | ns            |
| Rise and Fall Time for Enable input                             | $t_{Er}, t_{Ef}$ | —     | 25 | —    | 25 | ns            |



# RANDOM ACCESS MEMORY (RAM) MCM68A10 • MCM68B10

**DC CHARACTERISTICS** ( $V_{CC} = 5.0 \text{ V} \pm 5\%$ ,  $V_{SS} = 0$ ,  $T_A = 0 \text{ to } 70^\circ\text{C}$  unless otherwise noted.)

| Characteristic                                                                                                                                    | Symbol   | Min | Typ | Max | Unit               |
|---------------------------------------------------------------------------------------------------------------------------------------------------|----------|-----|-----|-----|--------------------|
| Input Current ( $I_{in}$ , R/W, $\overline{CS}_n$ , $\overline{CS}_n$ )<br>( $V_{in} = 0 \text{ to } 5.25 \text{ V}$ )                            | $I_{in}$ | —   | —   | 2.5 | $\mu\text{A}_{dc}$ |
| Output High Voltage<br>( $I_{OH} = -205 \mu\text{A}$ )                                                                                            | $V_{OH}$ | 2.4 | —   | —   | Vdc                |
| Output Low Voltage<br>( $I_{OL} = 1.6 \text{ mA}$ )                                                                                               | $V_{OL}$ | —   | —   | 0.4 | Vdc                |
| Output Leakage Current (Three-State)<br>( $CS = 0.8 \text{ V}$ or $\overline{CS} = 2.0 \text{ V}$ , $V_{out} = 0.4 \text{ V to } 2.4 \text{ V}$ ) | $I_{LO}$ | —   | —   | 10  | $\mu\text{A}_{dc}$ |
| Supply Current<br>( $V_{CC} = 5.25 \text{ V}$ , all other pins grounded, $T_A = 0^\circ\text{C}$ )                                                | $I_{CC}$ | —   | —   | 80  | $\text{mA}_{dc}$   |

## **AC CHARACTERISTICS**

**READ CYCLE** ( $V_{CC} = 5.0 \text{ V} \pm 5\%$ ,  $V_{SS} = 0$ ,  $T_A = 0 \text{ to } 70^\circ\text{C}$  unless otherwise noted.)

| Characteristic            | Symbol       | MCM68A10 |     | MCM68B10 |     | Unit |
|---------------------------|--------------|----------|-----|----------|-----|------|
|                           |              | Min      | Max | Min      | Max |      |
| Read Cycle Time           | $t_{cyc(R)}$ | 360      | —   | 250      | —   | ns   |
| Access Time               | $t_{acc}$    | —        | 360 | —        | 250 | ns   |
| Address Setup Time        | $t_{AS}$     | 20       | —   | 20       | —   | ns   |
| Address Hold Time         | $t_{AH}$     | 0        | —   | 0        | —   | ns   |
| Data Delay Time (Read)    | $t_{DDR}$    | —        | 220 | —        | 180 | ns   |
| Read to Select Delay Time | $t_{RCS}$    | 0        | —   | 0        | —   | ns   |
| Data Hold from Address    | $t_{DHA}$    | 10       | —   | 10       | —   | ns   |
| Output Hold Time          | $t_H$        | 10       | —   | 10       | —   | ns   |
| Data Hold from Write      | $t_{DHW}$    | 10       | 60  | 10       | 60  | ns   |

**WRITE CYCLE** ( $V_{CC} = 5.0 \text{ V} \pm 5\%$ ,  $V_{SS} = 0$ ,  $T_A = 0 \text{ to } 70^\circ\text{C}$  unless otherwise noted.)

| Characteristic                  | Symbol       | MCM68A10 |     | MCM68B10 |     | Unit |
|---------------------------------|--------------|----------|-----|----------|-----|------|
|                                 |              | Min      | Max | Min      | Max |      |
| Write Cycle Time                | $t_{cyc(W)}$ | 360      | —   | 250      | —   | ns   |
| Address Setup Time              | $t_{AS}$     | 20       | —   | 20       | —   | ns   |
| Address Hold Time               | $t_{AH}$     | 0        | —   | 0        | —   | ns   |
| Chip Select Pulse Width         | $t_{CS}$     | 250      | —   | 210      | —   | ns   |
| Write to Chip Select Delay Time | $t_{WCS}$    | 0        | —   | 0        | —   | ns   |
| Data Setup Time (Write)         | $t_{DSW}$    | 80       | —   | 60       | —   | ns   |
| Input Hold Time                 | $t_H$        | 10       | —   | 10       | —   | ns   |



**MOTOROLA Semiconductor Products Inc.**

3501 ED BLUESTEIN BLVD., AUSTIN, TEXAS 78721 • A SUBSIDIARY OF MOTOROLA INC.