


# LMBT3904LT1G

## General Purpose Transistors NPN Silicon


### 1. FEATURES

- We declare that the material of product compliance with RoHS requirements and Halogen Free.



### 2. DEVICE MARKING AND ORDERING INFORMATION

| Device       | Marking | Shipping        |
|--------------|---------|-----------------|
| LMBT3904LT1G | 1AM     | 3000/Tape&Reel  |
| LMBT3904LT3G | 1AM     | 13000/Tape&Reel |



### 3. MAXIMUM RATINGS(Ta = 25°C)

| Parameter                      | Symbol | Limits | Unit |
|--------------------------------|--------|--------|------|
| Collector–Emitter Voltage      | VCEO   | 40     | V    |
| Collector–Base Voltage         | VCBO   | 60     | V    |
| Emitter–Base Voltage           | VEBO   | 6      | V    |
| Collector Current — Continuous | IC     | 200    | mA   |

### 4. THERMAL CHARACTERISTICS

| Parameter   | Symbol   | Limits     | Unit        |
|---|----------|------------|-------------|
| Total Device Dissipation,<br>FR-5 Board (Note 1) @ TA = 25°C<br>Derate above 25°C | PD       | 225<br>1.8 | mW<br>mW/°C |
| Thermal Resistance,<br>Junction–to–Ambient(Note 1)                                | RθJA     | 556        | °C/W        |
| Junction–to–Case(Note 1)  | RθJC     | 300        | °C/W        |
| Junction and Storage temperature  | TJ, Tstg | -55~+150   | °C          |

1. FR-5 = 1.0×0.75×0.062 in.

## 5. ELECTRICAL CHARACTERISTICS (Ta= 25°C)

### OFF CHARACTERISTICS

| Characteristic   | Symbol   | Min. | Typ. | Max. | Unit |
|--|----------|------|------|------|------|
| Collector–Emitter Breakdown Voltage<br>(IC = 1.0 mA, IB = 0) | VBR(CEO) | 40   | -    | -    | V    |
| Collector–Base Breakdown Voltage<br>(IC = 10 μA, IE = 0)     | VBR(CBO) | 60   | -    | -    | V    |
| Emitter–Base Breakdown Voltage<br>(IE = 10 μA, IC = 0)       | VBR(EBO) | 6    | -    | -    | V    |
| Collector Cutoff Current<br>( VCE = 30 V, VEB = 3.0V)        | ICEX     | -    | -    | 50   | nA   |
| Base Cutoff Current<br>(VCE = 30 Vdc, VEB = 3.0Vdc)          | IBL      | -    | -    | 50   | nA   |

### ON CHARACTERISTICS (Note 2.)

|   |          |                             |                       |                         |   |
|---|----------|-----------------------------|-----------------------|-------------------------|---|
| DC Current Gain<br>(IC = 0.1 mA, VCE = 1.0 V)<br>(IC = 1.0 mA, VCE = 1.0 V)<br>(IC = 10 mA, VCE = 1.0 V)<br>(IC = 50 mA, VCE = 1.0 V)<br>(IC = 100 mA, VCE = 1.0 V) | HFE      | 40<br>70<br>100<br>60<br>30 | -<br>-<br>-<br>-<br>- | -<br>-<br>300<br>-<br>- |   |
| Collector–Emitter Saturation Voltage<br>(IC = 10 mA, IB = 1.0 mA)<br>(IC = 50 mA, IB = 5.0 mA)  | VCE(sat) | -<br>-                      | -<br>-                | 0.2<br>0.3              | V |
| Base–Emitter Saturation Voltage<br>(IC = 10 mA, IB = 1.0 mA)<br>(IC = 50 mA, IB = 5.0 mA)   | VBE(sat) | -<br>-                      | -<br>-                | 0.85<br>0.95            | V |

### SMALL–SIGNAL CHARACTERISTICS





|   |      |     |   |   |     |
|---|------|-----|---|---|-----|
| Current–Gain — Bandwidth Product<br>(IC = 10mA, VCE= 20V, f = 100MHz) | fT   | 300 | - | - | MHz |
| Output Capacitance<br>(VCB = 5.0 V, IE = 0, f = 1.0 MHz)              | Cobo | -   | - | 4 | pF  |
| Input Capacitance<br>(VEB = 0.5 V, IC = 0, f = 1.0 MHz)               | Cibo | -   | - | 8 | pF  |

### SWITCHING CHARACTERISTICS




|              |  |    |   |   |     |    |
|--------------|--|----|---|---|-----|----|
| Delay Time   | (VCC = 3.0 V, VBE=-0.5V,<br>IC = 10mA, IB1 = 1.0 mA) | td | - | - | 35  | ns |
| Rise Time    |  | tr | - | - | 35  |    |
| Storage Time | (VCC = 3.0 V, IC = 10<br>mA, IB1 = IB2 = 1.0 mA)     | ts | - | - | 200 |    |
| Fall Time    |  | tf | - | - | 50  |    |

2.Pulse Test: Pulse Width ≤300 μs, Duty Cycle ≤2.0%.




### 6. ELECTRICAL CHARACTERISTICS CURVES




### 6. ELECTRICAL CHARACTERISTICS CURVES(Con.)



### 7.OUTLINE AND DIMENSIONS



SECTION B-B




| SOT23                |         |      |      |
|----------------------|---------|------|------|
| DIM                  | MIN     | NOR  | MAX  |
| A                    | 0.89    | -    | 1.12 |
| A1                   | 0.01    | -    | 0.10 |
| A2                   | 0.88    | 0.95 | 1.02 |
| b                    | 0.30    | -    | 0.50 |
| b1                   | 0.30    | 0.40 | 0.45 |
| c                    | 0.08    | -    | 0.20 |
| c1                   | 0.08    | 0.10 | 0.16 |
| D                    | 2.80    | 2.90 | 3.04 |
| E                    | 2.10    | -    | 2.64 |
| E1                   | 1.20    | 1.30 | 1.40 |
| e                    | 0.95BSC |      |      |
| e1                   | 1.90BSC |      |      |
| L                    | 0.40    | 0.46 | 0.60 |
| L1                   | 0.54REF |      |      |
| θ                    | 0°      | -    | 8°   |
| All Dimensions in mm |         |      |      |

#### GENERAL NOTES

1. Top package surface finish Ra0.4±0.2um
2. Bottom package surface finish Ra0.7±0.2um
3. Side package surface finish Ra0.4±0.2um

### 8.SOLDERING FOOTPRINT



| SOT-23 |      |
|--------|------|
| DIM    | (mm) |
| X      | 0.80 |
| Y      | 0.90 |
| A      | 2.00 |
| B      | 0.95 |
| C      | 0.95 |

## **DISCLAIMER**

- Curve guarantee in the specification. The curve of test items with electric parameter is used as quality guarantee. The curve of test items without electric parameter is used as reference only.
- Before you use our Products for new Project, you are requested to carefully read this document and fully understand its contents. LRC shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any LRC's Products against warning, caution or note contained in this document.
- All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using LRC's Products, please confirm the latest information with a LRC sales representative.