


Single N-Channel Logic Level Enhancement Mode Field Effect Transistor

•Product Summary:

	N-CH
BVDSS	30V
$R_{DS(ON)(MAX.)}@V_{GS}=10V$	20.0m Ω
$R_{DS(ON)(MAX.)}@V_{GS}=4.5V$	30.0m Ω
$I_D @T_C=25^\circ C$	22.0A
$I_D @T_A=25^\circ C$	8.0A

• Pin Description:



Single N Channel MOSFET

UIS, Rg 100% Tested

Pb-Free Lead Plating & Halogen Free

•ABSOLUTE MAXIMUM RATINGS ($T_C = 25^\circ C$ Unless Otherwise Noted)



PARAMETERS/TEST CONDITIONS	SYMBOL	LIMITS	UNIT
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current	I_D	$T_C = 25^\circ C$	22
		$T_C = 100^\circ C$	14
Continuous Drain Current	I_D	$T_A = 25^\circ C$	8.5
		$T_A = 70^\circ C$	7
Pulsed Drain Current ¹	I_{DM}	75	A
Avalanche Current	I_{AS}	19	
Avalanche Energy	E_{AS}	309	
Repetitive Avalanche Energy ²	E_{AR}	154	
Power Dissipation	P_D	$T_C = 25^\circ C$	62.5
		$T_C = 100^\circ C$	25
Power Dissipation	P_D	$T_A = 25^\circ C$	8
		$T_A = 70^\circ C$	6
Operating Junction & Storage Temperature Range	T_j, T_{stg}	-55 to 150	$^\circ C$

•THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNIT
Junction-to-Case	$R_{\theta JC}$		2	$^\circ C/W$
Junction-to-Ambient ³	$R_{\theta JA}$		60	

¹Pulse width limited by maximum junction temperature.

²Duty cycle < 1%

³60 $^\circ C$ / W when mounted on a 1 in² pad of 2 oz copper.

⁴Guarantee by Engineering test

▪ CH-1_ELECTRICAL CHARACTERISTICS (T_j = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage ⁴	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250uA	30			V
Gate Threshold Voltage ⁴	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250uA	1.2	1.6	2.5	
Gate-Body Leakage ⁴	I _{GSS}	V _{DS} = 0V, V _{GS} = ±20V			±100	nA
Zero Gate Voltage Drain Current ⁴	I _{DSS}	V _{DS} = 24V, V _{GS} = 0V			1	uA
		V _{DS} = 20V, V _{GS} = 0V, T _j = 125 °C			25	
On-State Drain Current ¹	I _{D(ON)}	V _{DS} = 10V, V _{GS} = 10V	22			A
Drain-Source On-State Resistance ^{1,4}	R _{DS(ON)}	V _{GS} = 10V, I _D = 8A		15.5	20	mΩ
		V _{GS} = 4.5V, I _D = 6A		25	30	
DYNAMIC						
Input Capacitance ⁵	C _{iss}	V _{GS} = 0V, V _{DS} = 15V, f = 1MHz		520		pF
Output Capacitance ⁵	C _{oss}			88		
Reverse Transfer Capacitance ⁵	C _{rss}			62		
Gate Resistance ^{4,5}	R _g	f = 1MHz		2		Ω
Total Gate Charge ^{1,2,5}	Q _g (V _{GS} =10V)	V _{DS} = 15V, V _{GS} = 10V, I _D = 8A		11.5		nC
	Q _g (V _{GS} =4.5V)			5		
Gate-Source Charge ^{1,2,5}	Q _{gs}			1.6		
Gate-Drain Charge ^{1,2,5}	Q _{gd}			2.8		
Turn-On Delay Time ^{1,2,5}	t _{d(on)}	V _{DS} = 15V, V _{GS} = 10V, I _D = 1A, R _g = 6Ω		5		nS
Rise Time ^{1,2,5}	t _r			3		
Turn-Off Delay Time ^{1,2,5}	t _{d(off)}			15		
Fall Time ^{1,2,5}	t _f			11		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS						
Continuous Current	I _S				22	A
Pulsed Current ³	I _{SM}				75	
Forward Voltage ^{1,4}	V _{SD}	I _F = I _S , V _{GS} = 0V			1.2	V
Reverse Recovery Time ⁵	t _{rr}	IF=20A, dIF/dt = 400A / mS		8.2		nS
Reverse Recovery Charge ⁵	Q _{rr}				10.5	

¹Pulse test : Pulse Width ≤ 300 usec, Duty Cycle ≤ 2%.

²Independent of operating temperature.

³Pulse width limited by maximum junction temperature.

⁴Guarantee by FT test Item

⁵Guarantee by Engineering test

EMC will review datasheet by quarter, and update new version.

▪ TYPICAL CHARACTERISTICS




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance Variation with Drain Current and Gate Voltage




Fig.3 Normalized On-Resistance v.s. Junction Temperature




Fig.4 On-Resistance v.s. Gate Voltage




Fig.5 Forward Characteristic of Reverse Diode




Fig.6 Transfer Characteristics




Fig.7 Gate Charge Characteristics




Fig.8 Typical Capacitance Characteristics




Fig.9. Maximum Safe Operating Area




Fig.10. Single Pulse Maximum Power Dissipation




Fig.11. Effective Transient Thermal Impedance

Ordering & Marking Information:

Device Name: EMB20N03V for EDFN 3x3



B20N03: Device Name

ABCDEFGG: Date Code


A: Assembly House

B: Year(A:2008 B:2009 C:2010....)

C: Month(A:01 B:02 C:03 D:04 E:05 F:06 G:07 H:08 I:09 J:10 K:11 L:12)


DEFG: Serial No.

Outline Drawing




Dimension	A	A1	b	c	D	D1	E	E1	E2	e	L	L1	θ1
Min.	0.65	0	0.2	0.1	2.9	2.15	3.1	2.9	1.53	0.55	0.25	-	0°
Typ.	0.75	-	0.3	0.15	3	2.45	3.2	3	1.97	0.65	0.4	0.075	10°
Max.	0.9	0.05	0.4	0.25	3.3	2.74	3.5	3.3	2.59	0.75	0.6	0.15	14°

Footprint



◆ Tape&Reel Information:5000pcs/Reel



產品別	EDFN3X3
Reel 尺寸	13"
編帶方式	<p>FEED DIRECTION</p>

Dimension in mm

Dimension	Carrier tape									Reel	
	A0	B0	D0	E	K0	P0	P1	P2	W	R	R1
Typ.	3.6	3.5	1.55	1.7	1.2	4	8	2	12	14	330
±	0.3	0.3	0.2	0.2	0.2	0.1	0.1	0.1	1	2	2