



MMBD301/MMBD452

SURFACE MOUNT SCHOTTKY DIODE

VOLTAGE 30 Volts **POWER** 200mWatts


SOT-23 Unit: inch (mm)

FEATURES

- Low Capacitance : 1.5pF(Max)at $V_R=15V$
- Very Low V_F : 0.36V (Typ) at $I_F = 1mA$
- Extremely Fast Switching Speed
- Lead free in comply with EU RoHS 2011/65/EU directives.
- Green molding compound as per IEC61249 Std. . (Halogen Free)

MECHANICAL DATA

- Case: SOT-23 plastic case.
- Terminals : Solderable per MIL-STD-750,Method 2026
- Standard packaging: 8mm tape
- Weight: approximately 0.0084gram



ABSOLUTE RATINGS AND THERMAL CHARACTERISTICS

Parameter	Symbol	MMBD301	MMBD452	Units
Marking Code	-	301	452	-
Maximum Reverse Voltage	V_R	30		V
Peak Reverse Voltage	V_{RRM}	30		V
Maximum Forward Current	I_F	0.2		A
Power Dissipation(Note 1)	P_{TOT}	200		mW
Thermal Resistance , Junction to Ambient (Note 1)	$R_{\theta JA}$	556		°C/W
Junction Temperature Range	T_J	-55 to +125		°C
Storage Temperature Range	T_{STG}	-55 to +150		°C
Circuit Figure	-	SINGLE	SERIES	-

NOTE:

1. FR-4 Board = 70 X 60 X 1mm.




Fig.14




Fig.17



MMBD301/MMBD452

ELECTRICAL CHARACTERISTICS (T_J=25°C unless otherwise noted)

PARAMETER	SYMBOL	Test Condition	MIN.	TYP.	MAX.	UNIT
Reverse Breakdown Voltage	V _(BR)	I _R =10μA	30			V
Reverse Leakage Current	I _R	V _R =25V			0.2	μA
Forward Voltage	V _F	I _F =1.0mA			0.45	V
Forward Voltage	V _F	I _F =10mA			0.6	V
Total Capacitance	C _J	V _R =15V, f=1.0MHz			1.5	pF

RATING AND CHARACTERISTIC CURVES




Fig.1 TYPICAL REVERSE CHARACTERISTICS




Fig.2-TYPICAL FORWARD CHARACTERISTICS





Fig.3 TYPICAL TOTAL CAPACITANCE



MMBD301/MMBD452

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
 - T/R - 12K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel



MMBD301/MMBD452

Part No_packing code_Version

MMBD301_R1_00001

MMBD301_R2_00001

For example :

RB500V-40_R2_00001



Packing Code XX				Version Code XXXXX		
Packing type	1 st Code	Packing size code	2 nd Code	HF or RoHS	1 st Code	2 nd ~5 th Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			



MMBD301/MMBD452

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.