

SS10PU80

Product profile

High Current Density Surface Mount Ultra Low VF

Schottky Rectifier

General description

Rectifiers 10 Amp 80V

Features

Very low profile - typical height of 1.1 mm

Ideal for automated placement

Low forward voltage drop, low power losses

High efficiency

Low thermal resistance

Meets MSL level 1, per J-STD-020

Solder dip 260 °C max. 10 s, per JESD 22-A111



Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC

Mechanical data

Case: Conform to JEDEC TO-277A; Suffix /A

Industry TO-277B; Suffix /B

Molding compound meets UL 94 V-0 flammability



NO	Dimensions	NO	Dimensions
A	1.20±0.1	e	1.84Typ
A2	0.25±0.05	E1	5.3±0.1
b1	0.9±0.1	E2	3.3±0.2
D	3.95±0.1	L	0.6±0.1
D2	3.00Typ	L1	0.6±0.1
E	6.5±0.1	W	1.3±0.2
		W1	0.8±0.15

All Dimensions in mm



Maximum Ratings (Tc=25°C unless otherwise noted)

Parameter	Symbol	SS10PU80	Unit
Maximum repetitive peak reverse voltage	VRRM	80	V
RMS Voltage (Max.)	VRMS	56	V
Working peak reverse voltage	VRWM	80	V
Maximum average forward rectified current	IF(AV)	10	A
Peak forward surge current	IFSM	160	A
8.3ms single half sine-wave superimposed on rated load (JEDEC Method)			
Operating junction temperature range	TJ	-55 to +150	°C
Storage temperature range	TSTG	-55 to +150	°C

SS10PU80

THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Unit
Typical thermal resistance	R θ JC	3	°C/W

- Notes: (1) Pulse test: 300 μ s pulse width, 1 % duty cycle
 (2) Pulse test: Pulse width \leq 40

Electrical characteristics (Tc=25°C unless otherwise noted)

OFF CHARACTERISTICS





Parameter	Symbol	Value		Unit
		Typical	Max	
Instantaneous forward voltage at IF=5A, Tj=25°C at IF=10A, Tj=25°C at IF=5A, Tj=125°C at IF=10A, Tj=125°C	VF	0.51	0.55	V
		0.61	0.66	
		0.44	0.47	
		0.56	0.61	
Maximum reverse current Tj=25°C	IR	50		u'A
at working peak reverse voltage Tj=125°C		30		m'A

DEVICE MARK

SS10PU80

SS10PU80

■ Characteristic Curves



SS10PU80

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Bruckewell Technology Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Bruckewell"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Bruckewell makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Bruckewell disclaims

- (i) Any and all liability arising out of the application or use of any product.
- (ii) Any and all liability, including without limitation special, consequential or incidental damages.
- (iii) Any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Bruckewell's knowledge of typical requirements that are often placed on Bruckewell products in generic applications.

Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time.

Product specifications do not expand or otherwise modify Bruckewell's terms and conditions of purchase, including but not limited to the warranty expressed therein.