


**RB501V-40**

Preliminary


DIODE**SURFACE MOUNT SCHOTTKY
DIODE****DESCRIPTION**

The UTC **RB501V-40** is a surface mount schottky diode, it uses UTC's advanced technology to provide the customers with high switching speed and low forward voltage, etc.

The UTC **RB501V-40** is suitable for automatic insertion, etc.

**FEATURES**


- * High switching speed
- * Low forward voltage

SYMBOL**ORDERING INFORMATION**

Ordering Number	Package	Pin Assignment		Packing
		1	2	
RB501VG-40-CB2-R	SOD-323	A	K	Tape Reel

Note: Pin Assignment: A: Anode K: Cathode

RB501VG-40-CB2-R (1) Packing Type (2) Package Type (3) Green Package	(1) R: Tape Reel (2) CB2: SOD-323 (3) G: Halogen Free and Lead Free
--	--

MARKING

■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
Maximum Reverse Voltage	V_{RRM}	40	V
RMS Reverse Voltage	$V_{R(RMS)}$	30	V
Maximum Forward Current	$I_{F(AV)}$	0.1	A
Maximum Forward Peak Current (f=60Hz)	I_{FPM}	1	A
Power Dissipation (Note 2)	P_D	0.4	W
Peak Forward Surge Current at t=8.3ms	I_{FSM}	500	mA
Junction Temperature	T_J	-55~+125	°C
Storage Temperature	T_{STG}	-55~+125	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. FR-5 board=1.0*0.75*0.062 in. Minimum pad layout.

■ THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient (Note 2)	θ_{JA}	300	°C/W

■ ELECTRICAL CHARACTERISTICS ($T_J=25^\circ\text{C}$, unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Reverse Leakage Current	I_R	$V_R=10\text{V}$			10	μA
Forward Voltage	V_F	$I_F=10\text{mA}$			0.34	V
		$I_F=100\text{mA}$			0.55	V
Total Capacitance	C_T	$V_R=10\text{V}$, f=1MHz		6		pF

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.