

## Standard SCRs, 55A

### Main Features


Symbol	Value	Unit
$I_{T(RMS)}$	55	A
$V_{DRM}/V_{RRM}$	600 to 1600	V
$I_{GT}$	80	mA

### DESCRIPTION

The 55PT series of silicon controlled rectifiers are high performance glass passivated technology, and are suitable for general purpose applications, where power handling and power dissipation are critical, such as solid state relay, welding equipment and high power motor control.

Base on a clip assembly technology, they offer a superior performance in surge current capabilities.

Thanks to their internal ceramic pad, they provide high voltage insulation(2500V<sub>RMS</sub>).



ABSOLUTE MAXIMUM RATINGS					
PARAMETER	SYMBOL	TEST CONDITIONS		VALUE	UNIT
RMS on-state current full sine wave (180° conduction angle)	$I_{T(RMS)}$	TO-3P/TO-247AB	$T_c=85^\circ\text{C}$	55	A
		TO-220AB/TO-263	$T_c=80^\circ\text{C}$		
		TO-220AB insulated/TO-3P insulated	$T_c=70^\circ\text{C}$		
Average on-state current (180° conduction angle)	$I_{T(AV)}$	TO-3P/TO-247AB	$T_c=85^\circ\text{C}$	35	A
		TO-220AB/TO-263	$T_c=80^\circ\text{C}$		
		TO-220AB insulated/TO-3P insulated	$T_c=70^\circ\text{C}$		
Non repetitive surge peak on-state current (full cycle, $T_j$ initial = 25°C)	$I_{TSM}$	F = 50 Hz	t = 20 ms	520	A
		F = 60 Hz	t = 16.7 ms	540	
$I^2t$ Value for fusing	$i^2t$	$t_p = 10$ ms		1352	A <sup>2</sup> s
Critical rate of rise of on-state current $V_D = 67\% V_{DRM}$ , $t_p = 200\mu\text{s}$ , $I_G = 0.3A$ $dI_G/dt = 0.3A/\mu\text{s}$	dI/dt	F = 60 Hz	$T_j = 125^\circ\text{C}$	150	A/ $\mu\text{s}$
Peak gate current	$I_{GM}$	$T_p = 20 \mu\text{s}$	$T_j = 125^\circ\text{C}$	5	A
Maximum gate power	$P_{GM}$	$T_p = 20\mu\text{s}$	$T_j = 125^\circ\text{C}$	10	W
Average gate power dissipation	$P_{G(AV)}$	$T_j = 125^\circ\text{C}$		2	W
Repetitive peak off-state voltage	$V_{DRM}$	$T_j = 125^\circ\text{C}$		600 to 1600	V
Repetitive peak reverse voltage	$V_{RRM}$				
Storage temperature range	$T_{stg}$			- 40 to + 150	°C
Operating junction temperature range	$T_j$			- 40 to + 125	
Maximum peak reverse gate voltage	$V_{RGM}$			5	V

ELECTRICAL SPECIFICATIONS (T <sub>j</sub> = 25 °C unless otherwise specified)								
SYMBOL	TEST CONDITIONS			55PT06xx	55PT10xx	55PT16xx	Unit	
				55PT08xx	55PT12xx			
I <sub>GT</sub>	V <sub>D</sub> = 12V, R <sub>L</sub> = 33Ω			Max.	30	40	80	mA
V <sub>GT</sub>				Max.	1.5			V
V <sub>GD</sub>	V <sub>D</sub> = V <sub>DRM</sub> , R <sub>L</sub> = 3.3KΩ, R <sub>GK</sub> = 220Ω	T <sub>j</sub> = 125°C	Min.	0.2			V	
I <sub>H</sub>	I <sub>T</sub> = 500mA, Gate open			Max.	80	100	120	mA
I <sub>L</sub>	I <sub>G</sub> = 1.2×I <sub>GT</sub>			Max.	100	130	150	mA
dV/dt	V <sub>D</sub> = 67% V <sub>DRM</sub> , Gate open	T <sub>j</sub> = 125°C	Min.	700	1000	1000	V/μs	
V <sub>TM</sub>	I <sub>T</sub> = 80A, t <sub>p</sub> = 380μs	T <sub>j</sub> = 25°C	Max.	1.6			V	
I <sub>DRM</sub> I <sub>RPM</sub>	V <sub>D</sub> = V <sub>DRM</sub> , V <sub>R</sub> = V <sub>RPM</sub> R <sub>GK</sub> = 220Ω	T <sub>j</sub> = 25°C	Max.	10			μA	
		T <sub>j</sub> = 125°C	Max.	6			mA	
V <sub>to</sub>	Threshold Voltage		T <sub>j</sub> = 125°C	Max.	1.02		V	
R <sub>d</sub>	Dynamic Resistance		T <sub>j</sub> = 125°C	Max.	85		mΩ	

THERMAL RESISTANCE						
SYMBOL	Parameter			VALUE	UNIT	
R <sub>th(j-c)</sub>	Junction to case (DC)			D <sup>2</sup> PAK/TO-220AB/TO-3P/TO-247AB	0.8	°C/W
				TO-220AB insulated/TO-3P insulated	0.9	
R <sub>th(j-a)</sub>	S = 1 cm <sup>2</sup> Junction to ambient			TO-263(D <sup>2</sup> PAK)	45	°C/W
				TO-220AB/TO-220AB insulated	60	
				TO-3P/TO-247AB/TO-3P insulated	50	

S=Copper surface under tab

PRODUCT SELECTOR							
PART NUMBER	VOLTAGE (xx)					SENSITIVITY	PACKAGE
	600 V	800 V	1000 V	1200 V	1600 V		
55PTxxA/55PTxxAI	V	V	V	V	V	80 mA	TO-220AB
55PTxxH	V	V	V	V	V	80 mA	D <sup>2</sup> PAK
55PTxxB/55PTxxBI	V	V	V	V	V	80 mA	TO-3P
55PTxxC	V	V	V	V	V	80 mA	TO-247AB

ORDERING INFORMATION					
ORDERING TYPE	MARKING	PACKAGE	WEIGHT	BASE Q'TY	DELIVERY MODE
55PTxxA	55PTxxA	TO-220AB	2.0g	50	Tube
55PTxxAI	55PTxxAI	TO-220AB (insulated)	2.3g	50	Tube
55PTxxH	55PTxxH	TO-263(D <sup>2</sup> PAK)	2.0g	50	Tube
55PTxxB	55PTxxB	TO-3P	4.3g	30	Tube
55PTxxBI	55PTxxBI	TO-3P insulated	4.8g	30	Tube
55PTxxC	55PTxxC	TO-247AB	5g	30	Tube

Note: xx = voltage

## ORDERING INFORMATION SCHEME

55 PT 06 AI

### Current

55 = 55A,  $I_{T(RMS)}$

### SCR series


### Voltage Code

06 = 600V  
 08 = 800V  
 10 = 1000V  
 12 = 1200V  
 16 = 1600V


### Package type

A = TO-220AB (non-insulated)  
 AI = TO-220AB (insulated)  
 B = TO-3P (non-insulated)  
 BI = TO-3P (insulated)  
 C = TO-247AB  
 H = TO-263 (D<sup>2</sup>PAK)


**Fig.1 Maximum power dissipation versus average on-state current (half cycle)**




**Fig.3 On-state characteristics (maximum values).**




**Fig.2 RMS on-state current versus case temperature (full cycle)**




**Fig.4 Surge peak on-state current versus number of cycles.**




**Fig.5 Non-repetitive surge peak on-state current for a sinusoidal pulse with width  $t_p < 10$  ms, and corresponding value of  $I^2t$ .**




**Fig.6 Relative variations of gate trigger current, holding current and latching current versus junction temperature (typical values)**



## Case Style




All dimensions in millimeters(inches)




## Case Style



**TO-3P**



**TO-263(D<sup>2</sup>PAK)**



**TO-247AB**



All dimensions in millimeters(inches)