

2SK556, 2SK557


HITACHI/(OPTOELECTRONICS)

SILICON N-CHANNEL MOS FET

HIGH SPEED POWER SWITCHING


■ FEATURES

- Low On-Resistance.
- High Speed Switching.
- Low Drive Current.
- No Secondary Breakdown.
- Suitable for Switching Regulator, DC-DC Converter, Motor Controls, and Ultrasonic Power Oscillators.




1. Gate
2. Drain (Flange)
3. Source

(Dimensions in mm)



(TO-3P)

POWER VS. TEMPERATURE DERATING



■ ABSOLUTE MAXIMUM RATINGS ($T_c=25^\circ\text{C}$)

Item	Symbol	2SK556	2SK557	Unit
Drain-Source Voltage	V_{DS}	450	500	V
Gate-Source Voltage	V_{GS}	± 20		V
Drain Current	I_D	12		A
Drain Peak Current	$I_{D(\text{pulse})}^*$	48		A
Body-Drain Diode Reverse Drain Current	I_{DR}	12		A
Channel Dissipation	P_{ch}^*	100		W
Channel Temperature	T_{ch}	150		$^\circ\text{C}$
Storage Temperature	T_{stg}	$-55 \sim +150$		$^\circ\text{C}$


 $^*PW \leq 10\mu\text{s}$, duty cycle $\leq 1\%$
 ** Value at $T_c=25^\circ\text{C}$

■ ELECTRICAL CHARACTERISTICS ($T_c=25^\circ\text{C}$)


Item	Symbol	Test Condition	min.	typ.	max.	Unit
Drain-Source Breakdown Voltage	$V_{(BR)DS}$	$I_D=10\text{mA}$, $V_{GS}=0$	450	—	—	V
			500	—	—	
Gate-Source Breakdown Voltage	$V_{(BR)GS}$	$I_G=\pm 100\mu\text{A}$, $V_{DS}=0$	± 20	—	—	V
Gate-Source Leak Current	I_{GS}	$V_{GS}=\pm 16\text{V}$, $V_{DS}=0$	—	—	± 10	μA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=360\text{V}$, $V_{GS}=0$	—	—	250	μA
		$V_{DS}=400\text{V}$, $V_{GS}=0$	—	—	—	
Gate-Source Cutoff Voltage	$V_{GS(off)}$	$I_D=1\text{mA}$, $V_{DS}=10\text{V}$	2.0	—	4.0	V
Static Drain-Source On State Resistance	$R_{DS(on)}$	$I_D=6\text{A}$, $V_{GS}=10\text{V}^*$	—	0.4	0.55	Ω
			—	0.45	0.60	
Forward Transfer Admittance	$ y_{fs} $	$I_D=6\text{A}$, $V_{DS}=10\text{V}^*$	6	10	—	S
Input Capacitance	C_{iss}	$V_{DS}=10\text{V}$, $V_{GS}=0$, $f=1\text{MHz}$	—	2050	—	pF
Output Capacitance	C_{oss}		—	720	—	pF
Reverse Transfer Capacitance	C_{rss}		—	80	—	pF
Turn-on Delay Time	t_{don}	$I_D=6\text{A}$, $V_{GS}=10\text{V}$, $R_L=5\Omega$	—	25	—	ns
Rise Time	t_r		—	85	—	ns
Turn-off Delay Time	t_{doff}		—	145	—	ns
Fall Time	t_f		—	85	—	ns
Body-Drain Diode Forward Voltage	V_{DF}	$I_F=12\text{A}$, $V_{GS}=0$	—	1.0	—	V
Body-Drain Diode Reverse Recovery Time	t_{rr}	$I_F=12\text{A}$, $V_{GS}=0$, $di_F/dt=100\text{A}/\mu\text{s}$	—	450	—	ns

 * Pulse Test


MAXIMUM SAFE OPERATION AREA




TYPICAL OUTPUT CHARACTERISTICS




TYPICAL TRANSFER CHARACTERISTICS




DRAIN-SOURCE SATURATION VOLTAGE VS. GATE-SOURCE VOLTAGE




STATIC DRAIN-SOURCE ON STATE RESISTANCE VS. DRAIN CURRENT




STATIC DRAIN-SOURCE ON STATE RESISTANCE VS. TEMPERATURE




**FORWARD TRANSFER ADMITTANCE
VS. DRAIN CURRENT**




**FORWARD TRANSFER ADMITTANCE
VS. FREQUENCY**




**TYPICAL CAPACITANCE VS.
DRAIN-SOURCE VOLTAGE**




DYNAMIC INPUT CHARACTERISTICS



SWITCHING CHARACTERISTICS




**REVERSE DRAIN CURRENT VS.
SOURCE - DRAIN VOLTAGE**




2SK556, 2SK557

HITACHI/(OPTOELECTRONICS)

**NORMALIZED TRANSIENT THERMAL
IMPEDANCE VS. PULSE WIDTH**



SWITCHING TIME TEST CIRCUIT



WAVEFORMS

